

Composite and S-Video to VGA Video Scan Converter - TAA

Product ID: VID2VGATV2



The VID2VGATV2 Composite and S-Video to VGA Video Scan Converter (with Scaler) provides a simple way to convert Composite or S-Video signals to VGA (or Component RCA) output, for use with computer monitors, projectors or HDTV sets.

Equipped with an On-Screen Display (OSD) menu and dip switches for simple configuration and selection of your video output settings, this compact video scaler installs quickly and easily for a true plug-and-play experience. An integrated scaler circuit dynamically converts the S-Video or Composite video input signal, giving you multiple output resolutions to choose from, to ensure compatibility with your display or projector.

Plus, the Component/S-Video-VGA Converter includes a VGA to Component (RCA) breakout cable, which enables you to connect to TV sets that are not equipped with a VGA port.

Backed by a StarTech.com 2-year warranty and free lifetime technical support.

Certifications, Reports and Compatibility



Applications

- Perfect for displaying video from DVD players, VCRs or legacy Game Consoles on VGA projectors and HDTV sets
- Display camcorder output on televisions or monitors equipped with VGA input
- Monitor security cameras with S-Video or composite signaling using VGA monitors or televisions

- Adapt VHS video in the classroom to newer televisions
- Convert legacy Medical Imaging equipment for display on computer monitors
- Use in boardrooms for adapting legacy video equipment to work with new projectors

Features

- Convert and scale Composite/S-Video input to VGA/Component output
- Accepts NTSC and PAL input
- On-Screen Display for simple output setting selection
- VGA to Component (YPbPr) RCA Adapter included
- 50 Hz to 60 Hz frame rate conversion
- Plug & Play installation - no drivers or software required

Hardware

Warranty	2 Years
Active or Passive Adapter	Active
AV Input	S-Video
	Composite
AV Output	VGA
	Component
Audio	No

Performance

Supported Resolutions	PC: 1600x1200, 1280x1024, 1024x768 HDTV: 480p (50/60Hz), 576p (50Hz), 720p (50/60Hz), 1080p (50/60Hz)
Signal Levels	Input Video @ 1V p-p, 75 ohm Y @ 1 V p-p, 75 ohm Color @ 0.7V p-p, 75 ohm

Connector(s)

Connector A	1 - Composite Video (1 x RCA) 1 - S-Video (4 pin, Mini-DIN)
Connector B	1 - VGA (15 pin, High Density D-Sub)

Indicators

LED Indicators	1 - Composite (Yellow) / S-Video (Red) input indicator
----------------	--

Power

Power Source	AC Adapter Included
Output Voltage	5 DC
Output Current	1A
Power Consumption (In Watts)	2.5

Environmental

Operating Temperature	0C to 40C (32F to 104F)
Storage Temperature	0C to 60C (32F to 140F)
Humidity	0~60% RH

Physical Characteristics

Color	Black
Material	Plastic
Product Length	4.4 in [11.2 cm]
Product Width	2.5 in [6.4 cm]
Product Height	1.0 in [2.6 cm]
Weight of Product	3.0 oz [86 g]

Packaging Information

Package Quantity	1
Package Length	8.3 in [21.0 cm]
Package Width	4.6 in [11.7 cm]

Package Height	2.4 in [6.2 cm]
Shipping (Package) Weight	15.7 oz [444.0 g]

What's in the Box

Included in Package	1 - Video Converter/Scaler
	1 - VGA to Component (RCA) breakout cable
	1 - Universal Power Adapter
	1 - Instruction Manual

Warranty Information

Warranty	2 Years
----------	---------

**Product appearance and specifications are subject to change without notice.*