OVERVIEW



1. 2x USB 3.2 Gen 1	8. Ethernet (RJ-45)
2. Headphone (3.5mm)	9. 2x USB 2.0
3. Microphone (3.5mm)	10. 3x Audio connectors
4. Power button	11. Optional ports on expansion cards *
5. 2x USB 2.0	12. Power connector
6. USB-C 3.2 Gen 2	13. Lighting switch
7. 2x USB 3.2 Gen 1	

Notes:

• Items with * are only available on selected models

PERFORMANCE

Processor

Processor Family

13th Generation Intel® Core $^{\rm \tiny M}$ i5 / i7 / i9 Processor

Processor**[1]

Processor Name	Cores	Threads	Base Frequency	Max Frequency	Cache	Memory Support	Processor Graphics
Core i5- 13400	10 (6 P-core + 4 E-core)	16	P-core 2.5GHz / E-core 1.8GHz	P-core 4.6GHz / E-core 3.3GHz	20MB	DDR5- 4800	Intel UHD Graphics 730
Core i5- 13400F	10 (6 P-core + 4 E-core)	16	P-core 2.5GHz / E-core 1.8GHz	P-core 4.6GHz / E-core 3.3GHz	20MB	DDR5- 4800	-
Core i5- 13600KF	14 (6 P-core + 8 E-core)	20	P-core 3.5GHz / E-core 2.6GHz	P-core 5.1GHz / E-core 3.9GHz	24MB	DDR5- 5600	-
Core i7- 13700	16 (8 P-core + 8 E-core)	24	P-core 2.1GHz / E- core 1.5GHz	Max Turbo up to 5.2GHz / P- core 5.1GHz / E-core 4.1GHz	30MB	DDR5- 5600	Intel UHD Graphics 770
Core i7- 13700F	16 (8 P-core + 8 E-core)	24	P-core 2.1GHz / E- core 1.5GHz	Max Turbo up to 5.2GHz / P- core 5.1GHz / E-core 4.1GHz	30MB	DDR5- 5600	-
Core i7- 13700K	16 (8 P-core + 8 E-core)	24	P-core 3.4GHz / E-core 2.5GHz	Max Turbo up to 5.4GHz / P-core 5.3GHz / E-core 4.2GHz	30MB	DDR5- 5600	Intel UHD Graphics 770
Core i7- 13700KF	16 (8 P-core + 8 E-core)	24	P-core 3.4GHz / E-core 2.5GHz	Max Turbo up to 5.4GHz / P-core 5.3GHz / E-core 4.2GHz	30MB	DDR5- 5600	-
Core i9- 13900	24 (8 P-core + 16 E-core)	32	P-core 2.0GHz / E-core 1.5GHz	Max Turbo up to 5.6GHz / P-core 5.2GHz / E-core 4.2GHz	36MB	DDR5- 5600	Intel UHD Graphics 770
Core i9- 13900F	24 (8 P-core + 16 E-core)	32	P-core 2.0GHz / E-core 1.5GHz	Max Turbo up to 5.6GHz / P-core 5.2GHz / E-core 4.2GHz	36MB	DDR5- 5600	-

Notes:

[1] Intel UHD Graphics in processor is disabled

Operating System

Operating System**

- Windows® 11 Pro
- Windows 11 Home
- Windows 11 Home Single Language

Graphics

Graphics**[1]

Graphics	Туре	Memory	Connector	Max Resolution	Key Features
NVIDIA® GeForce RTX™ 4060 Ti	Discrete	8G GDDR6	1x HDMI® 2.1 FRL, 3x DP 1.4a	7680*4320@60Hz(HDMI), 7680x4320@120Hz(DP)	DirectX® 12
AMD Radeon™ RX 6500XT	Discrete	4GB GDDR6	1x HDMI 2.1 FRL , 1x DP 1.4	7680x4320@60Hz(HDMI), 7680x4320@60Hz(DP)	DirectX 12, OpenGL 4.6
NVIDIA GeForce RTX 3050	Discrete	8GB GDDR6	1x HDMI 2.1 FRL, 3x DP 1.4	7680x4320@60Hz(HDMI), 7680x4320@120Hz(DP)	DirectX 12
NVIDIA GeForce RTX 3060	Discrete	12G GDDR6	3x DP 1.4a, 1x HDMI 2.1 FRL	7680x4320@60Hz(HDMI), 5120x2880@60Hz(DP)	DirectX 12
NVIDIA GeForce RTX 3060 Ti	Discrete	8G GDDR6	1x HDMI 2.1 FRL, 3x DP 1.4a	7680*4320@60Hz(HDMI), 7680x4320@120Hz(DP)	DirectX 12

Lenovo

NVIDIA GeForce RTX 4070	Discrete	12G GDDR6X	3x DP 1.4a, 1x HDMI 2.1 FRL	7680x4320@60Hz(HDMI); 7680x4320@120Hz(DP)	DirectX 12
NVIDIA GeForce RTX 4070 Ti	Discrete	12G GDDR6X	3x DP 1.4a, 1x HDMI 2.1 FRL	7680x4320@60Hz(HDMI); 7680x4320@120Hz(DP)	DirectX 12

Notes:

[1] The information of integrated graphics are not applicable for the models with processor which has no integrated graphics inside (for the details, please refer to processor section)

Monitor Support

Monitor Support

Supports up to 4 independent displays via discrete graphics ports (DP, HDMI)

Chipset

Chipset

Intel B660 chipset

Memory

Max Memory^[1]

Up to 64GB DDR5-5600

Memory Slots

Four DDR5 UDIMM slots, dual-channel capable

Memory Type**

- DDR5-4800
- DDR5-5600

Memory Protection

Non-ECC

Notes:

[1] The max memory is based on the test results with current Lenovo® memory offerings. The system may support more memory as the technology develops.

Storage

Storage Support^[1]

Up to five drives, 2x 3.5" HDD + 1x M.2 SSD + 1x open M.2 SSD + 1x open 2.5 HDD Bay

- 3.5" HDD up to 2TB each
- M.2 SSD up to 1TB each

Storage Type**

Disk Type	Interface	RPM
3.5" SATA HDD	SATA 6Gb/s	7.2K
M.2 2280 SSD	PCIe® NVMe®, PCIe 4.0 x4	-

RAID

No support

Notes:

[1] The max capacity of each disk type is based on the test results with current Lenovo storage offerings. The system may support larger storage as the technology develops

Removable Storage

Optical

None

Card Reader

No card reader

Lenovo

Multi-Media

Audio Chip

High Definition (HD) Audio, Realtek® ALC897-Q codec

Speakers

No speakers

Power Supply

Power Supply**

Power	Туре	Efficiency	Key Features
350W	Fixed	85%	100-240V, 50-60Hz
500W	Fixed	85%	100V - 240V
850W	Fixed	90%	100V - 240V

DESIGN

Input Device

Keyboard

- Lenovo Calliope Keyboard (USB connector), black
- No keyboard

Mouse

- Lenovo Calliope Mouse (USB connector), black
- No mouse

Mechanical

Form Factor

Tower (26L)

Dimensions (WxDxH)[1]

205 x 396.9 x 425.9 mm (8.1 x 15.62 x 16.76 inches)

Packaging Dimensions (WxDxH)

325 x 502 x 580 mm (12.79 x 19.76 x 22.83 inches)

Weight^[2]

Around 14 kg (30.86 lbs)

Packaging Weight

All models: Around 16 kg (35.27 lbs)

Case Color

Storm grey

Chassis**

- Normal side cover
- Transparent side cover
- Transparent side cover and inner decorate cover

Bays

- 1x 2.5" disk bay
- 2x 3.5" disk bay

Expansion Slots

- One PCIe 4.0 x16
- One PCIe 3.0 x4
- Three M.2 slots (one for WLAN, two for SSD)

Cooling System (Fan & Cooler)**

- 1x front system fan, 1x rear system fan
- 1x rear system fan
- 1x rear system fan with ARGB
- 1x rear system fan with ARGB, 2x front system fan with ARGB

Lenovo

- 1x rear system fan with ARGB, 2x front system fan with ARGB, 2x top system fan with ARGB
- 2x M.2 SSD Heatsink
- 65W 80MM-Fan cooler
- 150W 120MM-Fan cooler
- 150W 120MM-Fan with ARGB light cooler
- M.2 SSD DECO Mylar[®] Heatsink
- M.2 SSD Heatsink
- PCH Heatsink
- VRM Heatsink

System Lighting**

- Legion Wordmark lighting
- (Optional) Internal ambient lighting

Notes:

[1] The system dimensions may vary depending on configurations.

[2] The system weight is approximate and based on results in Lenovo lab, which varies depending on the source of component, variance of the distribution of each component, and manufacturing process. It may not be the exact weight for each specific model.

CONNECTIVITY

Network

Onboard Ethernet

2.5GbE, Realtek RTL8125BG Gaming Ethernet, 1x RJ-45

WLAN + Bluetooth®^[1]

Wi-Fi[®] 6, 802.11ax 2x2 Wi-Fi + Bluetooth 5.1, M.2 card

Notes:

[1] Bluetooth 5.2 is hardware ready but may run at a lower version due to OS limitations.

Ports

Rear Ports^[2]

• 1x USB-C[®] 3.2 Gen 2 (support data transfer and 5V@3A charging)

- 4x USB 2.0
- 2x USB 3.2 Gen 1
- 3x audio connector (3.5mm)
- 1x Lighting switch
- 1x Ethernet (RJ-45)
- 1x power connector

Top Ports

- 2x USB 3.2 Gen 1
- 1x headphone (3.5mm)
- 1x microphone (3.5mm)

Notes:

[1] The transfer speed of following ports will vary and, depending on many factors, such as the processing speed of the host device, file attributes and other factors related to system configuration and your operating environment, will be slower than theoretical speed.

USB 2.0: 480 Mbit/s;

USB 3.2 Gen 1 (SuperSpeed USB 5Gbps, formerly USB 3.0 / USB 3.1 Gen 1): 5 Gbit/s;

USB 3.2 Gen 2 (SuperSpeed USB 10Gbps, formerly USB 3.1 Gen 2): 10 Gbit/s;

USB4[®] 20Gbps / USB 3.2 Gen 2x2 (SuperSpeed USB 20Gbps): 20 Gbit/s;

USB4 40Gbps (USB 40Gbps): 40 Gbit/s;

Thunderbolt[™] 3/4: 40 Gbit/s

[2] For video ports on discrete graphics, please see graphics section

SECURITY & PRIVACY

Lenovo

Security

Security Chip

Firmware TPM 2.0 integrated in chipset

BIOS Security

- Administrator password
- Power-on password

SERVICE

Warranty^{II}

Base Warranty**

- 1-year courier or carry-in service
- 1-year mail-in service
- 1-year limited onsite service
- 2-year courier or carry-in service
- 3-year courier or carry-in service

Notes:

[1] The warranty upgrades may be bundled with some models, please check the "Included upgrade" column in the specific model's configurations. For more service extensions, please go to <u>https://smartfind.lenovo.com/</u>. To learn more details of warranty policy, please access <u>https://pcsupport.lenovo.com/warranty</u>.

ENVIRONMENTAL

Operating Environment

Temperature

- Operating: 5°C (41°F) to 35°C (95°F)
- Storage: -40°C (-40°F) to 60°C (140°F)

Humidity

- Operating: 20% to 80%
- Storage: 10% to 90%

Altitude

- Operating: -15.2 m (-50 ft) to 3048 m (10,000 ft)
- Storage: -15.2 m (-50 ft) to 12192 m (40,000 ft)

CERTIFICATIONS

Green Certifications

Green Certifications

- (Optional) ENERGY STAR[®] 8.0
- ErP Lot 3
- RoHS compliant
- Feature with ** means that only one offering listed under the feature is configured on selected models.
- Lenovo reserves the right to change specifications or other product information without notice. Lenovo is not responsible for photographic or typographical errors. LENOVO PROVIDES THIS PUBLICATION "AS IS," WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some jurisdictions do not allow disclaimer of express or implied warranties in certain transactions, therefore this disclaimer may not apply to you.

• The specifications on this page may not be available in all regions, and may be changed or updated without notice.



intel



intel



intel



intel



intel



intel