

THE GERMAN
WORKSPACE
BRAND 

ICY BOX® IB-HUB1742CR-C2PD

11-in-1 USB Type-C® hub with card reader

Key features

- 2x USB 3.2 Gen 2 Type-C® with a transfer rate of up to 10 Gbit/s
- 1x USB 3.2 Gen 2 Type-A with a transfer rate of up to 10 Gbit/s
- 3x USB 3.2 Gen 1 Type-A with a transfer rate of up to 5 Gbit/s and BC 1.2/ 7.5 watts
- 2x USB Type-C® Power Delivery with up to 22 watts with LED display
- SD®/microSD® card slots with up to 104 Mbit/s
- Supports Power Delivery up to 100 watts upstream to host
- Integrated USB-C/A host cable (up to 10 Gbit/s), 60 cm
- Power adapter 24 V/3 A, 72 W included



Packing content

- 1x IB-HUB1742CR-C2PD
- 1x 24 V/3A power adapter, 120 cm
- 1x Manual



Multi-connectivity

For content creators, editors, and professionals who manage multiple devices daily. It provides 11 ports, including two USB 3.2 Gen 2 Type-C® and one USB Type-A port, delivering speeds of up to 10 Gbit/s. It also features three USB 3.2 Gen 1 Type-A ports with BC 1.2 fast charging and integrated SD®/microSD® card readers with up to 104 MB/s for quick file transfers.



Durable aluminum build

Made from robust aluminum, this hub is designed for efficient heat dissipation. The sleek design makes it a reliable and stylish addition to any workspace. This durable construction allows long-term use and keeps temperatures in check during demanding tasks.



Power Delivery

The device is equipped with two dedicated USB Type-C® ports for PD, offering up to 22 watts each. One port can even provide up to 45 watts when used alone. The 100 W PD upstream port powers notebooks and devices, and the real-time LED wattage display helps you track power usage for optimal management.

Offers and deliveries are only done under our General Terms and Conditions. Errors and omissions excepted.



ICY BOX® IB-HUB1742CR-C2PD

11-in-1 USB Type-C® hub with card reader

General data

Model	IB-HUB1742CR-C2PD
Article no.	61159
EAN code	4250078174936
Colour	Blue
Material	Aluminum
Interface to host computer	USB 3.2 Gen 2 Type-C®
Length of cable	60 cm
Transfer rate	Up to 10 Gbit/s
UASP support	Yes
Plug & Play	Yes
LED	Power and access
ON/OFF button	-
Chipset	GL3590+AW3410+RM1211+FL7102+NS1081
Required space	-

Interfaces

USB 3.2 Gen 2 Type-A	1
USB 3.2 Gen 1 Type-A	3
USB 2.0 Type-A	-
USB4 Type-C®	-
USB 3.2 Gen 2 Type-C®	2
USB 3.2 Gen 1 Type-C®	-
USB Type-A Power Delivery	-
USB Type-C® Power Delivery	2
HotSwap	Yes

Additional features

Additional interfaces	1x SDHC / SDXC / SD® 3.0 (UHS-I) 1x MicroSDHC / microSDXC / microSD 3.0 (UHS-I)
Display	LED display for Power Delivery charging status
Kensington Lock	-
Degree of protection	-
Cooling	Passive
Mounting	-

Power

Power supply	24V / 3A power adapter
Plug dimension	Ø5.5 x Ø2.5 x L10 mm

Host system

Operating system	Windows®, macOS®, Linux®
System requirements	One free USB Type-C® or Type-A port on your host computer

Logistical data

Packing unit	16 pcs. / carton
Total weight	11.65 kg
Gross weight (with packing)	0.680 kg
Net weight	0.182 kg
Dimension / carton	428x308x238 mm
Dimension (with packing)	202x103x71 mm
Dimension of article	147x47x17 mm
Country of origin	China

Offers and deliveries are only done under our General Terms and Conditions. Errors and omissions excepted.