

# Eaton ELP1200FR

Catalog Number: ELP1200FR

Eaton Ellipse PRO UPS FR, 1200 VA, 750 W, Input: C14, Outputs: (4) French, (4) French surge only, Tower



### General specifications

Product Name	Catalog Number
Eaton Ellipse PRO UPS	ELP1200FR
UPC	Product Length/Depth
743172437716	390 mm
Product Height	Product Width
275 mm	82 mm
Product Weight	Warranty
9.8 kg	3 year
Compliances	Certifications
CE Marked	IEC/EN 62040-1
	IEC/EN 62040-2
	CE
	EAC

## Battery

### Battery type

Sealed, lead-acid

### Runtime graph

[View runtime graph](#)

### Battery replacement

User replaceable

### Battery quantity

2

### Battery management

Replaceable batteries, Automatic battery test, deep-discharge protection, cold-start capable

### Battery rating

12 V / 7 Ah

### Extended battery capability

No

## Electrical output

### Receptacle

(4) French, (4) French surge only

### Voltage

230V

### Wattage

750W

### Output power factor

0.6

### Output voltage range

176-284 V

### Output nominal voltage

230V default (220/230/240V)

### Feed type

1

### Topology

Line-interactive

### VA rating

1200 VA

## Electrical input

### Input connection

Protective contact (SCHUKO)

### Input nominal voltage

230V default (220/230/240V)

### Nominal frequency

50/60 Hz

### Input cord length

1.5 m

### Input voltage range

165-285 V (adjustable to 150-285 V)

### Input frequency range

46-70 Hz

## Communications

### Includes network card

No

### Communication

USB port (HID compliant)

### Ethernet interface

No

### User interface

LCD (UPS status and measurements, configuration of UPS settings)

### Potential free switch contact

No

### Expansion slots

No

### Software compatibility

Eaton UPS Companion (enables safe system shutdown, energy

usage metering and configuration of UPS settings)

#### Type of interface

USB

### Environmental

#### Altitude

2000 m

#### Noise level

<27 dB at 1 meter

#### Temperature range

0° to 35°C (32° to 95°F)

#### Relative humidity

0-85% non-condensing

### Additional specifications

#### Construction type

Free standing model

#### Package contents

Input cable

USB cable

User manual

Safety instructions

#### Phase (output)

1

#### Auto shutdown function

Yes

#### Color

Black

#### Efficiency

97

#### Rack mounting kit

No

#### Phase (input)

1

#### Surge protection

Yes

### Resources

#### Brochures

[Eaton UPS and battery services - EN](#)

[Eaton UPS Services Quick Guide - EN](#)

#### Manuals and user guides

[Eaton Ellipse PRO UPS 650/800/1200/1600 VA Installation and user manual \(multiple languages\)](#)

#### Software, firmware, and applications

[Eaton UPS Companion v1.06 release notes](#)

[Eaton UPS Companion 2.1 software download](#)

#### Technical data sheets

[Eaton Ellipse PRO UPS 650/800/1200/1600 VA Datasheet](#)



Eaton Corporation plc  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com  
© 2024 Eaton. All rights reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://Eaton.com/socialmedia)