

WNP-RP300-03-BK

## Wi-Fi repeater, 300 Mbps, black

### STAY CONNECTED

- Extends the range of your wireless network
- Quick and easy installation in any power socket
- Small and compact design



### Features

- Compact 300 Mbps WiFi repeater with integrated antennas
- Supports all IEEE 802.11b/g/n WiFi standards (2.4GHz networks)
- Up to 300 Mbps data transfer rate via the wireless 802.11n protocol
- Maximum WLAN security with WPA2, WPA and WEP(128/64)
- Quick setup via easy to use web-interface or WPS function
- Can be setup as wireless repeater or as access point
- Practical LAN port and LED status indication

### Packaging

|                                |                |
|--------------------------------|----------------|
| Q'ty in crtn, pcs              | 300            |
| Crtn volume, CUM               | 0.051086       |
| Crtn weight, kgs               | 15.36          |
| Individual package size LxWxH: | 40x40x80 mm    |
| Carton size LxWxH:             | 445x410x280 mm |
| Country of origin              | CN             |
| Barcode                        | 8716309117210  |
| Customs code                   | 8522900090     |

### Package contents

WiFi repeater  
User manual

### Certificates



### Specifications

Supported standards: IEEE 802.3, 802.3u, 802.11b/g/n  
Wireless transmission rate: max. 300 Mbps  
Security : 64/128-bit WEP, WPA-PSK, WPA2-PSK,WPA -MIXED-PSK

Supported modes: repeater mode, AP mode  
Ports: 1 x 10/100M RJ45  
Chipset: MT7628KN  
Frequency band: 2.412~2.484 GHz  
Channels: 1-13 (Europe)  
Power class: RF power up to 20 dBm (max. EIRP)  
Internal antenna gain (typical): 2x 3 dBi ±1 dBi  
Power consumption: up to 2.5 W, input 100 240 VAC 50/60 Hz

Dimensions: 40 x 40 x 68 mm (W x D x H)  
Net weight: 44 g  
Operating temperature: 0 ~ 40 °C  
Storage temperature: -40 ~ 70 °C  
Operating humidity: 10 ~ 90% non-condensing  
Storage humidity: 5 ~ 95% non-condensing