

USB-0504 Gigabit USB-C Network Adapter with USB Hub

Product Images



Short Description

- 10/100/1000Mbps wire speed transmission and reception
- USB 3.0 SuperSpeed (5Gb/s)
- Add 3 x USB 3.0 ports to your USB Type-C devices
- Multi-platform support: Windows, Mac OS
- Built-in Wake-on-LAN feature to startup computers remotely
- Simple Plug and Play installation, no additional power supply required

Description

The LevelOne USB-C Hub and Gigabit Ethernet Combo Adapter allows you to connect to the internet easily through the built-in USB-C port on your laptop. This is an ideal solution for MacBook or other Windows computers that may have wireless built-in but don't come with an Ethernet port. Sometimes you need to physically connect to a network cable to help transfer files or access secure information. The USB-0504 easily does the job, all through your USB-C port. The USB-0504 also combines a regular USB hub. So you can connect external USB peripherals, such as a digital camera, printer or pen drive. The USB-0504 establishes a direct point-to-point contact between the hub and the adapter that plugged into your PC.

The USB-0504 is USB 1.0, 2.0, and 3.0 compliant. It also follows the Ethernet standards set by the IEEE 802.3/3u and 802.3ab, allowing you to take advantage of Gigabit Ethernet speeds of up to 1000Mbps. This provides a strong backbone for any high-speed broadband connection to the internet as well as fast speeds for the Local Area Network file transfers.

This makes the USB-0504 the best choice for reliability, efficiency and standard compliance.

Additional Information

Color

FAN

Model Number

Features

Host Interface

Network Card Type

Data rate

Operating temperature

Operating humidity

Approval and Compliance

Storage humidity

Storage temperature

Compatible operating systems

Package Contents

Dimensions (W x D x H)

Product weight (kg)

Power supply

Standards

Silver

4015867226681

USB-0504

IPv4/IPv6 network operation

USB-C

Wired

Gigabit Ethernet

0°C ~ 40°C

10% RH ~ 85% RH

● CE ● RoHS

10% RH ~ 85% RH

0°C ~ 80°C

Windows XP/Vista/7/8/10 ● macOS X

10.9/10/11/12/13/14/15 ● macOS Big Sur 11.3 ● macOS Monterey 12.0.1 (Support automatic driver installation

plug-and-play functions)

● USB-0504 ● Quick Installation Guide

110 x 23.5 x 16.5 mm

0.044

USB power

● IEEE 802.3: 10Base-T (Ethernet) ● IEEE 802.3u:

100Base-TX (Fast Ethernet) ● IEEE 802.3ab: 1000Base-T (Gigabit Ethernet) ● IEEE 802.3az-2010 (EEE) ● IEEE 802.1

P Layer 2 Priority Encoding ● IEEE 802.1 Q VLAN tagging

