
Wide viewing angles with eye protection

Dynamic By Design





- · VGA, DVI, HDMI & DisplayPort
- · Low Blue Mode & Flicker Free
- · VESA Mount
- · Height Adjustable Stand
- Speakers



























Flicker Free Backlight Technology


Most LED monitors use PWM (pulse width modulation) to control brightness; the pulsing creates flicker that may cause discomfort, headaches and eye strain, especially in low-light environments. Flicker Free technology uses a smooth DC (direct current) backlight system.





Low Blue Mode

AOC Low Blue Mode filters harmful short-wave blue light, with 4 levels that suit different viewing situations.





Clear Vision

The image performance engine can upscale Standard Definition (SD) sources to High Definition (HD) for sharper, more vivid viewing.





Easy Assembly Height Adjustable Stand with Easy Assembly.



Specifications

Model Name	24P1
Panel Size	23.8" / 604.7mm
Pixel Pitch (mm)	0.2745 (H) × 0.2745 (V)
Effective Viewing Area (mm)	527.04 (H) × 296.46 (V)
Brightness (typical)	250 cd/m²
Contrast Ratio	1000:1 (Typical) 20,000,000:1 (DCR)
Smart Response	5ms (GtG)
Viewing Angle	178/178 (CR > 10)
Color Gamut	NTSC 90% (CIE1976) / sRGB 106% (CIE1931)
Optimum Resolution	1920 x 1080 @ 60Hz
Display Colors	16.7 Million
Signal Input	VGA, DVI, HDMI 1.4, DisplayPort 1.2
Power Supply	100 - 240V ~ 1.5A, 50 / 60Hz
Smart Power Mode: Typical	20W
Built-in Speakers	2W x 2
Regulatory Approvals	CE / FCC / KC / KCC / BSMI / TCO 7
Wall-Mount	100mm x 100mm
Cabinet Color	Black & Grey
Adjustable Stand	Tilt: -3.5° ~ 21.5°, Height : 130 ± 5 mm, Pivot: 0° ~ 90°, Swivel: 175° ± 5°
Product with Stand (mm)	510.3 (H) × 539.1 (W) × 202.5 (D)
Packaging (mm)	408 (H) × 752 (W) × 159 (D)
Weight (Net /Gross) kg	4.6 / 6.55

Design and Specifications are subject to change without notice.