

OKI MC883dnv - Multifunction printer

colour - LED - A3/Ledger (297 x 432 mm) (original) - A3 (media) - up to 35 ppm (copying) - up to 35 ppm (printing) - 2005 sheets - 33.6 Kbps - USB 2.0 - Gigabit LAN - USB 2.0 host

Group	Multifunction Printers
Manufacturer	OKI
Manufacturer item no.	09006109
EAN/UPC	5031713072935

Description

Faster print and copy speeds and higher capacity consumables make the MC883 the ideal solution for the most demanding workgroups. With print speeds of up to 35ppm and just 9.5 seconds to the first page out time in color and mono, larger workgroups can use the MC883 with ease. Low user intervention and lower total cost of ownership, together with the easy to use operator panel ensure the whole workgroup is more productive and efficient.

Main features

Product Description	OKI MC883dnv - multifunction printer - colour
Device Type	Multifunction printer
Fax Type	Super G3 - plain paper
Printing Technology	LED (colour)
Monthly Duty Cycle (max)	75000 pages
Recommended Monthly Volume	10000 pages
Max Copying Speed	Up to 35 ppm (mono) / up to 35 ppm (colour)
Max Copying Resolution	Up to 1200 x 1200 dpi (mono) / up to 1200 x 1200 dpi (colour)
Max Printing Speed	Up to 35 ppm (mono) / up to 35 ppm (colour)
Max Printing Resolution	Up to 1200 x 1200 dpi (mono) / up to 1200 x 1200 dpi (colour)
Max Fax Transmission Speed	33.6 Kbps
Data Compression System	MH, MR, MMR, JBIG
Scanning	600 x 600 dpi
Display	7"
Original Size	105 x 148 mm (min) - A3/Ledger (297 x 432 mm) (max)
Original Type	Sheets, books
Document Feeder Capacity	100 sheets
Media Size	64 x 90 mm (min) - 297 x 1321 mm (max)
Media Type	Envelopes, plain paper, cards
Standard Media Capacity	2005 sheets
Max Media Capacity	2005 sheets

Output Trays Capacity	350 sheets
Stapler	Included
Automatic Duplexing	Yes (copying) Yes (printing) Yes (scanning)
Connection Availability	Yes
Interface	USB 2.0, Gigabit LAN, USB 2.0 host
Office Machine Features	Save to USB flash drive, scan to e-mail, save to network folder, scan to FTP
Power	AC 230 V (50/60Hz)
Dimensions (WxDxH)	56.3 cm x 60 cm
Environmental Standards	Blue Angel

Extended details

Device Type Multifunction printer Fax Type Plain paper Printing Technology LED - colour Monthly Duty Cycle (max) 75000 pages Recommended Monthly Volume 10000 pages Display Diagonal Size 7" Display Colour Support Colour Connection Availability Yes Interface USB 2.0, Gigabit LAN, USB 2.0 host Office Machine Features Save to USB flash drive, scan to e-mail, save to network folder, scan to FTP Memory Standard Memory 1.25 GB Max Supported Memory 1.25 GB Hard Disk Drive 250 GB Wax Copying Speed Up to 35 ppm (mono) / up to 35 ppm (colour) Max Copying Resolution Up to 1200 x 1200 dpi (mono) / up to 1200 x 1200 dpi (colour) Preset Reductions 25% Maximum Copies 999 Automatic Duplexing Yes Max Printing Resolution Up to 1200 x 1200 dpi (mono) / up to 35 ppm (colour) Max Printing Speed Up to 35 ppm (mono) / up to 35 ppm (colour) Max Printing Speed Up to 35 ppm (mono) / up to 35 ppm (colour)		General
Printing Technology LED - colour Monthly Duty Cycle (max) 75000 pages Recommended Monthly Volume 10000 pages Display Diagonal Size 7" Display Colour Support Colour Display Features Touch screen Connection Availability Yes Interface USB 2.0, Gigabit LAN, USB 2.0 host Office Machine Features Save to USB flash drive, scan to e-mail, save to network folder, scan to FTP Memory 1.25 GB Max Supported Memory 1.25 GB Hard Disk Drive 250 GB Copying Copying Max Copying Speed Up to 35 ppm (mono) / up to 35 ppm (colour) Max Copying Resolution Up to 1200 x 1200 dpi (mono) / up to 1200 x 1200 dpi (colour) Preset Reductions 25% Maximum Copies 999 Automatic Duplexing Yes Printing Up to 1200 x 1200 dpi (mono) / up to 1200 x 1200 dpi (colour) Max Printing Resolution Up to 35 ppm (mono) / up to 35 ppm (colour) Max Printing Speed Up to 35 ppm (mono) / up to 35 ppm (colour) Printing Speed Up to 35 ppm (mono) / up to 35 ppm (colour) Printing Spee	Device Type	Multifunction printer
Monthly Duty Cycle (max)75000 pagesRecommended Monthly Volume10000 pagesDisplay Diagonal Size7"Display Colour SupportColourDisplay FeaturesTouch screenConnection AvailabilityYesInterfaceUSB 2.0, Gigabit LAN, USB 2.0 hostOfffice Machine FeaturesSave to USB flash drive, scan to e-mail, save to network folder, scan to FTPMemory1.25 GBMax Supported Memory1.25 GBHard Disk Drive250 GBCopyingUp to 35 ppm (mono) / up to 35 ppm (colour)Max Copying SpeedUp to 35 ppm (mono) / up to 1200 x 1200 dpi (colour)Preset Enlargements400%Preset Reductions25%Maximum Copies999Automatic DuplexingYesMax Printing ResolutionUp to 1200 x 1200 dpi (mono) / up to 1200 x 1200 dpi (colour)Max Printing SpeedUp to 35 ppm (mono) / up to 35 ppm (colour)Max Printing ResolutionUp to 1200 x 1200 dpi (mono) / up to 1200 x 1200 dpi (colour)Max Printing SpeedUp to 35 ppm (mono) / up to 35 ppm (colour)Printer Drivers / EmulationsPostScript 3, PCL 5c, IBM Proprinter, PCL 6 (XL), PDF 1.7, XPS, EPSON FXAutomatic DuplexingYesFirst Print Out Time B/W9.5 secFirst Print Out Time Colour9.5 secFirst Print Out Time Colour9.5 sec	Fax Type	Plain paper
Recommended Monthly Volume Display Diagonal Size T' Display Colour Support Colour Display Features Touch screen Connection Availability Yes Interface USB 2.0, Gigabit LAN, USB 2.0 host Office Machine Features Save to USB flash drive, scan to e-mail, save to network folder, scan to FTP Memory Standard Memory 1.25 GB Max Supported Memory 1.25 GB Hard Disk Drive Copying Max Copying Speed Up to 35 ppm (mono) / up to 35 ppm (colour) Max Copying Resolution Up to 1200 x 1200 dpi (mono) / up to 1200 x 1200 dpi (colour) Preset Reductions System Max Printing Resolution Up to 1200 x 1200 dpi (mono) / up to 1200 x 1200 dpi (colour) Max Printing Resolution Up to 1200 x 1200 dpi (mono) / up to 1200 x 1200 dpi (colour) Max Printing Resolution Max Printing Resolution Max Printing Speed Up to 35 ppm (mono) / up to 35 ppm (colour) Printer Drivers / Emulations PostScript 3, PCL 5c, IBM Proprinter, PCL 6 (XL), PDF 1.7, XPS, EPSON FX Automatic Duplexing Yes First Print Out Time B/W 9.5 sec First Print Out Time B/W 9.5 sec First Print Out Time Colour 9.5 sec	Printing Technology	LED - colour
Display Diagonal Size 7" Display Colour Support Colour Display Features Touch screen Connection Availability Yes Interface USB 2.0, Gigabit LAN, USB 2.0 host Office Machine Features Save to USB flash drive, scan to e-mail, save to network folder, scan to FTP Memory Standard Memory 1.25 GB Max Supported Memory 1.25 GB Hard Disk Drive 250 GB Copying Max Copying Speed Up to 35 ppm (mono) / up to 35 ppm (colour) Max Copying Resolution Up to 1200 x 1200 dpi (mono) / up to 1200 x 1200 dpi (colour) Preset Enlargements 400% Preset Reductions 999 Automatic Duplexing Yes Printing Max Printing Resolution Up to 1200 x 1200 dpi (mono) / up to 1200 x 1200 dpi (colour) Max Printing Speed Up to 35 ppm (mono) / up to 1200 x 1200 dpi (colour) Max Printing Resolution Up to 1200 x 1200 dpi (mono) / up to 1200 x 1200 dpi (colour) Max Printing Speed Up to 35 ppm (mono) / up to 35 ppm (colour) Max Printing Speed Up to 35 ppm (mono) / up to 35 ppm (colour) Max Printing Speed Up to 35 ppm (mono) / up to 35 ppm (colour) Max Printing Speed Up to 35 ppm (mono) / up to 35 ppm (colour) Printer Drivers / Emulations PostScript 3, PCL 5c, IBM Proprinter, PCL 6 (XL), PDF 1.7, XPS, EPSON FX Automatic Duplexing Yes First Print Out Time B/W 9.5 sec First Print Out Time B/W 9.5 sec First Print Out Time Colour 9.5 sec	Monthly Duty Cycle (max)	75000 pages
Display Colour Support Display Features Touch screen Connection Availability Yes Interface USB 2.0, Gigabit LAN, USB 2.0 host Office Machine Features Save to USB flash drive, scan to e-mail, save to network folder, scan to FTP Memory Standard Memory 1.25 GB Max Supported Memory 1.25 GB Hard Disk Drive 250 GB Copying Max Copying Speed Up to 35 ppm (mono) / up to 35 ppm (colour) Max Copying Resolution Up to 1200 x 1200 dpi (mono) / up to 1200 x 1200 dpi (colour) Preset Enlargements 400% Preset Reductions 25% Maximum Copies 999 Automatic Duplexing Yes Printing Max Printing Resolution Up to 1200 x 1200 dpi (mono) / up to 1200 x 1200 dpi (colour) Printing Speed Up to 35 ppm (mono) / up to 35 ppm (colour) Printer Drivers / Emulations PostScript 3, PCL 5c, IBM Proprinter, PCL 6 (XL), PDF 1.7, XPS, EPSON FX Automatic Duplexing Yes First Print Out Time B/W 9.5 sec First Print Out Time B/W 9.5 sec Scanning	Recommended Monthly Volume	10000 pages
Display Features Connection Availability Yes Interface USB 2.0, Gigabit LAN, USB 2.0 host Office Machine Features Save to USB flash drive, scan to e-mail, save to network folder, scan to FTP Memory Standard Memory 1.25 GB Max Supported Memory 1.25 GB Hard Disk Drive 250 GB Copying Max Copying Speed Up to 35 ppm (mono) / up to 35 ppm (colour) Max Copying Resolution Up to 1200 x 1200 dpi (mono) / up to 1200 x 1200 dpi (colour) Preset Enlargements 400% Preset Reductions 25% Maximum Copies 999 Automatic Duplexing Yes Printing Max Printing Resolution Up to 1200 x 1200 dpi (mono) / up to 1200 x 1200 dpi (colour) Printer Drivers / Emulations PostScript 3, PCL 5c, IBM Proprinter, PCL 6 (XL), PDF 1.7, XPS, EPSON FX Automatic Duplexing Yes First Print Out Time B/W 9.5 sec First Print Out Time Colour 9.5 sec	Display Diagonal Size	7"
Connection Availability Interface USB 2.0, Gigabit LAN, USB 2.0 host Office Machine Features Save to USB flash drive, scan to e-mail, save to network folder, scan to FTP Memory Standard Memory 1.25 GB Max Supported Memory 1.25 GB Hard Disk Drive Copying Max Copying Speed Up to 35 ppm (mono) / up to 35 ppm (colour) Max Copying Resolution Up to 1200 x 1200 dpi (mono) / up to 1200 x 1200 dpi (colour) Preset Enlargements 400% Preset Reductions 25% Maximum Copies 999 Automatic Duplexing Yes Printing Max Printing Resolution Up to 1200 x 1200 dpi (mono) / up to 1200 x 1200 dpi (colour) Max Printing Resolution Up to 1200 x 1200 dpi (mono) / up to 1200 x 1200 dpi (colour) Max Printing Resolution Vp to 1200 x 1200 dpi (mono) / up to 1200 x 1200 dpi (colour) Max Printing Speed Up to 35 ppm (mono) / up to 35 ppm (colour) Printer Drivers / Emulations PostScript 3, PCL 5c, IBM Proprinter, PCL 6 (XL), PDF 1.7, XPS, EPSON FX Automatic Duplexing Yes First Print Out Time B/W 9.5 sec First Print Out Time Colour 9.5 sec	Display Colour Support	Colour
Interface USB 2.0, Gigabit LAN, USB 2.0 host Office Machine Features Save to USB flash drive, scan to e-mail, save to network folder, scan to FTP Memory Standard Memory 1.25 GB Max Supported Memory 1.25 GB Hard Disk Drive 250 GB Copying Max Copying Speed Up to 35 ppm (mono) / up to 35 ppm (colour) Max Copying Resolution Up to 1200 x 1200 dpi (mono) / up to 1200 x 1200 dpi (colour) Preset Enlargements 400% Preset Reductions 25% Maximum Copies 999 Automatic Duplexing Yes Printing Max Printing Resolution Up to 1200 x 1200 dpi (mono) / up to 1200 x 1200 dpi (colour) Max Printing Speed Up to 1200 x 1200 dpi (mono) / up to 1200 x 1200 dpi (colour) Max Printing Speed Up to 35 ppm (mono) / up to 35 ppm (colour) Printer Drivers / Emulations PostScript 3, PCL 5c, IBM Proprinter, PCL 6 (XL), PDF 1.7, XPS, EPSON FX Automatic Duplexing Yes First Print Out Time B/W 9.5 sec First Print Out Time Colour 9.5 sec Scanning	Display Features	Touch screen
Memory Standard Memory 1.25 GB Max Supported Memory 1.25 GB Hard Disk Drive 250 GB Copying Max Copying Speed Mux Copying Resolution Vp to 1200 x 1200 dpi (mono) / up to 1200 x 1200 dpi (colour) Preset Enlargements 400% Preset Reductions 25% Maximum Copies 999 Automatic Duplexing Max Printing Resolution Up to 1200 x 1200 dpi (mono) / up to 1200 x 1200 dpi (colour) Max Printing Speed Up to 35 ppm (mono) / up to 1200 x 1200 dpi (colour) Preset Reductions 25% Maximum Copies 999 Automatic Duplexing Yes Printing Max Printing Resolution Up to 1200 x 1200 dpi (mono) / up to 1200 x 1200 dpi (colour) Max Printing Speed Up to 35 ppm (mono) / up to 35 ppm (colour) Printer Drivers / Emulations PostScript 3, PCL 5c, IBM Proprinter, PCL 6 (XL), PDF 1.7, XPS, EPSON FX Automatic Duplexing Yes First Print Out Time B/W 9.5 sec First Print Out Time Colour 9.5 sec Scanning	Connection Availability	Yes
MemoryStandard Memory1.25 GBMax Supported Memory1.25 GBHard Disk Drive250 GBCopyingMax Copying SpeedUp to 35 ppm (mono) / up to 35 ppm (colour)Max Copying ResolutionUp to 1200 x 1200 dpi (mono) / up to 1200 x 1200 dpi (colour)Preset Enlargements400%Preset Reductions25%Maximum Copies999Automatic DuplexingYesPrintingMax Printing ResolutionUp to 1200 x 1200 dpi (mono) / up to 1200 x 1200 dpi (colour)Max Printing SpeedUp to 35 ppm (mono) / up to 35 ppm (colour)Printer Drivers / EmulationsPostScript 3, PCL 5c, IBM Proprinter, PCL 6 (XL), PDF 1.7, XPS, EPSON FXAutomatic DuplexingYesFirst Print Out Time B/W9.5 secFirst Print Out Time Colour9.5 secFirst Print Out Time Colour9.5 sec	Interface	USB 2.0, Gigabit LAN, USB 2.0 host
Standard Memory1.25 GBMax Supported Memory1.25 GBHard Disk DriveZopyingMax Copying SpeedUp to 35 ppm (mono) / up to 35 ppm (colour)Max Copying ResolutionUp to 1200 x 1200 dpi (mono) / up to 1200 x 1200 dpi (colour)Preset Enlargements400%Preset Reductions25%Maximum Copies999Automatic DuplexingYesPrintingMax Printing ResolutionUp to 1200 x 1200 dpi (mono) / up to 1200 x 1200 dpi (colour)Max Printing SpeedUp to 35 ppm (mono) / up to 35 ppm (colour)Printer Drivers / EmulationsPostScript 3, PCL 5c, IBM Proprinter, PCL 6 (XL), PDF 1.7, XPS, EPSON FXAutomatic DuplexingYesFirst Print Out Time B/W9.5 secFirst Print Out Time Colour9.5 secScanning	Office Machine Features	Save to USB flash drive, scan to e-mail, save to network folder, scan to FTP
Max Supported Memory 1.25 GB Hard Disk Drive 250 GB Copying Max Copying Speed Up to 35 ppm (mono) / up to 35 ppm (colour) Max Copying Resolution Up to 1200 x 1200 dpi (mono) / up to 1200 x 1200 dpi (colour) Preset Enlargements 400% Preset Reductions 25% Maximum Copies 999 Automatic Duplexing Yes Printing Max Printing Resolution Up to 1200 x 1200 dpi (mono) / up to 1200 x 1200 dpi (colour) Max Printing Speed Up to 1200 x 1200 dpi (mono) / up to 1200 x 1200 dpi (colour) Max Printing Speed Up to 35 ppm (mono) / up to 35 ppm (colour) Printer Drivers / Emulations PostScript 3, PCL 5c, IBM Proprinter, PCL 6 (XL), PDF 1.7, XPS, EPSON FX Automatic Duplexing Yes First Print Out Time B/W 9.5 sec First Print Out Time Colour 9.5 sec Scanning		Memory
Copying Max Copying Speed Up to 35 ppm (mono) / up to 35 ppm (colour) Max Copying Resolution Up to 1200 x 1200 dpi (mono) / up to 1200 x 1200 dpi (colour) Preset Enlargements 400% Preset Reductions 25% Maximum Copies 999 Automatic Duplexing Yes Printing Max Printing Resolution Up to 1200 x 1200 dpi (mono) / up to 1200 x 1200 dpi (colour) Max Printing Speed Up to 35 ppm (mono) / up to 1200 x 1200 dpi (colour) Printer Drivers / Emulations PostScript 3, PCL 5c, IBM Proprinter, PCL 6 (XL), PDF 1.7, XPS, EPSON FX Automatic Duplexing Yes First Print Out Time B/W 9.5 sec First Print Out Time Colour 9.5 sec Scanning	Standard Memory	1.25 GB
CopyingMax Copying SpeedUp to 35 ppm (mono) / up to 35 ppm (colour)Max Copying ResolutionUp to 1200 x 1200 dpi (mono) / up to 1200 x 1200 dpi (colour)Preset Enlargements400%Preset Reductions25%Maximum Copies999Automatic DuplexingYesPrintingMax Printing ResolutionUp to 1200 x 1200 dpi (mono) / up to 1200 x 1200 dpi (colour)Max Printing SpeedUp to 35 ppm (mono) / up to 35 ppm (colour)Printer Drivers / EmulationsPostScript 3, PCL 5c, IBM Proprinter, PCL 6 (XL), PDF 1.7, XPS, EPSON FXAutomatic DuplexingYesFirst Print Out Time B/W9.5 secFirst Print Out Time Colour9.5 secFirst Print Out Time Colour9.5 sec	Max Supported Memory	1.25 GB
Max Copying SpeedUp to 35 ppm (mono) / up to 35 ppm (colour)Max Copying ResolutionUp to 1200 x 1200 dpi (mono) / up to 1200 x 1200 dpi (colour)Preset Enlargements400%Preset Reductions25%Maximum Copies999Automatic DuplexingYesPrintingMax Printing ResolutionUp to 1200 x 1200 dpi (mono) / up to 1200 x 1200 dpi (colour)Max Printing SpeedUp to 35 ppm (mono) / up to 35 ppm (colour)Printer Drivers / EmulationsPostScript 3, PCL 5c, IBM Proprinter, PCL 6 (XL), PDF 1.7, XPS, EPSON FXAutomatic DuplexingYesFirst Print Out Time B/W9.5 secFirst Print Out Time Colour9.5 secScanning	Hard Disk Drive	250 GB
Max Copying Resolution Up to 1200 x 1200 dpi (mono) / up to 1200 x 1200 dpi (colour) Preset Enlargements 400% Preset Reductions 25% Maximum Copies 999 Automatic Duplexing Yes Printing Max Printing Resolution Up to 1200 x 1200 dpi (mono) / up to 1200 x 1200 dpi (colour) Max Printing Speed Up to 35 ppm (mono) / up to 35 ppm (colour) Printer Drivers / Emulations PostScript 3, PCL 5c, IBM Proprinter, PCL 6 (XL), PDF 1.7, XPS, EPSON FX Automatic Duplexing Yes First Print Out Time B/W 9.5 sec First Print Out Time Colour 9.5 sec Scanning		Copying
Preset Enlargements 400% Preset Reductions 25% Maximum Copies 999 Automatic Duplexing Yes Printing Max Printing Resolution Up to 1200 x 1200 dpi (mono) / up to 1200 x 1200 dpi (colour) Max Printing Speed Up to 35 ppm (mono) / up to 35 ppm (colour) Printer Drivers / Emulations PostScript 3, PCL 5c, IBM Proprinter, PCL 6 (XL), PDF 1.7, XPS, EPSON FX Automatic Duplexing Yes First Print Out Time B/W 9.5 sec First Print Out Time Colour 9.5 sec Scanning	Max Copying Speed	Up to 35 ppm (mono) / up to 35 ppm (colour)
Preset Reductions 25% Maximum Copies 999 Automatic Duplexing Printing Max Printing Resolution Up to 1200 x 1200 dpi (mono) / up to 1200 x 1200 dpi (colour) Max Printing Speed Up to 35 ppm (mono) / up to 35 ppm (colour) Printer Drivers / Emulations PostScript 3, PCL 5c, IBM Proprinter, PCL 6 (XL), PDF 1.7, XPS, EPSON FX Automatic Duplexing Yes First Print Out Time B/W 9.5 sec First Print Out Time Colour 9.5 sec Scanning	Max Copying Resolution	Up to 1200 x 1200 dpi (mono) / up to 1200 x 1200 dpi (colour)
Maximum Copies 999 Automatic Duplexing Yes Printing Max Printing Resolution Up to 1200 x 1200 dpi (mono) / up to 1200 x 1200 dpi (colour) Max Printing Speed Up to 35 ppm (mono) / up to 35 ppm (colour) Printer Drivers / Emulations PostScript 3, PCL 5c, IBM Proprinter, PCL 6 (XL), PDF 1.7, XPS, EPSON FX Automatic Duplexing Yes First Print Out Time B/W 9.5 sec First Print Out Time Colour 9.5 sec Scanning	Preset Enlargements	400%
Automatic Duplexing Printing Max Printing Resolution Up to 1200 x 1200 dpi (mono) / up to 1200 x 1200 dpi (colour) Max Printing Speed Up to 35 ppm (mono) / up to 35 ppm (colour) Printer Drivers / Emulations PostScript 3, PCL 5c, IBM Proprinter, PCL 6 (XL), PDF 1.7, XPS, EPSON FX Automatic Duplexing Yes First Print Out Time B/W 9.5 sec First Print Out Time Colour 9.5 sec Scanning	Preset Reductions	25%
Printing Max Printing Resolution Up to 1200 x 1200 dpi (mono) / up to 1200 x 1200 dpi (colour) Max Printing Speed Up to 35 ppm (mono) / up to 35 ppm (colour) Printer Drivers / Emulations PostScript 3, PCL 5c, IBM Proprinter, PCL 6 (XL), PDF 1.7, XPS, EPSON FX Automatic Duplexing Yes First Print Out Time B/W 9.5 sec First Print Out Time Colour 9.5 sec Scanning	Maximum Copies	999
Max Printing Resolution Up to 1200 x 1200 dpi (mono) / up to 1200 x 1200 dpi (colour) Max Printing Speed Up to 35 ppm (mono) / up to 35 ppm (colour) Printer Drivers / Emulations PostScript 3, PCL 5c, IBM Proprinter, PCL 6 (XL), PDF 1.7, XPS, EPSON FX Automatic Duplexing Yes First Print Out Time B/W 9.5 sec First Print Out Time Colour 9.5 sec Scanning	Automatic Duplexing	Yes
Max Printing Speed Up to 35 ppm (mono) / up to 35 ppm (colour) Printer Drivers / Emulations PostScript 3, PCL 5c, IBM Proprinter, PCL 6 (XL), PDF 1.7, XPS, EPSON FX Automatic Duplexing Yes First Print Out Time B/W 9.5 sec First Print Out Time Colour 9.5 sec Scanning		Printing
Printer Drivers / Emulations PostScript 3, PCL 5c, IBM Proprinter, PCL 6 (XL), PDF 1.7, XPS, EPSON FX Automatic Duplexing Yes First Print Out Time B/W 9.5 sec First Print Out Time Colour 9.5 sec Scanning	Max Printing Resolution	Up to 1200 x 1200 dpi (mono) / up to 1200 x 1200 dpi (colour)
Automatic Duplexing Yes First Print Out Time B/W 9.5 sec First Print Out Time Colour 9.5 sec Scanning	Max Printing Speed	Up to 35 ppm (mono) / up to 35 ppm (colour)
First Print Out Time B/W 9.5 sec First Print Out Time Colour 9.5 sec Scanning	Printer Drivers / Emulations	PostScript 3, PCL 5c, IBM Proprinter, PCL 6 (XL), PDF 1.7, XPS, EPSON FX
First Print Out Time Colour 9.5 sec Scanning	Automatic Duplexing	Yes
Scanning	First Print Out Time B/W	9.5 sec
	First Print Out Time Colour	9.5 sec
Scan Element CIS		Scanning
	Scan Element	CIS

Optical Resolution	600 x 600 dpi
	Fax Machine
Compatibility	Super G3
Max Transmission Speed	33.6 Kbps
Data Compression System	MH, MR, MMR, JBIG
Total Memory Capacity	Up to 8192 pages
PC Faxing	Yes
	Fax Machine Features
One-Touch Dialing	40 station(s)
Speed Dialing	1000 station(s)
Broadcast Transmission	320 stations
	Document & Media Handling
Min Original Size	105 x 148 mm
Max Original Size	A3/Ledger (297 x 432 mm)
Supported Original Sizes	ANSI A (Letter) (216 x 279 mm), Legal (216 x 356 mm), Executive (184 x 267 mm), A4 (210 x 297 mm), A5 (148 x 210 mm), B5 (176 x 250 mm), A3 (297 x 420 mm), B4 (250 x 353 mm), A6 (105 x 148 mm), Folio (216 x 330 mm), Statement (139.7 x 215.9 mm), Tabloid (279 x 432 mm)
Original Type	Sheets, books
Document Feeder Capacity	100 sheets
Min Media Size	64 x 90 mm
Max Media Size	A3
Min Media Weight	64 g/m²
Max Media Weight	220 g/m²
Supported Media Type	Envelopes, plain paper, cards
Supported Media Sizes	ANSI A (Letter) (216 x 279 mm), Legal (216 x 356 mm), Executive (184 x 267 mm), A4 (210 x 297 mm), A5 (148 x 210 mm), B5 (176 x 250 mm), A3 (297 x 420 mm), B4 (250 x 353 mm), A6 (105 x 148 mm), Folio (216 x 330 mm), Statement (139.7 x 215.9 mm), 297 x 1321 mm, Tabloid (279 x 432 mm), 64 x 90 mm
Standard Media Capacity	2005 sheets
Max Media Capacity	2005 sheets
Bypass Feeder Capacity	100 sheets
Output Trays Capacity	350 sheets
Document & Media Handling Details	RADF - 100 sheets size: $105 \times 148 \text{ mm}$ - A3/Ledger (297 x 432 mm) weight: 60 g/m^2 - 120 g/m^2 Multi-purpose tray - 100 sheets size: $64 \times 90 \text{ mm}$ - $297 \times 1321 \text{ mm}$ weight: 64 g/m^2 - 256 g/m^2 Input tray - 300 sheets weight: 64 g/m^2 - 220 g/m^2 $3 \times 100 \times $
Speed Details	Copying: up to 35 ppm (A4) - B/W Copying: up to 35 ppm (A4) - colour Printing: up to 35 ppm (A4) - B/W landscape Printing: up to 35 ppm (A4) - colour landscape Printing: up to 20 ppm (A3) - B/W landscape Printing: up to 20 ppm (A3) - colour landscape Scanning: up to 50 ipm - B/W Scanning: up to 50 ipm - colour Scanning: up to 17 ipm - B/W duplex Scanning: up to 17 ipm - colour duplex
	Finishing Equipment
Stapler	Included

USB Type A 2 x phone line - RJ-11 Security Protocols & Features LDAP, Secure Print Linux, MS Windows Server 2008 R2, MS Windows Server 2012, MS Windows Server 2018 R2, MS Windows Server 2012 R2, MS Windows Server 2003 (32/64-bits), MS Windows Server 2008 (32/64-bits), MS Windows Server 2012, MS Windows Server 2008 (32/64-bits), MS Windows Server 2012, MS Windows Server 2008 (32/64-bits), MS Windows Server 2003 (32/64-bits), MS Windows Server 2008 (32/64-bits), Ms Windows 8.102/64 (20/64), Mindows 8.102/64 (20/64), Mindows 8.102/64 (20/64), Ms Windows 8.10		Connections
Linux, MS Windows Server 2008 R2, MS Windows Server 2012, MS Windows Server 2012 R2, MS Windows Server 2003 (32/64-bits), MS Windows Server 2008 (32/64-bits), MS Windows Server 2008 (32/64-bits), MS Windows Server 2008 (32/64-bits), MS Windows 7 (32/64 bits), Windows 8 (32/64-bits), Ms Windows 8 (32/64-bits), Apple Mac OS X 10.6 - 10.10 Ms Windows 8 (32/64-bits), Apple Mac OS X 10.6 - 10.10 Ms Windows 8 (32/64-bits), Apple Mac OS X 10.6 - 10.10 Ms Windows 8 (32/64-bits), Apple Mac OS X 10.6 - 10.10 Ms Windows 8 (32/64-bits), Apple Mac OS X 10.6 - 10.10 Ms Windows 8 (32/64-bits), Apple Mac OS X 10.6 - 10.10 Ms Windows 8 (32/64-bits), Apple Mac OS X 10.6 - 10.10 Ms Windows 8 (32/64-bits), Mindows 8 (32/64-bits), Ms Windows 8 (32/64-bits), Ms	Interfaces	
Server 2012 R2, MS Windows Server 2003 (32/64-bits), MS Windows Server 2008 (32/64-bits), MS Windows Server 2008 (32/64-bits), MS Windows Server 2008 (32/64-bits), Windows Server 2008 (32/64-bits), Windows 8 (32/64-bits), Windows 8.1 (32/64-bits), Apple Mac OS X 10.6 - 10.10 MS Windows 8 (32/64-bits), Windows 8.1 (32/64-bits), Apple Mac OS X 10.6 - 10.10 MS Windows 8 (32/64-bits), Apple Mac OS X 10.6 - 10.10 MS Windows 8 (32/64-bits), Windows 8.1 (32/64-bits), Apple Mac OS X 10.6 - 10.10 MS WINDOWS Explorer Power Power Voltage Required	Security Protocols & Features	LDAP, Secure Print
Power Voltage Required AC 230 V (50/60Hz) Power Consumption Operational 1400 Watt Power Consumption Standby 120 Watt Power Consumption Sleep 3 Watt Miscellaneous Warm-Up Time 32 sec First Copy Out Time B/W 10 sec First Copy Out Time Colour 10 sec Included Accessories Phone cable, caster base Consumables Included 1 x Cartridge (black) 1 x Cartridge (cyan) 1 x Cartridge (magenta) 1 x Cartridge (yellow) Compliant Standards GS, EMC Environmental Standards Blue Angel Compliant Yes Manufacturer Warranty Service & Support Limited warranty - 3 years with product registration Dimensions & Weight Width 56.3 cm Depth 60 cm Environmental Parameters Sound Emission 37 dBA (idle) / 54 dBA (operating) Min Operating Temperature 10 °C Max Operating Temperature 32 °C	Operating System Support	Server 2012 R2, MS Windows Server 2003 (32/64-bits), MS Windows Server
Voltage Required AC 230 V (50/60Hz) Power Consumption Operational 1400 Watt Power Consumption Standby 120 Watt Power Consumption Sleep 3 Watt Miscellaneous Warm-Up Time 32 sec First Copy Out Time B/W 10 sec First Copy Out Time Colour 10 sec Included Accessories Phone cable, caster base Consumables Included 1 x Cartridge (black) 1 x Cartridge (cyan) 1 x Cartridge (magenta) 1 x Cartridge (yellow) Compliant Standards GS, EMC Environmental Standards Blue Angel Compliant Yes Manufacturer Warranty Service & Support Limited warranty - 3 years with product registration Dimensions & Weight Width 56.3 cm Depth 60 cm Environmental Parameters Sound Emission 37 dBA (idle) / 54 dBA (operating) Min Operating Temperature 10 °C Max Operating Temperature 32 °C	Software Included	ABBYY FineReader Sprint, OKI smartPrintSuperVision, SENDYS Explorer
Power Consumption Operational 1400 Watt Power Consumption Standby 120 Watt Power Consumption Sleep 3 Watt Miscellaneous Warm-Up Time 32 sec First Copy Out Time B/W 10 sec First Copy Out Time Colour 10 sec Included Accessories Phone cable, caster base Consumables Included 1 x Cartridge (black) 1 x Cartridge (cyan) 1 x Cartridge (magenta) 1 x Cartridge (yellow) Compliant Standards GS, EMC Environmental Standards Blue Angel Compliant Yes Manufacturer Warranty Service & Support Limited warranty - 3 years with product registration Dimensions & Weight Width 56.3 cm Depth 60 cm Environmental Parameters Sound Emission 37 dBA (idle) / 54 dBA (operating) Min Operating Temperature 10 °C Max Operating Temperature 32 °C		Power
Power Consumption Standby Power Consumption Sleep 3 Watt Miscellaneous Warm-Up Time 32 sec First Copy Out Time B/W 10 sec First Copy Out Time Colour 10 sec Included Accessories Phone cable, caster base Consumables Included 1 x Cartridge (black) 1 x Cartridge (cyan) 1 x Cartridge (magenta) 1 x Cartridge (yellow) Compliant Standards GS, EMC Environmental Standards Blue Angel Compliant Yes Manufacturer Warranty Service & Support Limited warranty - 3 years with product registration Dimensions & Weight Width 56.3 cm Depth 60 cm Environmental Parameters Sound Emission 37 dBA (idle) / 54 dBA (operating) Min Operating Temperature 10 °C Max Operating Temperature 32 °C	Voltage Required	AC 230 V (50/60Hz)
Miscellaneous Warm-Up Time 32 sec First Copy Out Time B/W 10 sec First Copy Out Time Colour 10 sec Included Accessories Phone cable, caster base Consumables Included 1 x Cartridge (black) 1 x Cartridge (cyan) 1 x Cartridge (magenta) 1 x Cartridge (yellow) Compliant Standards GS, EMC Environmental Standards Blue Angel Compliant Yes Manufacturer Warranty Service & Support Limited warranty - 3 years with product registration Dimensions & Weight Width 56.3 cm Depth 60 cm Environmental Parameters Sound Emission 37 dBA (idle) / 54 dBA (operating) Min Operating Temperature 10 °C Max Operating Temperature 32 °C	Power Consumption Operational	1400 Watt
Miscellaneous Warm-Up Time 32 sec First Copy Out Time B/W 10 sec First Copy Out Time Colour 10 sec Included Accessories Phone cable, caster base Consumables Included 1 x Cartridge (black) 1 x Cartridge (cyan) 1 x Cartridge (magenta) 1 x Cartridge (yellow) Compliant Standards GS, EMC Environmental Standards Blue Angel Compliant Yes Manufacturer Warranty Service & Support Limited warranty - 3 years with product registration Dimensions & Weight Width 56.3 cm Depth 60 cm Environmental Parameters Sound Emission 37 dBA (idle) / 54 dBA (operating) Min Operating Temperature 10 °C Max Operating Temperature 32 °C	Power Consumption Standby	120 Watt
Warm-Up Time 32 sec First Copy Out Time B/W 10 sec First Copy Out Time Colour 10 sec Included Accessories Phone cable, caster base Consumables Included 1 x Cartridge (black) 1 x Cartridge (cyan) 1 x Cartridge (magenta) 1 x Cartridge (yellow) Compliant Standards GS, EMC Environmental Standards Blue Angel Compliant Yes Manufacturer Warranty Service & Support Limited warranty - 3 years with product registration Dimensions & Weight Width 56.3 cm Depth 60 cm Environmental Parameters Sound Emission 37 dBA (idle) / 54 dBA (operating) Min Operating Temperature 10 °C Max Operating Temperature 32 °C	Power Consumption Sleep	3 Watt
First Copy Out Time B/W 10 sec Included Accessories Phone cable, caster base Consumables Included 1 x Cartridge (black) 1 x Cartridge (cyan) 1 x Cartridge (magenta) 1 x Cartridge (yellow) Compliant Standards GS, EMC Environmental Standards Blue Angel Compliant Yes Manufacturer Warranty Service & Support Limited warranty - 3 years with product registration Dimensions & Weight Width 56.3 cm Depth 60 cm Environmental Parameters Sound Emission 37 dBA (idle) / 54 dBA (operating) Min Operating Temperature 10 °C Max Operating Temperature 32 °C		Miscellaneous
First Copy Out Time Colour Included Accessories Phone cable, caster base Consumables Included 1 x Cartridge (black) 1 x Cartridge (cyan) 1 x Cartridge (magenta) 1 x Cartridge (yellow) Compliant Standards GS, EMC Environmental Standards Blue Angel Compliant Yes Manufacturer Warranty Service & Support Limited warranty - 3 years with product registration Dimensions & Weight Width 56.3 cm Depth 60 cm Environmental Parameters Sound Emission 37 dBA (idle) / 54 dBA (operating) Min Operating Temperature 10 °C Max Operating Temperature 32 °C	Warm-Up Time	32 sec
Included Accessories Phone cable, caster base Consumables Included 1 x Cartridge (black) 1 x Cartridge (cyan) 1 x Cartridge (magenta) 1 x Cartridge (yellow) Compliant Standards GS, EMC Environmental Standards Yes Manufacturer Warranty Service & Support Limited warranty - 3 years with product registration Dimensions & Weight Width 56.3 cm Depth 60 cm Environmental Parameters Sound Emission 37 dBA (idle) / 54 dBA (operating) Min Operating Temperature 10 °C Max Operating Temperature 32 °C	First Copy Out Time B/W	10 sec
Consumables Included 1 x Cartridge (black) 1 x Cartridge (cyan) 1 x Cartridge (magenta) 1 x Cartridge (yellow) Compliant Standards GS, EMC Environmental Standards Blue Angel Compliant Yes Manufacturer Warranty Service & Support Limited warranty - 3 years with product registration Dimensions & Weight Width 56.3 cm Depth 60 cm Environmental Parameters Sound Emission 37 dBA (idle) / 54 dBA (operating) Min Operating Temperature 10 °C Max Operating Temperature 32 °C	First Copy Out Time Colour	10 sec
Cartridge (yellow) Compliant Standards GS, EMC Environmental Standards Blue Angel Compliant Yes Manufacturer Warranty Service & Support Limited warranty - 3 years with product registration Dimensions & Weight Width 56.3 cm Depth 60 cm Environmental Parameters Sound Emission 37 dBA (idle) / 54 dBA (operating) Min Operating Temperature 10 °C Max Operating Temperature 32 °C	Included Accessories	Phone cable, caster base
Environmental Standards Yes Manufacturer Warranty Service & Support Limited warranty - 3 years with product registration Dimensions & Weight Width 56.3 cm Depth 60 cm Environmental Parameters Sound Emission 37 dBA (idle) / 54 dBA (operating) Min Operating Temperature 10 °C Max Operating Temperature 32 °C	Consumables Included	
Blue Angel Compliant Manufacturer Warranty Service & Support Limited warranty - 3 years with product registration Dimensions & Weight Width 56.3 cm Depth 60 cm Environmental Parameters Sound Emission 37 dBA (idle) / 54 dBA (operating) Min Operating Temperature 10 °C Max Operating Temperature 32 °C	Compliant Standards	GS, EMC
Manufacturer Warranty Service & Support Limited warranty - 3 years with product registration Dimensions & Weight Width 56.3 cm Depth 60 cm Environmental Parameters Sound Emission 37 dBA (idle) / 54 dBA (operating) Min Operating Temperature 10 °C Max Operating Temperature 32 °C		Environmental Standards
Service & Support Limited warranty - 3 years with product registration Dimensions & Weight Width 56.3 cm Depth 60 cm Environmental Parameters Sound Emission 37 dBA (idle) / 54 dBA (operating) Min Operating Temperature 10 °C Max Operating Temperature 32 °C	Blue Angel Compliant	Yes
Dimensions & Weight Width 56.3 cm Depth 60 cm Environmental Parameters Sound Emission 37 dBA (idle) / 54 dBA (operating) Min Operating Temperature 10 °C Max Operating Temperature 32 °C		Manufacturer Warranty
Width 56.3 cm Depth 60 cm Environmental Parameters Sound Emission 37 dBA (idle) / 54 dBA (operating) Min Operating Temperature 10 °C Max Operating Temperature 32 °C	Service & Support	Limited warranty - 3 years with product registration
Depth 60 cm Environmental Parameters Sound Emission 37 dBA (idle) / 54 dBA (operating) Min Operating Temperature 10 °C Max Operating Temperature 32 °C		Dimensions & Weight
Environmental Parameters Sound Emission 37 dBA (idle) / 54 dBA (operating) Min Operating Temperature 10 °C Max Operating Temperature 32 °C	Width	56.3 cm
Sound Emission 37 dBA (idle) / 54 dBA (operating) Min Operating Temperature 10 °C Max Operating Temperature 32 °C	Depth	60 cm
Min Operating Temperature 10 °C Max Operating Temperature 32 °C		
Max Operating Temperature 32 °C	Sound Emission	37 dBA (idle) / 54 dBA (operating)
	Min Operating Temperature	10 °C
Humidity Range Operating 20 - 80%	Max Operating Temperature	32 °C
	Humidity Range Operating	20 - 80%

Technical data © CNET Content Solutions. Subject to technical modifications and errors.