ThinkCentre M920x Tiny 10S10013++

Region EMEA

Machine Type 10S1

TopSeller TopSeller

Processor Core i7-8700 (6C, 3.2 / 4.6GHz, 12MB)

vPro vPro

Graphics Integrated Intel UHD Graphics 630

Monitor Cable None

Memory 16GBx1

Storage 256GB SSD M.2 PCIe NVMe Opal

Optical None

WLAN + Bluetooth Intel 9560 ac, 2x2 + BT5.0

Ethernet Integrated

Optional Rear Ports 2nd DP + Serial

Extension Card None

Kensington Cable Lock None

Adapter Cage Adapter Cage

Toolless Chassis Screw Toolless Chassis Screw

Speaker 1.5Wx1 Dust Filter None

VESA Mount VESA Mount

Stand None

Keyboard / Mouse USB / USB

Power Supply 135W 88% Adapter

TUV Low Noise None

Operating System Windows 10 Pro 64

Warranty 3-year, Onsite

End of Support Aug 31, 2024

Ann Date (mm/yy) 07/18

Note:

* Country Code "US" is for United States, "++" is for EMEA countries (e.g. AD - Saudi, Arabia, AT - Austria, BM - Bulgaria, etc.), "xx" is for EAST countries (e.g. BM - Bulgaria, CX -Hungary, CY - Cyprus, etc.), and "**" is for MEA countries (e.g. AD - Saudi, Arabia, ED - Egypt, EQ - Sweden, etc.). Please be aware that the EMEA/ EAST/MEA models listed above might not be available in all countries

WWW.LENOVO.COM

This publication was developed for products and services oered in the United States and E.M.E.A countries. Lenovo may not oer the products, services or features discussed in this document in other countries. Lenovo may withdraw an oering at any time. Information is subject to change without notice. Consult your local representative for information on oerings available in your area.

Lenovo reserves the right to change specifications or other product information without notice. Lenovo is not responsible for photographic or typographical errors.

Lenovo provides this publication "as is" without warranty of any kind, either express or implied, including the implied warranties of merchantability or ftness for a particular purpose.

http://psref.lenovo.com

PSREF

Visit psref website for the latest version of Product Specifcations Reference. © Lenovo, 2017. All rights reserved.

ThinkCentre M920x Tiny Platform Specifications

Product Specifications Reference (PSREF)

		01.0	1					
						l	Some: 11ac wireless, M.2 Card, Realtek RTL8822BE (dual band),	
Processor	Threads Base/Max(GHz) Cache (Up to) Graphics				Integrated Graphics		Wi-Fi + Bluetooth 4.2 combo adapter, 2x2 Some: 11ac wireless, M.2 Card, Intel Dual Band Wireless-AC 3165,	
Celeron G4900	2/2	3.1G	2 MB	DDR4-2400	UHD 610		Wi-Fi + Bluetooth 4.2 combo adapter, 1x1 Some: 11ac wireless, M.2 Card, Intel Dual Band Wireless-AC 8265,	
							Wi-Fi + Bluetooth 4.2 combo adapter, 2x2	
							Some: 11ac wireless, M.2 Card, Intel Wireless-AC 9560 (dual band),	
						Diverse	Wi-Fi + Bluetooth 5.0 combo adapter, Intel vPro technology support, 2x	
							Some: Bluetooth 4.2/5.0 wireless, integrated in Wi-Fi + BT combo adapter Gigabit ethernet, Intel Ethernet Connection I219-LM(Jacksonville), Wake on LA	
							Some: Intel Ethernet Server Adapter I350-T4, gigabit ethernet, 4x RJ-45, PCIe	
						· · · · · · · · · · · · · · · · · · ·	Intel Active Management Technology 12 (Intel AMT 12);	
						wanageability	Intel vPro technology on some models (require choosing a vPro-support Wi-Fi	
							adapter to enable vPro function through wireless connection)	
							 Discrete TPM 2.0, TCG Certified Security slot (in rear for optional Kensington[®] MicroSaver[®] cable) Chassis intrusion switch Power-on password Administrator password Boot sequence control Boot without keyboard and mouse Individual USB port disablement Smart USB protection, allows keybo mouse only, blocks all storage device 	
						Security features		
							Hard disk password	
						Keyboard	Some: Lenovo Calliope Keyboard (USB connector), black	
						-	Some: Lenovo Traditional Keyboard (USB connector), black	
						Mouse	Some: Lenovo Calliope Wireless Keyboard (2.4GHz via USB receiver), black	
						wouse	Some: Lenovo Calliope Mouse (USB connector), black Some: Lenovo Fingerprint Mouse (USB connector), Windows Hello support, t	
Core i7-8700T	6/12	2.4G / 4.0G	12 MB	DDR4-2666	UHD 630		<i>Some:</i> Lenovo Calliope Wireless Mouse (2.4GHz via USB receiver), black	
dual-channel capable * System automatically clocks down for the processors with lower memory controller					ory controller	 Optional dust filter one 2.5" bay for HDD/SSD, one PCle 3.0 x8 slot (low-profile), three M.2 slots (or 		
orage Some: Hard Drive / SATA 6.0Gb/s, 2.5", 5400 rpm or 7200 rpm Some: Solid State Drive (SSD) / SATA 6.0Gb/s, 2.5" Some: Solid State Drive (SSD) / PCIe NVMe, PCIe 3.0 x 4*, 32Gb/s, RAID 0/1 support (RAID preset only available via special bid model) * 128GB SSD M.2 (2242) PCIe NVMe only supports PCIe 3.0 x 2, 16Gb/s Some: Intel Optane™ Memory (not support Celeron / Pentium Processor), M.2 Some: DVD-ROM, slim (9.0mm), via USB external ODD box Some: DVD Burner (DVD±RW), slim (9.0mm), via USB external ODD box nboard SATA							one 2.5" bay for HDD/SSD, one PCIe 3.0 x8 slot (low-profile), three M.2 slots (on for WLAN, two for M.2 SSD), 2.5" HDD/SSD and PCIe card are mutually exclusiv	
							Dimensions (WxDxH) Weight (Approx.)	
					or), M.2			
					OX			
Intel HD Graphics 610/630 in processor, uses main memory, DirectX [®] 12, one DisplayPort [™] , one HDMI, one optional video port (2nd HDMI, VGA, 2nd DP, or USB 3.1 Type-C Gen1 with DisplayPort function), up to 3 independent displays;						VESA mount Floor Stand	Optional VESA mount bracket kit, supports VESA 75mm and 100mm Optional system floor stand for vertical orientation	
<i>Max resolution:</i> 4096x2304 (DP)@60Hz; 4096x2304 (Type-C)@60Hz;								
	4096x2160 (onboard HDMI)@24Hz; 2048x1536 (VGA)@50Hz					,		
4x Mini DisplayPort, up to 4 independent displays, works along with							Some: 1-year or 3-year, limited onsite service / service upgrades available	
Max resolution	10 FDIVI	880@60Hz ((un	to 2 Min	i DisplayPort).		Preload	Preloaded operating system	
4096x2160@60Hz ((up to 4 Mini DisplayPort)					(for Collage		Some: Windows® 10 Pro 64-bit Some: Windows 10 Home 64-bit Preloaded applications (only some listed)	
							Lenovo Vantage	
Intel Q370 Chipset							Microsoft Office preloaded;	
(Std.) one USB 3.1 Gen1 (Always On and fast charge), one USB 3.1 Type-C Gen 1, one microphone (3.5mm), one headphone / microphone combo jack (3.5mm)					ien 1.		purchase a product key to activate	
					5mm)		 Cyberlink PowerDVD (only for models with DVD / DVD±RW) Cyberlink Power2GO (only for models with DVD±RW) 	
2x USB 3.1 Gen2, 2x USB 3.1 Gen1, 1x ethernet (RJ-45), 1x DisplayPort, 1x HDM							Cybennik Powerzao (only for models with DVD±RW) LinkedIn	
2nd HDMI / serial / USB 3.1 Type-C Gen 1 with DP function); Port 2 for serial; Optional ports via PCIe card: 2x USB 3.1 Gen1 via PCIe x1, 4x serial (9-pin) via					2na DP /		ENERGY STAR [®] 7.0, EPEAT™ Gold rating (North America), ErP Lot 3, TCO,	
					-nin) via		TUV ultra low noise verified (coming soon, on some models), RoHS-compliant	
					via PCle x4	MIL-SPEC test	MIL-STD-810G military certification (Low Pressure [Altitude], High Temperature,	
							Low Temperature, Temperature Shock, Humidity, Sand and Dust, Vibration,	
Realtek ALC233VB2 / optional internal speaker (1.5 watt or 2 watt)						Fungus, Solar Radiation)		
						Accessories	For compatible accessories, please go to http://smartfind.lenovo.com	
	Processor Celeron G4900 Celeron G4920 Pentium Gold G5400 Pentium Gold G5400 Pentium Gold G5500 Core i3-8100 Core i3-8300 Core i5-8400 Core i5-8600 Core i5-8600 Core i5-8600 Core i5-8600 Core i3-8300T Core i3-8300T Core i3-8300T Core i3-8300T Core i5-8400T Core i5-8400T Core i5-8600T Core i5-8600T Core i5-8600T Core i5-8600T Core i5-8600T Core i5-8500T Core i5-8500T Core i5-8500T Core i5-8500T Core i5-8500T Core i5-8500T Core i5-8500T Core i5-8500T Core i5-8500T Core i5-8600T Core i5-8500T Core i5-8500T Core i5-8500T Core i5-8500T Core i5-8500T Core i5-800T Core i5-800T	Processor Cores / Threads Celeron G4900 2 / 2 Celeron G4920 2 / 2 Centron G4920 2 / 2 Pentium Gold G5400 2 / 4 Pentium Gold G5500 2 / 4 Pentium Gold G5500 2 / 4 Pentium Gold G5500 2 / 4 Core i3-8100 4 / 4 Core i3-8100 4 / 4 Core i5-8500 6 / 6 Core i3-8100T 2 / 4 Core i3-8100T 4 / 4 Core i3-8300T 4 / 4 Core i3-8300T 4 / 4 Core i3-8300T 6 / 6 Core i5-8600T 6 / 6 Core i7-8700T 6 / 12 32GB max, DDR4-2666*, two 2 4 Aual-channel capable * System automatically clocks o Some: Solid State Drive (SSD Some: Nat SSD (support up to RAID 01 support (RAII) * 128GB SD M.2 (2242	Processor Cores / Threads Frequency Base/Max(GHz) Celeron G4900 2 / 2 3.1G Celeron G4900 2 / 2 3.2G Pentium Gold G5400 2 / 4 3.7G Pentium Gold G5500 2 / 4 3.9G Core i3-8100 4 / 4 3.6G Core i3-8100 4 / 4 3.6G Core i3-8300 4 / 4 3.7G Core i5-8400 6 / 6 2.8G / 4.0G Core i5-8500 6 / 6 3.0G / 4.1G Core i5-8500 6 / 6 3.1G / 4.3G Core i7-8700 6 / 12 3.2G / 4.6G Celeron G4900T 2 / 2 2.9G Pentium Gold G5500T 2 / 4 3.1G Core i3-8100T 4 / 4 3.2G Core i3-8300T 4 / 4 3.2G Core i3-8300T 4 / 4 3.2G Core i5-8500T 6 / 6 1.7G / 3.3G Core i5-8500T 6 / 6 2.1G / 3.5G Core i5-8500T 6 / 6 2.3G / 3.7G Core i7-8700T 6 / 12	Processor Cores / Threads Frequency Base/Max(GHz) Cache Celeron G4900 2 / 2 3.1G 2 MB Pentium Gold G5400 2 / 4 3.7G 4 MB Pentium Gold G5500 2 / 4 3.8G 4 MB Pentium Gold G5500 2 / 4 3.8G 4 MB Pentium Gold G5600 2 / 4 3.8G 4 MB Core i3-8100 4 / 4 3.6G 6 MB Core i3-8500 6 / 6 2.8G / 4.0G 9 MB Core i5-8500 6 / 6 3.0G / 4.1G 9 MB Core i7-8700 6 / 12 3.2G / 4.6G 12 MB Celeron G4900T 2 / 2 2.9G 2 MB Pentium Gold G5500T 2 / 4 3.1G 4 MB Core i3-8100T 4 / 4 3.2G 8 MB Core i5-8600T 6 / 6 1.7G / 3.3G 9 MB Core i5-8600T 6 / 6 2.1G / 3.5G 9 MB Core i5-8600T 6 / 6 2.3G / 3.7G 9 MB Core i5-8600T 6 / 6 2.1	Processor Cores / Threads Frequency Base/Max(GHz) Cache Memory Support (Up to) Celeron G4900 2 / 2 3.1G 2 MB DDR4-2400 Celeron G4920 2 / 2 3.2G 2 MB DDR4-2400 Pentium Gold G5500 2 / 4 3.7G 4 MB DDR4-2400 Pentium Gold G5500 2 / 4 3.9G 4 MB DDR4-2400 Core i3-8100 4 / 4 3.6G 6 MB DDR4-2400 Core i3-8100 4 / 4 3.7G 8 MB DDR4-2400 Core i3-800 6 / 6 3.0G / 4.1G 9 MB DDR4-2666 Core i5-8500 6 / 6 3.1G / 4.1G 9 MB DDR4-2666 Core i5-8600 6 / 12 3.2G / 4.6G 12 MB DDR4-2666 Core i3-8100T 2 / 4 3.1G 4 MB DDR4-2400 Core i3-8100T 4 / 4 3.2G 4 MB DDR4-2400 Core i3-8100T 4 / 4 3.2G 4 MB DDR4-2400 Core i3-8100T 6 / 6 1.7G / 3.3G 9	Processor Threads Base/Max(GHz) Value (Up to) Graphics Celeron G4900 2 / 2 3.1G 2 MB DDR4-2400 UHD 610 Pentium Gold G5500 2 / 4 3.7G 4 MB DDR4-2400 UHD 630 Pentium Gold G5500 2 / 4 3.8G 4 MB DDR4-2400 UHD 630 Core i3-8100 4 / 4 3.6G 6 MB DDR4-2400 UHD 630 Core i5-8400 6 / 6 2.8G / 4.0G 9 MB DDR4-2666 UHD 630 Core i5-8600 6 / 6 3.0G / 4.1G 9 MB DDR4-2666 UHD 630 Core i7-8700 6 / 12 3.2G / 4.6G 12 MB DDR4-2666 UHD 630 Core i7-8700 6 / 12 3.2G / 4.6G 12 MB DDR4-2400 UHD 630 Core i3-8100T 2 / 4 3.1G 4 MB DDR4-2400 UHD 630 Core i5-8400T 6 / 6 3.1G / 4.3G 9 MB DDR4-2400 UHD 630 Core i5-8300T 6 / 6 3.0G / 4.1G 9 MB DDR4-266	Processor Cores / The absorbed and the processor is an absorbed and the processor is a special bid model (Up to absorbed and the processor is a special bid model) Memory Support Integrated (Up to bid processor) Celeron G4900 2 / 2 3.1G 2 MB DDR4-2400 UHD 610 Celeron G4900 2 / 2 3.2G 2 MB DDR4-2400 UHD 610 Pentium Gold G5600 2 / 4 3.8G 4 MB DDR4-2400 UHD 630 Core i3-8100 4 / 4 3.7G 4 MB DDR4-2400 UHD 630 Core i3-8300 6 / 6 3.8G 4 MB DDR4-2600 UHD 630 Core i3-8300 6 / 6 3.6G / 4.3G 9 MB DDR4-2666 UHD 630 Core i3-8300 6 / 1 2.2G / 4.6G 12 MB DDR4-2666 UHD 630 Core i3-8300T 6 / 6 3.1G / 4.3G 9 MB DDR4-2666 UHD 630 Core i3-8300T 6 / 6 1.7G / 3.3G 9 MB DDR4-2666 UHD 630 Core i3-8300T 6 / 6 1.7G / 3.3G 9 MB DDR4-2666 UHD 630 <t< td=""></t<>	

Note: The specifications above may not be available in all regions.

Lenovo

ThinkCentre M920x Tiny





(intel) inside

(intel) inside





(intel)





(intel) inside