




Screen size:  
13" - 32"



Max load:  
41 7/8 lbs



VESA:  
75x75 - 100x100 mm



Height adjustment:  
0"

|                                      |                                 |
|--------------------------------------|---------------------------------|
| Made of                              | Plastic, SPCC cold rolled steel |
| Max. load of monitors/TVs            | 41 7/8 lbs                      |
| VESA                                 | 75x75, 100x100 mm               |
| Screen size (min)                    | 13"                             |
| Screen size (max)                    | 32"                             |
| Number of screens                    | 1                               |
| Wall distance (max)                  | 23.82"                          |
| Height adjustment (max)              | 0"                              |
| Upward tilt angle (max)              | 90°                             |
| Downward tilt angle (max)            | 90°                             |
| Angle of rotation (range)            | 360°                            |
| Warranty                             | 5 years                         |
| Overall dimensions complete          | 61.5x11.5x53.4                  |
| Dimensions of the individual package | 1 7/8" x 1 7/8" x 0 7/8"        |
| Overall dimensions of the group pack | 2 1/4 x 2 x 1 1/2 inch          |
| Individual package volume            | 7.4 ft³                         |
| Gross weight individual              | 8 7/8 lbs                       |
| Group gross weight                   | 79 7/8 lbs                      |
| Number in group                      | 4 item(s)                       |

- ONKRON mounting solutions:
- Are suitable for continuous 24/7 use when installed and used in accordance with the applicable product documentation, installation instructions, and load specifications;
  - Are intended for professional and commercial installations;
  - Are designed to support secure and reliable installation of compatible displays in public environments;
  - Comply with standard safety, installation, and mechanical requirements applicable to professional display mounting solutions;
  - May be used in high-traffic public spaces, provided that installation is performed by qualified personnel and in accordance with all applicable local regulations, safety standards, and project requirements.