



Net weight 4.89kg

## MILO 12 Slim & compact Mini-ITX enclosure

- Compatible with Mini-ITX motherboard & ATX PSU
- Supports 3-slot graphics cards up to 345mm length
- · Horizontal or vertical orientation
- Modular design with 4 removable panels (top, left, right, bottom)
- ATX to SFX adapter bracket included -9.5mm slim ODD can be installed when using SFX PSU
- CPU cooler opening on motherboard back plate for convenient assembly and upgrade

## **Product Specifications**

## Model No. Material SST-ML12B Plastic bezel, steel body Motherboard **Drive** bay Mini-ITX 9.5mm slim optical bay (only when used in conjunction with SFX-L PSU) Internal Limitation of CPU cooler **Cooling system** Front 80mm x 1 (supports up to 15mm thickness) Limitation of VGA card **Expansion slot** Length: 345mm Height: 160mm Limitation of PSU **Power supply** Standard PS2 (ATX) / SFX-L 160mm Front I/O port Dimension USB Type-C x 1, USB 3.0 Type-A x 2, combo audio x 1 105mm (W) x 393mm (H) x 378mm (D), 15.6 liters 4.13" (W) x 15.47" (H) x 14.88 (D), 15.6 liters

<sup>\*</sup> The included riser card does not support PCIe 5.0. However, you can still use it with any PCIe 5.0 supported card and motherboard by selecting to run at PCIe 4.0 setting in your motherboard BIOS/UEFI.





## Great component compatibility and versatility

Supports up to 3-slot, 345mm length graphics cards, with an included PCIe  $4.0\,\mathrm{riser}$  card.



