



# Delock External Enclosure for M.2 NVMe PCIe SSD with SuperSpeed USB 20 Gbps (USB 3.2 Gen 2x2) USB Type-C™ female

## Description

This enclosure by Delock enables the installation of an **M.2 PCIe NVMe SSD** in 2280 format, it can be connected via USB to the PC or laptop. The **robust metal housing with cooling fins** ensures an optimum temperature of the memory.

### SuperSpeed USB 20 Gbps

The enclosure allows a data transfer rate of **20 Gbps** on the USB-C™ port.



## Specification

- Connectors:
  - external: 1 x SuperSpeed USB 20 Gbps (USB 3.2 Gen 2x2) USB Type-C™ female
  - internal: 1 x 67 pin M.2 key M slot
- Chipset: Asmedia ASM2364
- Supports M.2 modules in format 2280 with key M or key B+M based on PCIe (NVMe)
- Maximum height of the components on the module: 1.5 mm, application of double-sided assembled modules supported
- Supports NVM Express (NVMe)
- Data transfer rate up to 20 Gbps
- LED indicator for power and access
- Metal housing
- Dimensions (LxWxH): ca. 99 x 50 x 18 mm
- Hot Plug, Plug & Play

## System requirements

- Android 9.0 or above
- Chrome OS 78.0 or above
- Linux Kernel 4.6 or above
- Mac OS 10.15.3 or above
- Windows 8.1/8.1-64/10/10-64
- PC or laptop with a free USB Type-C™ port
- PC or laptop with a free Thunderbolt™ 3 port

## Package content

- External enclosure M.2
- Mounting material
- 1 x thermal conductive pad
- Screwdriver
- Cable USB-C™ male to USB-C™ male, length ca. 50 cm
- User manual

## Item no. 42000

EAN: 4043619420001

Country of origin: China

Package: • Retail Box



Images



**General**

|                             |                           |
|-----------------------------|---------------------------|
| Supported operating system: | Android 9.0 or above      |
|                             | Chrome OS 78.0 or above   |
|                             | Linux Kernel 4.6 or above |
|                             | Mac OS 10.15.3 or above   |
|                             | Windows 10 32-bit         |
|                             | Windows 10 64-bit         |
|                             | Windows 8.1 32-bit        |
|                             | Windows 8.1 64-bit        |

|                   |                                                                                |
|-------------------|--------------------------------------------------------------------------------|
| Supported module: | Supports M.2 modules in format 2280 with key M or key B+M based on PCIe (NVMe) |
|-------------------|--------------------------------------------------------------------------------|

|                                                 |                                                                |
|-------------------------------------------------|----------------------------------------------------------------|
| Maximum height of the components on the module: | 1.5 mm application of double-sided assembled modules supported |
|-------------------------------------------------|----------------------------------------------------------------|

**Interface**

|           |                                                                 |
|-----------|-----------------------------------------------------------------|
| External: | 1 x SuperSpeed USB 20 Gbps (USB 3.2 Gen 2x2) USB Type-C™ female |
| Internal: | 1 x 67 pin M.2 key M slot                                       |

**Technical characteristics**

|                     |                 |
|---------------------|-----------------|
| Chipset:            | Asmedia ASM2364 |
| Data transfer rate: | up to 20 Gbps   |

**Physical characteristics**

|                   |       |
|-------------------|-------|
| Housing material: | metal |
| Length:           | 99 mm |
| Width:            | 50 mm |
| Height:           | 18 mm |
| Colour:           | black |