D&LLTechnologies

Specification Sheet



PowerEdge R660xs

Best choice in balanced and dense compute for the most popular IT applications

Buy the performance and density you need

The new Dell PowerEdge R660xs is a 1U, two-socket rack server. Buy the best fit in dense performance with this purpose-built 1U system. Focused on delivering the latest technology to power the most popular applications and workloads used by businesses today, including virtualization, scale out-database and high performance compute. All delivered in a thoughtfully crafted platform that will provide dense compute that fits in your current infrastructure.

Easily configurable

- Add up to two 5th generation Intel® Xeon® Scalable processors with up to 28 cores and 4th generation Intel® Xeon® Scalable processors with up to 32 cores per socket for faster performance
- · Accelerate in-memory workloads with up to 16 DDR5 RDIMMS up to 5200 MT/sec
- Improve data throughput and reduce latency with support up to 5 I/O devices (up to 3 PCIe slots, 1 OCP 3.0 networking slot, and 1 dedicated PERC slot)
- Storage options include up to 4x 3.5" HDDs/SSDs; or up to 10x 2.5" HDDs/SSDs/NVMe

A breeze to cool

- · Thoughtfully designed to fit in your current air-cooled infrastructure
- · Alleviate the worry about expensive liquid cooling retrofitting to your data center
- · Sychronize your workload needs with a tailored performance configuration that is air-cooled
- Minimize the carbon footprint of your data center by better matching the system power consumption with anticipated workload requirements

Cyber Resilient Architecture for Zero Trust IT environment & operations

Security is integrated into every phase of the PowerEdge lifecycle, including protected supply chain and factory-to-site integrity assurance. Silicon-based root of trust anchors end-to-end boot resilience while Multi-Factor Authentication (MFA) and role-based access controls ensure trusted operations.

Increase efficiency and accelerate operations with autonomous collaboration

The Dell OpenManage[™] systems management portfolio delivers a secure, efficient, and comprehensive solution for PowerEdge servers. Simplify, automate and centralize one-to-many management with the OpenManage Enterprise console and iDRAC.

Sustainability

From recycled materials in our products and packaging, to thoughtful, innovative options for energy efficiency, the PowerEdge portfolio is designed to make, deliver, and recycle products to help reduce the carbon footprint and lower your operation costs. We even make it easy to retire legacy systems responsibly with Dell Technologies Services.

Rest easier with Dell Technologies Services

Maximize your PowerEdge Servers with comprehensive services ranging from Consulting, to ProDeploy and ProSupport suites, Data Migration and more – available across 170 locations and backed by our 60K+employees and partners.

PowerEdge R660xs

The Dell PowerEdge R660xs offers compelling performance in a purpose-built system with the latest PCIe Gen 5 bandwidth and storage to support:

- Virtualization / Cloud
- Scale-Out Database
- High Performance Compute

Feature	Technical Specifications	
Processor	Up to two 5th Generation Intel Xeon Scalable processor with up to 28	cores and 4th Generation Intel Xeon Scalable processor with up to
	32 cores per processor	
Vemory	16 DDR5 DIMM slots, supports RDIMM 1.5 TB max, speeds up to 5200 MT/s, Supports registered ECC DDR5 DIMMs only	
Storage controllers	Internal Controllers: PERC H965i, PERC H755, PERC H755N, PERC H355, HBA355i, HBA465i	
5	Internal Boot: Boot Optimized Storage Subsystem (BOSS-N1): HWRAID 1, 2 x M.2 NVMe SSDs (cold swap) or USB	
	External HBA (non-RAID): HBA355e	
	Software RAID: S160	
Drive Bays	Front bays:	Rear bays:
	0 drive bay	• Up to 2 x 2.5-inch SAS/SATA/NVMe (HDD/SSD) max 15.2 TB
	• Up to 4 x 3.5-inch SAS/SATA (HDD/SSD) max 96 TB	
	• Up to 8 x 2.5-inch SAS/SATA/NVMe (HDD/SSD) max 122.88 TB	
	• Up to 10 x 2.5-inch SAS/SATA/NVMe (HDD/SSD) max 153.6 TB	
Hot swap Redundant	 1800 W Titanium 200—240 VAC or 240 VDC 	 1100 W -(48V — 60V) DC
Power Supplies	 1400 W Titanium 100—240 VAC or 240 VDC 	 800 W Platinum 100—240 VAC or 240 VDC
	 1400 W Platinum 100—240 VAC or 240 VDC 	 700 W Titanium 200—240 VAC or 240 VDC
	 1400 W Titanium 277 VAC or HVDC (HVDC stands for High- 	 600 W Platinum 100—240 VAC or 240 VDC
	Voltage DC, with 336V DC)	
	 1100 W Titanium 100—240 VAC or 240 VDC 	
Cooling Options	Air cooling	
Fans	Standard (STD) fans / High performance Gold (VHP) fans, Up to 7	7 hot swappable fans
Dimensions and	 Height – 42.8 mm (1.68 inches) 	 Depth – 748.79 mm (29.85 inches) with bezel
Weight	 Width – 482 mm (18.97 inches) 	712.95 mm (28.05 inches) without bezel
		 Weight – 19.45 Kg (55.33 pound)
Form Factor	1U rack server	
Embedded	iDRAC9	iDRAC Service Module
Management	iDRAC Direct	Quick Sync 2 wireless module
	iDRAC RESTful API with Redfish	
Bezel	Optional LCD bezel or security bezel	
OpenManage	CloudIQ for PowerEdge plug in	OpenManage Integration with Windows Admin Center
Software	OpenManage Enterprise	OpenManage Power Manager plugin
	OpenManage Enterprise Integration for VMware vCenter	OpenManage Service plugin
	OpenManage Integration for Microsoft System Center	OpenManage Update Manager plugin
Mobility	OpenManage Mobile	
OpenManage	BMC Truesight	Red Hat Ansible Modules
Integrations	Microsoft System Center	Terraform Providers
Integrations	-	
Socurity	OpenManage Integration with ServiceNow Cryptographically signed firmware	VMware vCenter and vRealize Operations Manager Secured Component Varification (Hardware integrity check)
Security		Secured Component Verification (Hardware integrity check)
	Data at Rest Encryption (SEDs with local or external key mgmt)	Silicon Root of Trust
	Secure Boot	System Lockdown (requires iDRAC9 Enterprise or Datacenter)
	Secure Erase	 TPM 2.0 FIPS, CC-TCG certified, TPM 2.0 China NationZ
Embedded NIC	2 x 1 GbE LOM card	
Network options	1 x OCP card 3.0 (optional)	
Ports	Front Ports	Rear Ports
	1 x iDRAC Direct (Micro-AB USB) port, 1 x USB 2.0, 1 x VGA	• 1 x Dedicated iDRAC Ethernet port, 1 x USB 2.0, 1 x USB 3.0,
	Internal Ports	1 x VGA, 1 x Serial (optional)
	• 1 x USB 3.0 (optional)	
PCIe	1 CPU Configuration: Up to 2 PCIe slots (1 x16 Gen4 + 1 x8 Gen5)	
	• 2 CPU configuration: Up to 3 PCIe Gen4 slots (1 x16 Gen4 + 2 x8 Gen4) or up to 2 PCIe Gen5 slots (1 x16 Gen5 + 1 x8 Gen5)	
Operating System	 Microsoft Windows Server with Hyper-V 	VMware ESXi
and Hypervisors	Red Hat Enterprise Linux	Canonical Ubuntu Server LTS
	SUSE Linux Enterprise Server.	For specifications and interoperability details, see Dell.com/OSsup
OEM-ready version	From bezel to BIOS to packaging, your servers can look and feel as if	
CLIVITICALLY VEISION	i tom bezer to broo to packaging, your servers can nook allu leel as it	andy word designed and built by you. For more information, VISIL Delice

APEX Flex on Demand

Acquire the technology you need to support your changing business with payments that scale to match actual usage. For more information, visit https://www.delltechnologies.com/en-us/payment-solutions/flexible-consumption/ flex-on-demand.htm.

Discover more about PowerEdge servers



Learn more about our

PowerEdge servers



Learn more about our systems management solutions



Search our Resource Library



Follow PowerEdge servers on Twitter



Contact a Dell Technologies Expert for Sales or Support

Copyright © 2024 Dell Inc. or its subsidiaries. All Rights Reserved. Dell Technologies, Dell, and other trademarks are trademarks of Dell Inc. or its subsidiaries. Other trademarks may be trademarks of their respective owners.

