

# **OVERVIEW**



1. USB 3.2 Gen 1	5. USB 3.2 Gen 1				
2. Ethernet (RJ-45)	6. HDMI				
3. Kensington Nano Security Slot	7. USB-C 3.2 Gen 1				
4. Power connector	8. Headphone / microphone combo jack (3.5mm)				



# **PERFORMANCE**

### **Processor**

### **Processor Family**

AMD Athlon<sup>™</sup> or AMD Ryzen<sup>™</sup> 3/5 Processor

### Processor\*\*

Processor Name	Cores	Threads	Base Frequency	Max Frequency	Cache	Processor Graphics	
AMD Athlon Gold 7220U	2	4	2.4GHz	3.7GHz 1MB L2 / 4MB L		AMD Radeon™ 610M Graphics	
AMD Athlon Silver 7120U	2 2 2.4GHz		2.4GHz	3.5GHz	1MB L2 / 2MB L3	AMD Radeon 610M Graphics	
AMD Ryzen 3 7320U	4	8	2.4GHz	4.1GHz	2MB L2 / 4MB L3	AMD Radeon 610M Graphics	
AMD Ryzen 5 7520U	4	8	2.8GHz	4.3GHz	2MB L2 / 4MB L3	AMD Radeon 610M Graphics	

# **Operating System**

### Operating System\*\*

- Windows® 11 Home
- Windows 11 Home Single Language
- Windows 11 Pro
- No operating system

# **Graphics**

# **Graphics**

Graphics	Туре	Memory	TGP	Key Features	
AMD Radeon 610M	Integrated	Shared	Share CPU TDP	DirectX® 12	

# **Monitor Support**

### **Monitor Support**

Supports up to 3 independent displays (native display and 2 external monitors via HDMI® and USB-C®)

- HDMI supports up to 3840x2160@30Hz
- USB-C supports up to 4096x2160@60Hz

# **Chipset**

### Chipset

AMD SoC (System on Chip) platform

# **Memory**

### **Max Memory**

- 8GB soldered memory, not upgradable
- 16GB soldered memory, not upgradable

#### **Memory Slots**

Memory soldered to systemboard, no slots, dual-channel

# **Memory Type**

LPDDR5-5500

# **Storage**

### Storage Support[1]

One drive, up to 512GB M.2 2242 SSD

# Storage Slot

One M.2 2242 PCIe® 3.0 x2 slot

# Storage Type\*\*



Disk Type	Interface	Offering
M.2 2242 SSD	PCIe NVMe®, PCIe 3.0 x4[2]	128GB
M.2 2242 SSD	PCIe NVMe, PCIe 4.0 x4[3]	256GB / 512GB

#### Notes:

- [1] The storage capacity supported is based on the test results with current Lenovo® storage offerings.
- [2] The SSD with PCle 3.0x4 is downgraded to closer to PCle 3.0x2 due to the system slot limitation.
- [3] The SSD with PCIe 4.0x4 is downgraded to closer to PCIe 3.0x2 due to the system slot limitation.

# Removable Storage

#### **Card Reader**

No card reader

## Multi-Media

### **Audio Chip**

High Definition (HD) Audio, Realtek® ALC3287 codec

#### Speakers

Stereo speakers, 1.5W x2, Dolby® Audio™

#### Microphone

Dual-microphone array

#### Camera

HD 720p, with privacy shutter, fixed focus

## **Battery**

### Battery\*\*

- Integrated Li-Polymer 38Wh battery, supports Rapid Charge (charge up to 80% in 1hr)
- Integrated Li-Polymer 47Wh battery, supports Rapid Charge (charge up to 80% in 1hr)

### Max Battery Life[1]

Models with 38Wh battery:

MobileMark® 2018: 8.7 hr

Local video (1080p) playback@150nits: 14.4 hr

Models with 47Wh battery:

MobileMark 2018: 11.6 hr

Local video (1080p) playback@150nits: 15.1 hr

### Notes:

[1] All battery life claims are approximate maximum and based on results using the MobileMark 2014, MobileMark 2018, MobileMark 25, JEITA 2.0, continuous 1080p video playback (with 150nits brightness and default volume level) or Google Power Load Test (PLT) battery-life benchmark tests. Actual battery life will vary depending on many factors such as product configuration and usage, software use, wireless functionality, power management settings, and screen brightness. The maximum capacity of the battery will decrease with time and use.

### **Power Adapter**

### Power Adapter\*\*[1]

- 65W round tip (3-pin) AC adapter, 100-240V, 50-60Hz
- 65W USB-C (3-pin) AC adapter, supports PD 3.0, 100-240V, 50-60Hz<sup>[2]</sup>

#### Notes:

- [1] AC adapter offerings depend on the country.
- [2] Only MT 83CQ configured with 65W USB-C AC adapter is TCO certified.

# **DESIGN**

# **Display**

### Display\*\*



	Size	Resolution	Touch	Туре	Brightness	Surface	Aspect Ratio	Contrast Ratio	Color Gamut	Refresh Rate	Viewing Angle (L/R/U/D)	Key Features
1	5.6"	FHD (1920x1080)	None	TN	250nits	Anti- glare	16:9	500:1	45% NTSC	60Hz	45°/45°/15°/35°	TÜV Low Blue Light (Software)
1	5.6"	FHD (1920x1080)	None	IPS[1]	300nits	Anti- glare	16:9	800:1	45% NTSC	60Hz	85°/85°/85°/85°	TÜV Low Blue Light (Software)

### **Touchscreen**

Non-touch

Notes:

[1] IPS (in-plane switching) technology may refer to IPS, PLS, ADS, AHVA, AAS.

# **Input Device**

# Keyboard

6-row, spill-resistant, multimedia Fn keys, SMB Service Hot key, numeric keypad

### **Keyboard Backlight**

Non-backlight

## Touchpad

Buttonless Mylar® surface multi-touch touchpad, supports Precision TouchPad (PTP), 62 x 104 mm (2.44 x 4.09 inches)

#### Mechanical

### Dimensions (WxDxH)[1]

359.2 x 235.8 x 19.9 mm (14.14 x 9.28 x 0.78 inches)

#### Weight<sup>[2]</sup>

Starting at 1.65 kg (3.64 lbs)

### Case Color\*\*

- · Arctic grey
- Business black

## Surface Treatment\*\*

- IMR (in-mold decoration by roller)
- Texture

# **Case Material**

PC-ABS (top), PC-ABS (bottom)

### Notes:

- [1] The system dimensions may vary depending on configurations.
- [2] The system weight is approximate and based on results in Lenovo lab, which varies depending on the source of component, variance of the distribution of each component, and manufacturing process. It may not be the exact weight for each specific model.

# CONNECTIVITY

### Network

### **Ethernet**

Gigabit Ethernet, 1x RJ-45

### WLAN + Bluetooth®\*\*[1]

- 802.11ac 2x2 Wi-Fi® + Bluetooth 5.1, M.2 card
- Wi-Fi 6, 802.11ax 2x2 Wi-Fi + Bluetooth 5.1, M.2 card<sup>[2]</sup>

### Notes:

- [1] Bluetooth 5.2 is hardware ready but may run at a lower version due to OS limitations.
- [2] Wi-Fi 6 full features might be limited by country-level restrictions.



### Ports<sup>11</sup>

#### **Standard Ports**

- 1x Ethernet (RJ-45)
- 1x HDMI 1.4b
- 1x Headphone / microphone combo jack (3.5mm)
- 1x Power connector
- 1x USB-C 3.2 Gen 1 (support data transfer, Power Delivery (20V only) and DisplayPort™ 1.2)
- 2x USB 3.2 Gen 1

#### Notes:

[1] The transfer speed of following ports will vary and, depending on many factors, such as the processing speed of the host device, file attributes and other factors related to system configuration and your operating environment, will be slower than theoretical speed.

USB 2.0: 480 Mbit/s;

USB 3.2 Gen 1 (SuperSpeed USB 5Gbps, formerly USB 3.0 / USB 3.1 Gen 1): 5 Gbit/s;

USB 3.2 Gen 2 (SuperSpeed USB 10Gbps, formerly USB 3.1 Gen 2): 10 Gbit/s;

USB4® 20Gbps / USB 3.2 Gen 2x2 (SuperSpeed USB 20Gbps): 20 Gbit/s;

USB4 40Gbps (USB 40Gbps): 40 Gbit/s;

Thunderbolt™ 3/4: 40 Gbit/s.

# **Docking**

### **Docking**

Various docking solutions supported via USB-C.

For more compatible docking solutions, please visit Docking for Lenovo V15 G4 AMN

# **SECURITY & PRIVACY**

## **Security**

### **Security Chip**

Firmware TPM 2.0 integrated in SoC

#### **Physical Locks**

Kensington® Nano Security Slot™, 2.5 x 6 mm

### **Fingerprint Reader**

No fingerprint reader

## **BIOS Security**

- Power-on password
- Supervisor password
- Hard disk password

### **Other Security**

Camera privacy shutter

# **SERVICE**

# **Warranty**<sup>[1]</sup>

# **Base Warranty\*\***

- 1-year courier or carry-in service
- 2-year (1-yr battery) courier or carry-in service
- No base warranty

# Notes:

[1] The warranty upgrades may be bundled with some models, please check the "Included upgrade" column in the specific model's configurations. For more service extensions, please go to <a href="https://smartfind.lenovo.com/">https://smartfind.lenovo.com/</a>. To learn more details of warranty policy, please access <a href="https://pcsupport.lenovo.com/warranty">https://pcsupport.lenovo.com/warranty</a>.

# ENVIRONMENTAL



# **Operating Environment**

#### Temperature[1]

- At altitudes up to 2438 m (8,000 ft)
  - Operating: 5°C to 35°C (41°F to 95°F)
  - Storage: 5°C to 43°C (41°F to 109°F)
- At altitudes above 2438 m (8,000 ft)
  - Maximum temperature when operating under the unpressurized condition: 31.3°C (88°F)

### Humidity

- Operating: 8% to 95% at wet-bulb temperature 23°C (73°F)
- Storage: 5% to 95% at wet-bulb temperature 27°C (81°F)

#### Altitudo

Maximum altitude (without pressurization): 3048 m (10,000 ft)

#### Notes:

[1] When you charge the battery, its temperature must be no lower than 10°C (50°F).

# **CERTIFICATIONS**

### 

### **Green Certifications**[2]

- (Optional) ENERGY STAR® 8.0
- (Optional) EPEAT™ Silver Registered<sup>[3]</sup>
- (Optional) TCO Certified 9.0
- ErP Lot 3
- FSC certified package
- · RoHS compliant

#### Notes:

- [1] The items listed under the "Green Certifications" section may not only refer to certification but also registration or self-declaration.
- [2] TCO Certified 9.0 is only available for MT 83CQ (excluding India and Brazil).
- [3] EPEAT is registered where applicable, please see https://www.epeat.net for registration status by country.

# **Other Certifications**

# Mil-Spec Test

MIL-STD-810H military test passed

### **Other Certifications**

TÜV Rheinland® Low Blue Light (Software Solution)

- Feature with \*\* means that only one offering listed under the feature is configured on selected models.
- Lenovo reserves the right to change specifications or other product information without notice. Lenovo is not
  responsible for photographic or typographical errors. LENOVO PROVIDES THIS PUBLICATION "AS IS,"
  WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES
  OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some jurisdictions do not allow
  disclaimer of express or implied warranties in certain transactions, therefore this disclaimer may not apply to
  you.
- The specifications on this page may not be available in all regions, and may be changed or updated without notice.







AMD





AMD





AMD

AMD

AMD