

- Supports all renowned RGB synchronization systems
- Rainbow RGB fan with a +5V addressable LED connector
- High-Performance (90% Eff. @230V) RGB Gaming

The highly innovative **Photon GOLD series** are aimed at gamers and enthusiasts, looking for the ultimate in power, longevity, performance and of course, RGB lighting effects and all this at a highly affordable price.

The +5V addressable LED connector of the PSU offers an extreme wide range of lightening modes and effects, supports all renowned RGB lightening synchronization systems such as **ASUS™ AURA SYNC**, **MSI™ MYSTIC LIGHT SYNC**, **ASROCK™ POLYCHROME SYNC** and **GIGABYTE™ RGB FUSION**.

Photon GOLD series in addition provide a vast number of predefined and MB-independent lightening modes and effects, which are set via a button on the rear of the power supply while a minute toggle switch, equally located on the rear of the PSU allows the choice between the M/B RGB control (if available) or the integrated modes and effects. With its vast amount of extra-long cables and an **efficiency of 90% @230V**, the models of the **Photon GOLD series** stands out as a perfect RGB gaming solutions.



Technical data







| | |
|-------------------------------|---|
| Model | Photon Gold 650W |
| Artikel no. | GDP-650C-RGB |
| EAN code | 0753263075895 |
| Weight (without/with package) | 2.12 kg / 2.52 kg |
| Specification | ATX 12V 2.3 |
| Form factor | PS II |
| Efficiency | >90% |
| PFC | Active PFC (0.9) (only 230V) |
| Fan | 140mm silent RGB Rainbow fan |
| Lightning modes | 14x dynamic modes integrated |
| Dimension (DxWxH) | 160mm x 150mm x 87mm |
| Security | AFC (Automatic Fanspeed Control) OPP (Overload protection) OVP (Overvoltage protection) SCP (Short-circuit protection) SIP (Surge & Inrush Protection) UVP (Undervoltage protection) |
| Warranty | 24 Months |

Output data

| Photon Gold 650W | AC Input | 200-240V 47- 63Hz 5A | | | | |
|------------------|---------------------|----------------------|-----|-------|------|-------|
| | DC Output | +3.3V | +5V | + 12V | -12V | +5VSB |
| | Max. Current | 20A | 20A | 53A | 0.3A | 2.5A |
| | Max. Combined Power | 120W | | 636W | 3.6W | 12.5W |
| | | | | | | 650W |

* The listed specifications may be altered at any point in time without any pre-notice.

** Chieftec® is a registered trademark. All other brands and/or logos are property of the respective owners.

| | Cable | Connectors | Length (mm) |
|---|-------------------|------------|-----------------|
|  | 24 PIN (20+4) | 1 | 550 |
|  | 8 PIN PCI-E (6+2) | 4 | 2x 550/150 |
|  | 8 PIN EPS | 1 | 550 |
|  | SATA | 6 | 2x 550/150/150 |
|  | MOLEX | 3 | 550/150/150/150 |
| | FLOPPY | 1 | |
|  | RGB LED PIN | 1 | 550 |

Certification



* The listed specifications may be altered at any point in time without any pre-notice.

** Chieftec® is a registered trademark. All other brands and/or logos are property of the respective owners.