



ICY BOX IB-RD2253-C31

External RAID enclosure
for 2x 2.5" SATA SSD

Key features

- Data availability – external and compact
- Versatility – RAID mode 1/0/JBOD (LARGE)/ SINGLE
- Performance advantage – with USB 3.2 Gen 2 transfer rate of up to 10 Gbit/s
- High quality – made of durable aluminium and robust plastic
- Compatibility – Windows®, macOS® or Chrome OS™



Packing content

1x IB-RD2253-C31, 1x USB Type-C® cable, 1x USB Type-A cable
1x Power adapter, 1x Screw set with screwdrivers,
1x Manual

Technical data

Model	IB-RD2253-C31
Article no.	61028
EAN code	4250078173618
Brand	ICY BOX
Colour	Black
Material	Aluminium, plastic
Interface to host computer	USB 3.2 Gen 2 Type-C® / Type-A
Transfer rate	Up to 10 Gbit/s
HDD size	2.5"
HDD height	Up to 9.5 mm
HDD interface	SATA I,II,III (6 Gbit/s)

HDD capacity	Unlimited
UASP support	Yes
Plug & Play	Yes
RAID level	0, 1, LARGE, Single
LED	Power, access and RAID mode
Cooling	Passive
Power supply	5 V@2 A power adapter
DC-Plug dimension	3.5 x 1.35 x 8 mm (Ø outside x Ø inside x length)
Operating system	Windows®, macOS®, Chrome OS™
System requirements	One free USB 3.2 Gen 2 Type-C® or Type-A port One free 230 V EU power socket



ICY BOX **IB-RD2253-C31** External RAID enclosure for 2x 2.5" SATA SSD



Failure safety or performance

Double the security of your data by mirroring with RAID 1 or push the performance of your drives and data transfer rates to the limits with RAID 0. Use each installed drive separately with SINGLE mode or the entire available storage volume in LARGE mode.



Data transfer at top speed

With USB 3.2 Gen 2 you enjoy data transfer rates of up to 10 Gbit/s without waiting times or delay and can transport files from one drive to another within seconds. To suit your current equipment best, the IB-RD2253-C31 comes fully equipped with both a USB Type-C® and a Type-A cable.



Compact and resilient

The enclosure is made from aluminium and therefore very durable. Designed with passive cooling and without a fan, both professional and private workplaces benefit from this very silent setup. A status LED keeps you informed about the current state of the installed drives at all times.

Logistical data

Packing unit:	20 pcs. / carton
Total weight:	10.74 kg
Gross weight (with packing):	0.494 kg
Net weight:	0.187 kg

Dimension/carton:	506x341x270 mm
Dimension (with packing):	66x131x231 mm
Dimension of article:	130x84x26 mm
Country of origin:	China