CHERRY SMART TERMINAL ST-1144

USB Smart Card Reader





Models may vary from the image shown

Smart, stable and can be operated with one hand. The SmartTerminal ST 1144 reads and writes your chipcards - and with extremely low power consumption to boot. Whether access controls, network logon or smart card-based Internet transactions - the SmartTerminal with USB connection supports you in protecting your sensitive data in an easy and reliable way.

FUNCTION AND PERFORMANCE

- → High-quality USB-smartcard reader
- → OmniKey 3121 (Aviator) compatible
- \rightarrow USB 2.0-compatible
- → Weighted base for "single-handed operation"
- → PC/SC smartcard reader
- → Protocols: T=0, T=1, S=8, S=9, S=10
- → CCID compatible
- → EMVco Level 1 compliant
- → CAC and FIPS 201 compliant
- → TAA compliant

TECHNICAL DATA

| Weight main product: | 11 oz |
|-----------------------------------|---|
| Dimensions product | |
| without packaging: | 2,01 in x 2,17 in x 2,95 in |
| Cable length: | 5.74 ft |
| Storage temperature: | -4 °F - 122 °F |
| Working temperature: | 32 °F - 140 °F |
| Produktzulassungen: | cURusGSVCCICEFCCUKCA |
| System Requirements- Hardware: | USB-A |
| Scope of delivery: | ManualSmartcard Terminal |
| Reliability: | MTBF > 45.000 Stunden |
| Software support: | Card Reader ToolsPC/SC Diagnose Tool |
| Protected PIN entry: | no |
| Protocols: | S=8 S=9 S=10 T=0 T=1 |
| Kontaktierung: | Sliding Contacts |
| SW interface: | CCIDCT-APIPC/SC |
| Installation location: | top-mounted |
| Mating cycles: | 100,000 |
| Chip card types: | ISO 7816 Cards |
| SmartCard-Speed: | 420 kBit/s |
| System speed: | 12 MBit/s |
| Clock frequency: | 4.8 MHz |
| Card power: | 60 mA |
| Status display of chip | |
| card reader: | two-in-one LED |
| Chip-card reader type: | contact |

Errors, technical changes and delivery options reserved. Technical information refers only to the specification of the products. Properties are not guaranteed.



Designation

CHERRY Smart Terminal ST-1144

Please contact your local CHERRY service and support teams or your CHERRY sales partners for versions available in your country.