

Delock HDMI Splitter 1 x HDMI in to 4 x HDMI out 4K 60 Hz with downscaler

Description

This splitter by Delock receives an HDMI signal from a PC or laptop and splits it to four connected displays. Thereby **one HDMI connection** can be used to operate **four HDMI monitors**.

Downscaler

If a monitor does not support the high resolution, the image can be scaled from 4K to 1080p with the integrated downscaler.

USB powered

The device is powered via a USB port, a suitable USB cable is included. If no free USB-A port is available, an optional external power supply is required.



- Connectors: Input: 1 x HDMI-A female 1 x USB Type Micro-B female (5 V power supply) Output: 4 x HDMI-A female
 Supports EDID management
 High Speed HDMI specification
 Supports 3D displays
 Supports HDR
 Supports HDCP 1.4 and 2.2
 Function: Mirrored
 Transmission of audio and video signals
 Supports all common 2.0 and 5.1 audio formats: LPCM, Dolby Digital, DTS Audio
 Resolution up to 3840 x 2160 @ 60 Hz (depending on the system and the connected hardware)
- · Video bandwidth up to 600 MHz / 6 Gbps per channel, max. 18 Gbps
- Power consumption: max. 2.5 W
- Robust metal housing



Item no. 18652

EAN: 4043619186525 Country of origin: China Package: Retail Box

DATASHEET



- Colour: black
- Dimensions (LxWxH): ca. 136 x 61 x 14 mm

System requirements

- HDMI cable
- · Power source with a free USB Type-A female port

Package content

- HDMI Splitter
- USB power cable, length: ca. 0.75 m
- User manual

Images





General

HDMI 2.0
HDCP 1.4
HDCP 2.2

Interface

Output:	4 x HDMI-A female
Input:	1 x USB Type Micro-B female (5 V power supply) 1 x HDMI female

Technical characteristics

Maximum screen resolution:	3840 x 2160 @ 60 Hz
Video bandwidth:	600 MHz / 6 Gbps

Physical characteristics

Housing colour:	black
Housing material:	metal
Length:	136 mm
Width:	61 mm
Height:	14 mm

Herstellerinformation

Strasse	Beeskowdamm 13/15
PLZ	14167
Ort	Berlin
Land	Deutschland
E-Mail	info@delock.de
Webseite	www.delock.de