OVERVIEW



1.	USB-C (USB 10Gbps), with USB PD 65-100W & DP 1.4	5. HDMI
2.	Headphone / microphone combo jack (3.5mm)	6. Ethernet (RJ-45)
3.	USB-A (USB 5Gbps)	7. USB-A (USB 5Gbps)
4.	USB-A (USB 5Gbps)	8. Power connector

LOQ 15IRX10

PERFORMANCE

Processor

Processor Family

13th Generation Intel[®] Core[™] i5 / i7 or 14th Generation Intel[®] Core[™] i7 Processor

Processor**

Processor Name	Cores hre		Base Frequency	Max Frequency	Cache	Processor Graphics
Core i5- 13450HX			P-core 2.4GHz / E-core 1.8GHz	P-core 4.6GHz / E-core 3.4GHz	20MB	Intel® UHD Graphics
Core i7- 13650HX	14 (6 P-core + 8 E- core)	20	P-core 2.6GHz / E-core 1.9GHz	P-core 4.9GHz / E-core 3.6GHz	24MB	Intel® UHD Graphics
Core i7- 13700HX	16 (8 P-core + 8 E- core)	24	P-core 2.1GHz / E-core 1.5GHz	P-core 5.0GHz / E-core 3.7GHz	30MB	Intel® UHD Graphics
Core i7- 14700HX	20 (8 P-core + 12 E-core)	28	P-core 2.1GHz / E-core 1.5GHz	P-core 5.5GHz / E-core 3.9GHz	33MB	Intel® UHD Graphics

AI (Artificial Intelligence)

AI PC Category

AI-Powered Gaming PC^[1]

Notes:

[1] AI-Powered Gaming PCs feature Lenovo® AI Engine+ and NVIDIA® GeForce RTX™ GPUs to handle AI-driven tasks and deliver exceptional gaming performance.

Operating System

Operating System**

- Windows® 11 Pro
- Windows® 11 Home
- Windows® 11 Home Single Language
- No preload operating system

Graphics

Graphics**

Graphics	Туре	Memory	Boost Clock	TGP	AI TOPS (Peak)	Key Features
NVIDIA® GeForce RTX™ 5050 Laptop GPU	Discrete	8GB GDDR7	2370 MHz	100W	440 TOPS	DLSS 4, Reflex 2, DirectX® 12 Ultimate
NVIDIA® GeForce RTX™ 5060 Laptop GPU	Discrete	8GB GDDR7	2497 MHz	100W	572 TOPS	DLSS 4, Reilex 2, DirectX® 12 Ultimate
NVIDIA® GeForce RTX™ 5070 Laptop GPU	Discrete	8GB GDDR7	2347 MHz	115W	798 TOPS	DLSS 4, Reflex 2, DirectX® 12 Ultimate

Monitor Support

Monitor Support

Supports up to 3 independent displays (native display and 2 external monitors via HDMI®, USB-C®)

- + HDMI $^{\! \rm s}$ supports up to 8K@60Hz
- USB-C[®] supports up to 5K@60Hz

Chipset

Chipset Intel® HM770 chipset

Memory

Max Memory^[1]

Lenovo

- Up to 32GB DDR5-4800 offering
- Up to 32GB DDR5-5600 offering

Memory Slots

Two DDR5 SO-DIMM slots, dual-channel capable

Memory Type**

- DDR5-4800
- DDR5-5600

Notes:

[1] The max memory is based on the test results with current Lenovo® memory offerings.

Storage

Max Storage Support^[1]

Up to two drives, 2x M.2 SSD • M.2 2242 SSD up to 1TB each

Storage Slot

Two M.2 2280 PCIe[®] 4.0 x4 slots

Storage Type

Disk Type	Interface	Offering
M.2 2242 SSD	PCIe® NVMe®, PCIe® 4.0 x4	512GB / 1TB

Notes:

[1] The storage capacity supported is based on the test results with current Lenovo® storage offerings.

Removable Storage

Optical

None

Card Reader

No card reader

Multi-Media

Audio Chip

High Definition (HD) Audio, Realtek® ALC3287 codec

Speakers

Stereo speakers, 2W x2, optimized with Nahimic Audio

Microphone

Dual-microphone array

Camera

5.0MP, with E-shutter, fixed focus

Battery

Battery

60Wh Rechargeable Li-ion Battery, supports Rapid Charge Pro (charge up to 50% in 30min)

Max Battery Life^[1]

Models with 60Wh battery: MobileMark® 30@250nits: 3.36 hr Local video (1080p) playback@150nits: 7.17 hr

Notes:

^[1] All battery life claims are approximate maximum and based on results using the MobileMark[®] 2014, MobileMark[®] 2018, MobileMark[®] 25, MobileMark[®] 30, JEITA 2.0, JEITA 3.0, continuous 1080p video playback (with 150nits brightness and default volume level) or Google Power Load Test (PLT) battery-life benchmark tests. Actual battery life will vary depending on many factors such as product configuration and usage, software use, wireless functionality, power management settings, and screen brightness. The maximum capacity of the battery will decrease with time and use.

Power Adapter

Power Adapter**[1]

- 170W slim tip (3-pin) AC adapter, 100-240V, 50-60Hz
- 245W slim tip (3-pin) AC adapter, 100-240V, 50-60Hz

Notes:

[1] AC adapter offerings depend on the country.

Special Features

Special Features

Al Chip: LA1

DESIGN

Display

Display**

Size	Resolution	Touch	Туре	Brightness	Surface	Aspect Ratio	Contrast Ratio	Color Gamut	Refresh Rate	Viewing Angle (L/R/U/D)	Key Features
15.6″	FHD (1920x1080)	None	IPS ^[1]	300nits	Anti- glare	16:9	1000:1	100% sRGB	144Hz	85° / 85° / 85° / 85°	Advanced Optimus, NVIDIA® G- SYNC®
15.6″	WQHD (2560x1440)	None	IPS ^[2]	350nits	Anti- glare	16:9	1000:1	100% sRGB	165Hz	85° / 85° / 85° / 85°	3ms response time, Advanced Optimus, NVIDIA® G- SYNC®

Touchscreen

Non-touch

Notes:

[1], [2] IPS (in-plane switching) technology may refer to IPS, PLS, ADS, AHVA, AAS.

Input Device

Pen

No support

Keyboard

6-row, multimedia Fn keys, numeric keypad, Copilot key

Keyboard Backlight**

- 24-Zone RGB backlight
- White backlight

Touchpad

Buttonless Mylar® surface multi-touch touchpad, supports Precision TouchPad (PTP), 75 x 120 mm (2.95 x 4.72 inches)

Mechanical

Dimensions (WxDxH)^[1]

359.86 x 258.7 x 21.9-23.9 mm (14.17 x 10.19 x 0.86-0.94 inches) Weight^[2] Starting at 2.4 kg (5.29 lbs) Case Color Luna grey Surface Treatment

Painting

Case Material

PC-ABS (top), PC-ABS (bottom)

Notes:

[1] The system dimensions may vary depending on configurations.

[2] The system weight is approximate and based on results in Lenovo[®] lab, which varies depending on the source of component, variance of the distribution of each component, and manufacturing process. It may not be the exact weight for each specific model.

CONNECTIVITY

Network

WLAN + Bluetooth®[1]

Wi-Fi[®] 6, 802.11ax 2x2 Wi-Fi[®] + Bluetooth[®] 5.2, M.2 card^[2]

WWAN

No support

Ethernet^[3]

Gigabit Ethernet, 1x RJ-45, supports Wake-on-LAN

Notes:

[1] Bluetooth[®] may operate at a lower version than hardware design depending on the factors such as operating system, driver, etc.

[2] Wi-Fi $^{\circ}$ 6 operation is subject to the regulation rules in each country.

[3] Wake-on-LAN needs the power adapter plugged in.

Ports^[1]

Standard Ports

- 3x USB-A (USB 5Gbps / USB 3.2 Gen 1)
- 1x USB-C[®] (USB 10Gbps / USB 3.2 Gen 2), with USB PD 65-100W and DisplayPort[™] 1.4^[2]
- 1x HDMI[®] 2.1, up to 8K/60Hz
- 1x Headphone / microphone combo jack (3.5mm)
- 1x Ethernet (RJ-45)
- 1x Power connector

Notes:

[1] The transfer speed of the ports will vary and, depending on many factors, such as the processing speed of the host device, file attributes and other factors related to system configuration and your operating environment, will be slower than theoretical speed.

[2] Supports Lenovo® protocol for 140W charging but requires a unique Lenovo® adapter for operation.

Docking

Docking

Various docking solutions supported via USB-C[®]. For more compatible docking solutions, please visit <u>Docking for LOQ™ 15IRX10</u>

SECURITY & PRIVACY

Security

Security Chip Firmware TPM 2.0 integrated in chipset

Fingerprint Reader

No fingerprint reader

BIOS Security

LOQ 15IRX10

Lenovo

- Administrator password
- Master hard disk password
- Power-on password
- User hard disk password
- User password
- Self-healing BIOS
- More BIOS security features, please visit <u>BIOS Simulator</u>^[1]

Other Security

E-shutter

Notes:

[1] The BIOS simulator is just for reference. Default settings and some options may vary depending on the hardware, operating system and BIOS version.

SERVICE

Warranty

Base Warranty**

- 1-year courier or carry-in service
- 1-year courier or carry-in with 2-year system board service (Korea only)
- 2-year courier or carry-in service
- 3-year courier or carry-in service
- No base warranty

ACCESSORIES

Bundled Accessories

Bundled Accessories^[1]

- Lenovo[®] LOQ[™] M100 RGB Mouse (USB connector)
- None

Notes:

[1] For compatible accessory solutions, please visit <u>Accessories for LOQ™ 15IRX10</u>.

OPERATING REQUIREMENTS

Operating Environment

Temperature^[1]

- At altitudes up to 2438 m (8,000 ft)
- Operating: 5°C to 35°C (41°F to 95°F)
- Storage: 5°C to 43°C (41°F to 109°F)
- At altitudes above 2438 m (8,000 ft)

- Maximum temperature when operating under the unpressurized condition: 31.3°C (88°F)

Relative Humidity

- Operating: 8% to 95% at wet-bulb temperature 23°C (73°F)
- Storage: 5% to 95% at wet-bulb temperature 27°C (81°F)

Altitude

Maximum altitude (without pressurization): 3048 m (10,000 ft)

Notes:

[1] When you charge the battery, its temperature must be no lower than 10°C (50°F).

CERTIFICATIONS

Green Certifications⁽¹⁾

Green Certifications

- ErP Lot 6/26
- RoHS compliant

Notes:

[1] The items listed under the "Green Certifications" section may not only refer to certification but also registration or self-declaration. For ESG & regulatory compliance documents, please visit <u>https://compliance.lenovo.com</u>.

Other Certifications

Other Certifications

TÜV Rheinland® Low Blue Light (Software Solution)

- Feature with ** means that only one option listed under the feature can be configured on selected models. Please refer to the model configuration for specific information.
- Lenovo reserves the right to change specifications or other product information without notice. Lenovo is not responsible for photographic or typographical errors. LENOVO PROVIDES THIS PUBLICATION "AS IS," WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some jurisdictions do not allow disclaimer of express or implied warranties in certain transactions, therefore this disclaimer may not apply to you.
- The specifications on this page may not be available in all regions, and may be changed or updated without notice.

Lenovo PSREF Product Specifications Reference

