Inter-Tech Elektronik Handels GmbH

## ITX A80 Black



### **ITX A80**

The Mini-ITX case A80 by Inter-Tech - modern, stylish and strikingly practical. Completely made of aluminum, it also offers a perfect, thermal relief through various ventilation openings. Its simple design language also makes it look timelessly elegant.

Systems based on Mini-ITX can be designed very energy-saving, so that the standard, external 60W power supply is usually sufficient to run a powerful ITX computer. However, the internal Mini-ITX PSU board is able to handle input voltages of up to 120W.

- √ Robust full aluminum case
- ✓ 2x USB 3.0
- ✓ including 60W power supply
- √ high quality feet, chrome plated



# ITX A80 Black

### **Specifications**

Motherboard

Drive bays

3.5" internal: 1/0\*
2.5" internal: 0/2\*

Front connectors

USB 3.0: 2

Microphone: -

Speaker: Case openings WLAN antenna: 2
COM ports: 3

Cooling system HDD tray: 2x 40x40x10mm

or 50x50x10mm or 60x60x10mm

Power input For 12V plugs with dimensions of 5.5x2.5x10.7mm

Maximum CPU cooler height 40mm<sup>1</sup>/30mm<sup>2</sup>

Maximum graphics card length -

Packing units Shipping unit: 1 Piece Packing unit: 6 Pieces

Warranty 24 Months
Article number 88881302
EAN-Code 4260455643399

Scope of delivery External 60W Power Supply, 12V/5A

Mini-ITX PSU max. 120W, 90°

Power cord

Cable ties Screw set

Features External 60W power supply

Mini-ITX PSU supports 12V power supplies up to 120W

Preparation for VESA mount 75x75mm

Stands

\* the values may differ for certain combinations

1 without drives, 2 with drives

## **Dimensions and Weight**

	Cage	Case	Package
Height	80mm	88mm	265mm
Width	200mm	200mm	150mm
Depth	200mm	200mm	240mm
Weight (net): 1.07kg			

Weight (net): 1.07kg Weight (gross): 1.79kg

D	C	/D	C	b	0	a	rd	:
---	---	----	---	---	---	---	----	---

Connectors	Quantity	Max. Length
Mainboard 20Pin	1x	-
P4 12V 4Pin	1x	60cm
IDE 4Pin	1x	20cm
S-ATA	1x	35cm

DC Output	Output Voltage (V)	Max. Output Current (A)
+3.30 V	+3.30	5.0
+5.00 V	+5.00	5.0
+5.00 VSB	+5.00	2.0
+12.00 V	+12.00	5.0
-12.00 V	-12.00	0.1

Certification:

