



IPC 2U-2129N

The **IPC 2U-2129N** is the perfect rack for a low-priced server system. The excellent quality of the materials combined with superb workmanship establishes the basis for a very variable case.

The **IPC 2U-2129N** provides the possibility to mount a 1U or 2U server power supply at the rear of the chassis as well as a normal ATX power supply with 80mm fan in the front.

Furthermore the **IPC 2U-2129N** is equipped with four 80mm fans and perforated slot brackets for excellent cooling.

Both serial USB front connectors, one of them **USB 3.0**, round off the whole package.

Specifications

| | |
|------------------------------|--|
| Motherboard | Mini ITX, mATX, µATX, ATX, eATX, SSI EEB maximum motherboard size WxD: 305mm x 350mm, 12" x 13.8" |
| Drive Bays | 5.25" external: 2 3.5" external: 6 3.5" internal: 6 |
| Front Connectors | USB 3.0: 1 USB 2.0: 1 |
| Cooling System | Internal: 4x 80mm (assembled board 4x 3Pin to 1x Molex) Rear: 1x 60mm (optional, not possible when using 2U/1U PSU) |
| Controls | Power-Button Reset-Button |
| LED | Power HDD Activity 3x Network Activity 1x Alert |
| Power Supply | 1U/2U Server PSU ATX PSU with 80mm fan |
| Material | 1.0-1.2mm Steel |
| Maximum CPU cooler height | 65mm |
| Maximum graphics card length | 350mm |
| Packing Units | Shipping Unit: 1 Piece Pallet: 18 Pieces |
| Guarantee and Warranty | Case 24 Months Warranty |
| Article Number | 88887194 |
| EAN-Code | 4260133128385 |
| Scope of Delivery | Screw Set Mounting frame for 2U / 1U PSU |
| Features | Serial 4x 80mm fan Possibility to mount a 1U/2U server PSU in the rear or a ATX PSU with 80mm fan in the front Removable and optional positionable HDD-cages 5.25" drives screwless mountable Slot brackets screwed and perforated (Riser Slot rear wall optional (Item no. 88887160)) |

Dimensions and Weight

| | Cage | Case | Package |
|--------|-------|-------|---------|
| Height | 89mm | 89mm | 155mm |
| Width | 433mm | 482mm | 565mm |
| Depth | 650mm | 680mm | 825mm |

Weight (net): 8.93kg
Weight (gross): 11.27kg

Power supply

| Connector | Quantity | Max. Length |
|--------------------|----------|-------------|
| Mainboard 20+4Pin | - | - |
| P4 12V 4Pin | - | - |
| P4/EPS 4+4Pin | - | - |
| P8 12V 8Pin | - | - |
| PCI-Express 6+2Pin | - | - |
| PCI-Express 6Pin | - | - |
| IDE 4Pin | - | - |
| S-ATA | - | - |
| Floppy | - | - |
| RPM sensor cable | - | - |
| Fan control | - | - |
| Fan 120mm | - | - |

Certification:

