

# Delock PCI Express x4 Card to 1 x external USB 10 Gbps Type-C<sup>™</sup> female + 1 x external USB 10 Gbps Type-A female - Low Profile Form Factor

### **Description**

This PCI Express card by Delock expands the PC by two external USB 10 Gbps ports. Different USB devices, such as docking stations, card readers, external enclosures etc., can be connected to the card. The card allows a data transfer rate of 10 Gbps on both ports when used simultaneously.



#### Item no. 90107

EAN: 4043619901074 Country of origin: China

Package: Box

# **Specification**

· Connectors:

external:

1 x USB 10 Gbps USB Type-C™ female

1 x USB 10 Gbps Type-A female

internal:

1 x SATA 15 pin power connector

1 x PCI Express x4, V3.0

- Chipset: Asmedia ASM3142
- Data transfer rate up to 10 Gbps
- Power supply via PCI Express interface or via SATA 15 pin power connector
- Electrical power per port:

USB Type-CTM: max. 12 watt (5 V / 2.4 A)

USB Type-A: max. 4.5 watt (5 V / 0.9 A)

- Supports eXtensible Host Controller Interface (xHCI) specification 1.1
- Supports Multiple INs
- Bootable





# **System requirements**

- Linux Kernel 5.15 or above
- Windows 8.1/8.1-64/10/10-64/11
- PC with one free PCI Express x4 / x8 / x16 / x32 slot

# **Package content**

- PCI Express card USB 10 Gbps
- · Low profile bracket
- User manual

# **Images**









#### General

Form factor:	Low Profile
Supported operating system:	Windows 10 32-Bit Windows 8.1 32-Bit Windows 8.1 64-Bit Windows 8.1 64-Bit Windows 11 Linux Kernel 5.15 or above

### Interface

External:	1 x USB 10 Gbps USB Type-C <sup>™</sup> female 1 x USB 10 Gbps Type-A female
Internal:	1 x PCI Express x4, V3.0 1 x SATA 15 pin power connector

### **Technical characteristics**

Chipset:	Asmedia ASM3142
Data transfer rate:	10 Gbps

# **Physical characteristics**

Slot bracket:	Low Profile
	standard