

IPC 1U-10248



IPC 1U-10248

The **IPC 1U-10248** is the perfect rack for a low-priced server system. The excellent quality of the materials combined with superb workmanship establishes the basis for a very variable case.

The **IPC 1U-10248** provides the possibility to mount eight 2.5" internal hard drives. Two standard 40mm fans guarantee an optimal cooling.

Additional extras like easily reachable USB 3.0 connectors and the universal ATX I/O plate complete this total package.



IPC 1U-10248

<u>Specifications</u>

Motherboard Mini ITX, mATX, μATX, ATX, SSI CEB maximal motherboard size WxD: 305mm x 270mm, 12" x 10.6" 5.25" external: 2* Drive Bays 3.5" internal: 2* 2.5" internal: 8* Front Connectors USB 3.0: 2 Cooling System Internal: 2x 40mm (included, 3pin (4pin connector)) Power-Button Controls Reset-Button **LED** Power **HDD Activity** 3x Network Activity Power Supply 1U Server PSU, FLEX-ATX Material 1.0-1.2mm Steel Maximum CPU cooler height 32mm Maximum graphics card length 270mm Shipping Unit: 1 Piece Packing Units Pallet: 30 Pieces Guarantee and Warranty Case 24 Months Warranty Article Number 88887100 EAN-Code 4260133126213 Scope of Delivery Screw Set Mounting bracket for FLEX-ATX PSU **Features** 2x 40mm fan included USB 3.0 as block connector Universal ATX I/O plate 1x Riser slot can vary by using several me

Dimensions and Weight

| | Cage | Case | Package |
|--------------------------|---------------------------|--------|---------|
| Height | 44.5mm | 44.5mm | 110mm |
| Width | 433mm | 482mm | 545mm |
| Depth | 480mm | 508mm | 660mm |
| Weight (ne Weight (gr | t): 5.60kg oss): 7.44k | g | |

| ower supply | <u>_</u> | |
|--------------------|-----------------------|-------------|
| Connector | Quantity | Max. Length |
| Mainboard 20+4Pin | - | - |
| P4 12V 4Pin | - | - |
| P4/EPS 4+4Pin | - | 4. |
| P8 12V 8Pin | - | - 1 🕶 |
| PCI-Express 6+2Pin | 4 1 ~ ^ | ur |
| PCI-Express in | | |
| IDE 4Pin | | - |
| S-ATA | | - |
| Floppy | - | - |
| RPM sensor cable | - | - |
| Fan control | - | - |
| Fan 120mm | _ | _ |

Certification: