

Serial DB9 RS232 Extender over Cat 5 - Up to 3300 ft (1000 meters)

Product ID: RS232EXTC1



The RS232EXTC1 Serial over Cat 5 Extender allows you to increase the distance of your RS232 Serial connection by up to 1000 meters (3300 feet), giving you the ability to connect serial peripheral devices up to a kilometer away from your system - an incredible 65x greater than normal RS232 serial cable length restrictions would permit.

The Extender is a cost-effective serial extension solution and completely hardware-based, eliminating the need to install additional software, allowing for a completely plug and play installation. The hardware can be setup in minutes, using existing or new Cat 5 or better Ethernet cabling.

Perfect for use in industrial monitoring and control, POS, security, medical, and traffic flow applications, the RS232 Serial over Cat 5 extender maintains the RS232 standard with support for data transfer rates of up to 230 Kbps.

Backed by a StarTech.com 2-year warranty and free lifetime technical support.

Certifications, Reports and Compatibility













Applications

• Industrial applications include controlling CNC machinery, polling bar code scanner data, administering process control equipment, weigh stations, and other manufacturing applications



- Monitor and control medical equipment, security keypads/card scanners, point of sale equipment and remote sensor data, and various other healthcare related serial communications
- Extend connectivity to Point of Sale card swipe devices, bar code scanners, scales, receipt printers or cash register displays
- Remotely poll data from access keypads, card scanners, camera installations or home security systems
- Remote sensor monitoring for traffic flow management (air traffic control, expressway flow)

Features

- Extend RS232 up to 1000m / 3300ft
- Data transfer rates of up to 230Kbps
- · Compatible with all RS232 communications
- Employ existing Cat 5, 5e, 6 or better Ethernet infrastructure to remotely connect serial devices
- Supports full-duplex data communication
- Compact design
- No driver software required for easy Plug-and-Play installation

Hardware		<u> </u>	
	Warranty	2 Years	
	Ports	1	
	Cabling	Cat 5 UTP	
Performance			
	Maximum Data Transfer Rate	230 Kbps	
	Max Distance	1 km (0.6 mi)	
Connector(s)			
	Local Unit Connectors	1 - DB-9 (9 pin, D-Sub)	
		1 - RJ-45	
	Remote Unit Connectors	1 - DB-9 (9 pin, D-Sub)	
		1 - RJ-45	





Software	OS Compatibility	OS independent
Special Notes / Requirements	System and Cable Requirements	Cat5 RJ45 cabling required
Power	Power Source	2 AC Adapters Included
	Input Voltage	100 - 240 AC
	Input Current	55mA
	Output Voltage	9V DC
	Output Current	0.3A
	Center Tip Polarity	Positive
	Plug Type	М
	Power Consumption (In Watts)	2.7
Environmental		
	Operating Temperature	0C to 70C (32F to 158F)
	Storage Temperature	0C to 85C (32F to 185F)
	Humidity	0% to 95%
Physical Characteristics		
	Color	Silver
	Material	Steel
	Product Length	3.6 in [9.2 cm]
	Product Width	1.3 in [3.4 cm]
	Product Height	0.9 in [2.2 cm]
	Weight of Product	9.6 oz [273.0 g]

Packaging



Information

Package Quantity 1

Package Length 5.6 in [14.2 cm]

Package Width 12.5 in [31.8 cm]

Package Height 2.4 in [6.0 cm]

Shipping (Package)

Weight

1.5 lb [0.7 kg]

What's in the Box

Included in Package 1 - RS232 Extender Local Unit

1 - RS232 Extender Remote Unit

1 - 20cm Null Modem cable (DB-9 Male to Male)

2 - Power Adapter

1 - User Manual

^{*}Product appearance and specifications are subject to change without notice.