


OVERVIEW



11

1. Card reader	6. USB-A (USB 10Gbps)
2. USB-C (USB 10Gbps), with DP 1.4	7. Ethernet (RJ-45)
3. USB-C (USB 10Gbps), with PD 140W & DP 1.4	8. HDMI
4. Combo audio jack	9. Power connector
5. USB-A (USB 10Gbps), Always On	

Notes:

- Port 3: PD 140W indicates the input power and requires the use of Lenovo unique adapter, otherwise it may support lower than 140W.

PERFORMANCE

Processor

Processor Family

AMD Ryzen™ 7 8000 Series Processor

Processor

Processor Name	Cores	Threads	Base Frequency	Max Frequency	Cache	Processor Graphics	NPU
AMD Ryzen™ 7 8845HS	8	16	3.8GHz	5.1GHz	8MB L2 / 16MB L3	AMD Radeon™ 780M	AMD Ryzen™ AI

AI (Artificial Intelligence)

AI PC Category

AI-Powered Gaming PC

AI Performance

Up to 38 overall TOPS

NPU

Integrated AMD Ryzen™ AI, up to 16 TOPS

Operating System

Operating System**

- Windows® 11 Pro
- Windows® 11 Home
- Windows® 11 Home Single Language
- No preload operating system

Graphics

Graphics**

Graphics	Type	Memory	Boost Clock	TGP	AI TOPS (Peak)	Key Features
NVIDIA® GeForce RTX™ 4050 Laptop GPU	Discrete	6GB GDDR6	2370 MHz	100W	194 TOPS	Advanced Optimus, DLSS 3.5, Dynamic Boost 2.0, DirectX® 12 Ultimate
NVIDIA® GeForce RTX™ 4060 Laptop GPU	Discrete	8GB GDDR6	2370 MHz	140W	233 TOPS	Advanced Optimus, DLSS 3.5, Dynamic Boost 2.0, VR ready, DirectX® 12 Ultimate
NVIDIA® GeForce RTX™ 4070 Laptop GPU	Discrete	8GB GDDR6	2175 MHz	140W	321 TOPS	Advanced Optimus, DLSS 3.5, Dynamic Boost 2.0, VR ready, DirectX® 12 Ultimate

Monitor Support

Monitor Support

Supports up to 4 independent displays (native display and 3 external monitors via HDMI® and USB-C®)

- HDMI® supports up to 8K@60Hz
- USB-C® supports up to 5K@60Hz

Chipset

Chipset

AMD SoC (System on Chip) platform

Memory

Max Memory^[1]

Up to 64GB DDR5-5600

Memory Slots

Two DDR5 SO-DIMM slots, dual-channel capable

Memory Type

DDR5-5600

Notes:
 [1] Maximum memory is only to test technical readiness of notebook. Available memory to sell would vary.

Storage

Storage Support^[1]

Up to two drives, 2x M.2 SSD
 • M.2 2242 SSD up to 1TB
 • M.2 2280 SSD up to 1TB

Storage Slot

Two M.2 2280 PCIe® 4.0 x4 slots

Storage Type**

Disk Type	Interface	Offering
M.2 2242 SSD	PCIe® NVMe®, PCIe® 4.0 x4	512GB / 1TB
M.2 2280 SSD	PCIe® NVMe®, PCIe® 4.0 x4	512GB / 1TB

Notes:
 [1] The storage capacity supported is based on the test results with current Lenovo® storage offerings.

Removable Storage

Card Reader

SD card reader

Multi-Media

Audio Chip

High Definition (HD) Audio, Realtek® ALC3287 codec

Speakers

Stereo speakers, 2W x2, optimized with Nahimic Audio

Microphone

Dual-microphone array

Camera**

- FHD 1080p, with E-shutter, fixed focus
- HD 720p, with E-shutter, fixed focus

Battery

Battery

Integrated Li-Polymer 80Wh battery, supports Rapid Charge Pro (charge up to 50% in 30min)

Max Battery Life^[1]

Models with 80Wh battery:
 MobileMark® 25: 6.2 hr
 Local video (1080p) playback@150nits: 11.3 hr

Notes:
 [1] All battery life claims are approximate maximum and based on results using the MobileMark® 2014, MobileMark® 2018, MobileMark® 25, MobileMark® 30, JEITA 2.0, JEITA 3.0, continuous 1080p video playback (with 150nits brightness and default volume level) or Google Power Load Test (PLT) battery-life benchmark tests. Actual battery life will vary depending on many factors such as product configuration and usage, software use, wireless functionality, power management settings, and screen brightness. The maximum capacity of the battery will decrease with time and use.

Power Adapter

Power Adapter**^[1]

- 170W slim tip (3-pin) AC adapter, 100-240V, 50-60Hz
- 230W slim tip (3-pin) AC adapter, 100-240V, 50-60Hz

Notes:

[1] AC adapter offerings depend on the country.

Special Features

Special Features

AI Chip: LA1

DESIGN

Display

Display**[1]

Size	Resolution	Touch	Type	Brightness	Surface	Aspect Ratio	Contrast Ratio	Color Gamut	Refresh Rate	Viewing Angle (L/R/U/D)	Key Features
16"	WQXGA (2560x1600)	None	IPS	350nits	Anti-glare	16:10	1200:1	100% sRGB	165Hz	89° / 89° / 89° / 89°	Advanced Optimus support, Dolby Vision®, AMD FreeSync™ Premium, NVIDIA® G-SYNC®, TÜV Low Blue Light
16"	WQXGA (2560x1600)	None	IPS	500nits	Anti-glare	16:10	1200:1	100% sRGB	240Hz	89° / 89° / 89° / 89°	DisplayHDR™ 400, Dolby Vision®, AMD FreeSync™ Premium, NVIDIA® G-SYNC®, TÜV Low Blue Light

Color Calibration

X-Rite® factory color calibration

Touchscreen

Non-touch

Notes:

[1] IPS (in-plane switching) technology may refer to IPS, PLS, ADS, AHVA, AAS.

Input Device

Pen

No support

Keyboard

6-row, multimedia Fn keys, numeric keypad

Keyboard Backlight**

- 4-Zone RGB backlight
- White backlight

Touchpad

Buttonless Mylar® surface multi-touch touchpad, 75 x 120 mm (2.95 x 4.72 inches)

Mechanical

Dimensions (WxDxH)^[1]

359.7 x 260.5 x 19.9-21.9mm (14.16 x 10.26 x 0.78-0.86 inches)

Weight^[2]

Around 2.3 kg (5.07 lbs)

Case Color

Luna grey

Surface Treatment

Aluminium stamping (anodized with sandblasting)

Case Material

Aluminium (top), PC-ABS (bottom)

System Lighting

No system lighting

Notes:

[1] The system dimensions may vary depending on configurations.

[2] The system weight is approximate and based on results in Lenovo® lab, which varies depending on the source of component, variance of the distribution of each component, and manufacturing process. It may not be the exact weight for each specific model.

CONNECTIVITY

Network

Ethernet^[1]

Gigabit Ethernet, 1x RJ-45, supports Wake-on-LAN

WLAN + Bluetooth^{[2][3]}

Wi-Fi® 6E, 802.11ax 2x2 Wi-Fi® + Bluetooth® 5.3, M.2 card

WWAN

No support

Notes:

[1] Wake-on-LAN needs the power adapter plugged in.

[2] Bluetooth® may operate at a lower version than hardware design depending on the factors such as operating system, driver, etc.

[3] Wi-Fi® 6E full features might be limited by country-level restrictions.

6GHz Wi-Fi® 6E operation is dependent on the support of the operating system, routers/APs/Gateways that support Wi-Fi® 6E, and the regional regulatory certifications & spectrum allocation.

Bluetooth® 5.3 operation requires Windows® 11. For more information please visit [General Bluetooth® Support Information on Microsoft®](#).

Ports^[1]

Standard Ports

- 1x USB-A (USB 10Gbps / USB 3.2 Gen 2), Always On
- 1x USB-A (USB 10Gbps / USB 3.2 Gen 2)
- 1x USB-C® (USB 10Gbps / USB 3.2 Gen 2), with Lenovo® PD 140W and DisplayPort™ 1.4^[2]
- 1x USB-C® (USB 10Gbps / USB 3.2 Gen 2), with DisplayPort™ 1.4
- 1x HDMI® 2.1, up to 8K/60Hz
- 1x Headphone / microphone combo jack (3.5mm)
- 1x Ethernet (RJ-45)
- 1x Card reader
- 1x Power connector

Notes:

[1] The transfer speed of the ports will vary and, depending on many factors, such as the processing speed of the host device, file attributes and other factors related to system configuration and your operating environment, will be slower than theoretical speed.

[2] PD 140W is the input power and requires the use of Lenovo® unique adapter, otherwise it may run lower than 140W.

SECURITY & PRIVACY

Security

Security Chip

Firmware TPM 2.0 integrated in SoC

Fingerprint Reader

No fingerprint reader

BIOS Security

- Administrator password
- Master hard disk password
- Power-on password
- User hard disk password
- User password
- Self-healing BIOS

Other Security

E-shutter

SERVICE

Warranty

Base Warranty**

- 1-year courier or carry-in service
- 1-year courier or carry-in with 2-year system board service (Korea only)
- 2-year (1-yr battery) courier or carry-in service
- 3-year (1-yr battery) courier or carry-in service

ACCESSORIES

Bundled Accessories

Bundled Accessories***[1]

- Lenovo® Legion™ Gaming Speed Mouse Pad M
- Lenovo® Legion™ M300s RGB Gaming Mouse (USB connector)
- None

Notes:

[1] For more compatible accessory solutions, please visit [Accessories for Legion Slim 5 16AHP9](#).

OPERATING REQUIREMENTS

Operating Environment

Temperature^[1]

- At altitudes up to 2438 m (8,000 ft)
 - Operating: 5°C to 35°C (41°F to 95°F)
 - Storage: 5°C to 43°C (41°F to 109°F)
- At altitudes above 2438 m (8,000 ft)
 - Maximum temperature when operating under the unpressurized condition: 31.3°C (88°F)

Relative Humidity

- Operating: 8% to 95% at wet-bulb temperature 23°C (73°F)
- Storage: 5% to 95% at wet-bulb temperature 27°C (81°F)

Altitude

Maximum altitude (without pressurization): 3048 m (10,000 ft)

Notes:

[1] When you charge the battery, its temperature must be no lower than 10°C (50°F).

CERTIFICATIONS

Green Certifications^[1]

Green Certifications

- ErP Lot 6/26
- RoHS compliant

Notes:

[1] The items listed under the "Green Certifications" section may not only refer to certification but also registration or self-declaration. For ESG & regulatory compliance documents, please visit <https://compliance.lenovo.com>.

Other Certifications

Other Certifications

TÜV Rheinland® Low Blue Light (Hardware Solution)

- Feature with ** means that only one option listed under the feature can be configured on selected models. Please refer to the model configuration for specific information.
- Feature with *** means that one or more options listed under the feature can be configured on selected models. Please refer to the model configuration for specific information.
- Lenovo reserves the right to change specifications or other product information without notice. Lenovo is not responsible for photographic or typographical errors. LENOVO PROVIDES THIS PUBLICATION "AS IS," WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some jurisdictions do not allow disclaimer of express or implied warranties in certain transactions, therefore this disclaimer may not apply to you.
- The specifications on this page may not be available in all regions, and may be changed or updated without notice.



AMD



AMD



AMD



AMD



AMD



AMD