

Desktop USB Gaming Microphone with Gooseneck and Mute Button

Description

This USB microphone by Delock can be used for voice and vocal transmissions.

Optimal recordings

The microphone has a circle pattern (omnidirectional) and therefore captures the acoustic signal ideally. Due to a high power, low self-noise and precise performance, even the finest sounds are optimally recorded.

Mute button & blue LED light

With the star shaped mute button in the middle of the microphone, the microphone can be muted very quickly. In mute mode the LEDs are switched off. In addition, the microphone has a switch on the side, which can be used to completely deactivate or reactivate the LEDs.

Flexible gooseneck

With the gooseneck, the microphone can be bent in the preferred direction.

Headphone output

The microphone has a 3.5 mm stereo jack output at the rear for connection of e.g. headphones or speakers.

Rugged cable

The 1.5 m long USB cable has a braided sleeving and a gold-plated USB plug and is therefore very rugged and has a high resistance to disturbances.

Plug & Play

Due to USB Plug & Play the microphone is ready to use immediately, no driver installation is needed. The microphone works with all common operating systems such as Windows, Mac OS, Chrome OS and Linux.



Specification

- Connectors:
 - 1 x USB 2.0 Type-A male
 - 1 x 3.5 mm 3 pin stereo jack female
- Directivity: omnidirectional
- Sensitivity: -30 dB +/- 3 dB
- Frequency range: 50 Hz - 16 kHz
- Sample rate: 16 Bit / 44.1 kHz
- Signal-to-noise ratio (SNR): ca. 60 dB
- Impedance: 2.2 kOhm
- Mute-Button
- LED on / off button
- Cable length: ca. 1.5 m
- Colour: black / blue
- Dimensions (LxWxH): ca. 108 x 97 x 325 mm
- USB bus powered
- Plug & Play

System requirements

- Chrome OS
- Linux Kernel 4.4 or above
- Mac OS 10.9 or above

Item no. 66330

EAN: 4043619663309

Country of origin: China

Package: Retail Box

- Windows 7/7-64/8.1/8.1-64/10/10-64
- PC or laptop with a free USB Type-A port

Package content

- USB microphone
- User manual

Images



General	
Function:	Plug & Play
Supported operating system:	Chrome OS Linux Kernel 4.4 or above Mac OS 10.9 or above Windows 10 32-bit Windows 10 64-bit Windows 7 32-bit Windows 7 64-bit Windows 8 32-bit Windows 8 64-bit Windows 8.1 32-bit Windows 8.1 64-bit
LED indicator:	2 x
Interface	
connector:	1 x USB 2.0 Type-A male
Technical characteristics	
Frequency range:	50 Hz - 16 kHz
Voltage:	USB bus powered
Sensibility:	-30 dB +/- 3 dB
Sample rate:	16 Bit / 44.1 kHz
Signal noise ratio (SNR):	ca. ≥ 60dB
Directivity:	omnidirectional
Physical characteristics	
Cable length:	1.5 m
Length:	108 mm
Width:	97 mm
Height:	325 mm
Colour:	black / blue
LED colour:	blue