

# **OVERVIEW**



1. Power connector	4. DP 1.4
2. HDMI 2.1 TMDS	5. Audio line-out (3.5mm)
3. HDMI 2.1 TMDS	



## **PERFORMANCE**

#### **Panel**

#### **Panel**

3-side NearEdgeless, VA

#### **Backlight**

WLED

#### **Display Size**

24.5 inches

#### **Max View Area**

WxH: 543.7 x 302.6 mm

### Resolution

1920 x 1080

#### **Aspect Ratio**

16:9

#### **Pixel Pitch**

0.283 x 0.280 mm

#### **Dot / Pixel Per Inch**

90 dpi

## **Brightness**

Peak: 380 cd/m²
Typical: 350 cd/m²

#### **Contrast Ratio**

• Contrast Ratio: 3000:1

• Dynamic Contrast Ratio: 3M:1

#### View Angle (H / V)

Horizontal: 178°, Vertical: 178°

### **Response Time**

- Moving Picture Response Time (MPRT): 0.5 ms
- Level 1: 7 ms
- Level 2: 6 ms
- Level 3: 4 ms
- Level 4: 2 ms
- Level 5: 1 ms

### **Refresh Rate**

240Hz (Overclock to 280Hz)

Overclocking at 280Hz is based on laboratory test data, and this function may cause irregularities in the display

#### **Color Gamut**

• Color Area Ratio: 117% sRGB

Coverage Ratio: 90% DCI-P3 (CIE 1976)

• Coverage Ratio: 99% sRGB (CIE 1931)

### **Color Support**

16.7 Million

#### **Color Depth**

8-bit

## **Screen Surface Treatment**

Anti-alare

## **Operating System**

## **Operating System**

- Windows® 11 Support
- Windows® 10 Support

## Multi-Media



## **Speakers**

Integrated Speakers, 2x 3W

## **Power Supply**

## **Power Consumption**

Typical / Max: 19W / 28W

• Sleep / Off mode: <0.3W

• Switch-off Mode: <0.5W

• Energy Star Power On: 18.8W

• Energy Star TEC: 58.5kWh

## Voltage Required

AC 100 to 240 V (50-60Hz)

## **Special Features**

## **Special Features**

- HDR10 Compliance
- Gaming Console Support: Xbox
- · Natural Low Blue Light
- AMD FreeSync™ Premium

AMD FreeSync™ technology only can work with AMD Radeon™ series graphics card.

Lenovo® Artery (Lenovo® Display Accessories and Display Manager) Support
Lenovo® Artery supports Windows® 10 & 11, Mac OS, and Windows® On Arm (functions vary across systems).
Lenovo® Display Accessories and Display Manager is formerly Lenovo® Display Control Center.

## **DESIGN**

#### Mechanical

#### ThinkCentre® M Series Support

None

## **Bezel Width**

• Side: 2.0mm

• Top / Bottom: 2mm / 18.5mm

## Cable Management

Support

#### Case Color

Raven black

## Dimensions (WxDxH)[1]

Models	Dimensions	
Lowest Position	557.3 x 258.8 x 364.2mm (21.94 x 10.19 x 14.34 inches)	
Highest Position	557.3 x 258.8 x 499.2mm (21.94 x 10.19 x 19.65 inches)	
Head Only	557.3 x 50.5 x 329.1 mm (21.94 x 1.99 x 12.96 inches)	

#### Packaging Dimensions (WxDxH)

647 x 188 x 420 mm (25.47 x 7.4 x 16.54 inches)

## Weight<sup>[2]</sup>

Models	Weight
Monitor With Stand	5.5 kg (12.1 lbs)
Monitor Head Only	3.6 kg (7.9 lbs)

## **Packaging Weight**

8.1 kg (17.9 lbs)

### Mounting

Supports VESA mount 100mm

## Stand

## Lenovo Legion R25f-30



Supports -5° to +22° tilt, left & right 30 swivel, -90° to +90° pivot, up to 135mm lift

#### In the Box

- · Monitor with Stand
- 1x DP Cable (1.8m)
- 1x Power cable (1.8m)
- · Warranty Booklet

#### Notes:

[1] The system dimensions may vary depending on configurations.

[2] The system weight is approximate and based on results in Lenovo® lab, which varies depending on the source of component, variance of the distribution of each component, and manufacturing process. It may not be the exact weight for each specific model.

## CONNECTIVITY

### Ports<sup>[1]</sup>

#### **Rear Ports**

- 2x HDMI® 2.1 TMDS[2]
- 1x DisplayPort<sup>™</sup> 1.4
- 1x audio-out (3.5mm)

#### Notes:

[1] The transfer speed of following ports will vary and, depending on many factors, such as the processing speed of the host device, file attributes and other factors related to system configuration and your operating environment, will be slower than theoretical speed.

USB 2.0: 480 Mbit/s;

USB 3.2 Gen 1 (SuperSpeed USB 5Gbps, formerly USB 3.0 / USB 3.1 Gen 1): 5 Gbit/s;

USB 3.2 Gen 2 (SuperSpeed USB 10Gbps, formerly USB 3.1 Gen 2): 10 Gbit/s;

USB4® 20Gbps / USB 3.2 Gen 2x2 (SuperSpeed USB 20Gbps): 20 Gbit/s;

USB4® 40Gbps (USB 40Gbps): 40 Gbit/s;

Thunderbolt™ 3/4: 40 Gbit/s.

[2] Supports 1920x1080@240Hz as specified in HDMI® 2.1

## **SECURITY & PRIVACY**

## Security

### **Physical Locks**

Kensington® Security Slot™ (2.5 mm x 6 mm and 3 mm x 7 mm)

## **SERVICE**

## **Warranty**

## **Base Warranty**

3-year limited warranty

## **CERTIFICATIONS**

## 

## **Green Certifications**

- EU Energy Label (E-class)
- RoHS compliant
- · Volatile Organic Compound Certification

### Notes:

[1] The items listed under the "Green Certifications" section may not only refer to certification but also registration or self-declaration.



## **Other Certifications**

## **Other Certifications**

- Eyesafe® Certified 2.0
- TÜV Rheinland® Eye Comfort Certification
- TÜV Rheinland® Low Blue Light (Hardware Solution)
- Lenovo reserves the right to change specifications or other product information without notice. Lenovo is not
  responsible for photographic or typographical errors. LENOVO PROVIDES THIS PUBLICATION "AS IS,"
  WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES
  OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some jurisdictions do not allow
  disclaimer of express or implied warranties in certain transactions, therefore this disclaimer may not apply to
  you.
- The specifications on this page may not be available in all regions, and may be changed or updated without notice.













