

A-3411 Creek









A-3411 Creek - RGB gaming case with tempered glass

For all ambitious gamers, the A-3411 Creek offers the ideal basis for a high-end gaming system. Thanks to the integrated RGB LED strip in the front, which can be controlled either via an integrated button in the front or via the 5V RGB board, it skilfully stages itself. The standard tempered glass side panel offers insights into the installed hardware and also upgrades the entire system. Up to four additional RGB devices with 5V 3pin RGB headers and four 3pin fans can be connected to the integrated RGB/fan board and thus offer a variety of configuration and design options.

There is space for optional fans not only behind the front, in the top and on the back, but also above the power supply tunnel, where two 120mm fans can be installed, which can contribute to waste heat and cooling. In the separate power supply tunnel there is not only the power supply mounting space, but also a removable hard drive cage that offers space for a 2.5" SSD and a 3.5" HDD. Dust filters in the top and bottom of the case, which are easy to remove and clean, keep the interior free of dust.

- ✓ Integrated RGB LED strip in the front panel
- √ Tempered glass side window
- ✓ RGB/fan board for four RGB devices and four 3pin fans
- √ 3pin RGB header connection for 5V RGB mainboard control



A-3411 Creek

Specifications

Motherboard ATX, µATX, ITX Max. drive bays 5.25" external: 0 3.5" external: 0

3.5" internal: 1 2.5" internal: 3

USB 3.0: 1 Front connectors USB 2.0: 2

> Microphone: 1 Speaker:

Cooling system Front: 2x 140mm or 3x 120mm

(optional)

Rear: 1x 120mm (optional)

Top: 2x 120mm

(optional)

Power supply tunnel: 2x 120mm (optional)

Max CPU-Cooler height 160mm Max Graphic card length 305mm Packing units Shipping unit: 1 pcs

Packing unit: 24 pcs Warranty 24 months 88881322 Article number 4260455645034 EAN-Code Scope of Delivery Screw set

Cable ties Speaker

Features Front panel with integrated RGB LED strip

Tempered glass side window

RGB/fan board for up to four RGB devices and four 3pin fans 3pin RGB header connection for 5V RGB mainboard control Separate 2.5" and 3.5" installation space in the power supply tunnel

Two 120mm fan bays above the power supply tunnel Space for water cooling in the sizes 120mm, 240mm, 280mm* and 360mm

Easy to remove dust filters in the bottom and in the top

Power supply mounting decoupled in a separate cage in the base part Reusable slot plates

Openings for easy cable laying

stands *only 2x 2.5" SSD possible

Dimensions and Weight

Height 440mm 455mm 460mm Width 200mm 205mm 255mm Depth 340mm 385mm 495mm		Cage	Case	Package
Width 200mm 205mm 255mm	lla:abt		455	460
	Height	440mm	455MM	460MM
Depth 340mm 385mm 495mm	Width	200mm	205mm	255mm
	Depth	340mm	385mm	495mm

ower Supply	L	
Connector	Quantity	Max. Length
Mainboard 20+4Pin	-	-
P4 12V 4Pin	-	-
P4/EPS 4+4Pin	-	4
P8 12V 8Pin	_ · _	a 1 2
PCI-Express 6+2Pin		
PCI-Express n IDE 4Pin	tho	-
S-ATA	-	-
Floppy	-	-
RPM sensor cable	-	-
Fan Control	-	-
Fan: 120mm	-	-

 ϵ Certification: