

# 2000 VA pure sine wave UPS, LCD display, 2 x Schuko + 3 x C13 outputs, USB, black

EG-UPS-PS2000-02

## ULTIMATE DEFENCE

- Pure sine wave output
- Provide backup power Prevents data loss
- Protects your sensitive and valuable equipment
- Perfect support for solar panel installations and other sensitive equipment that requires pure sinewave input
- Compact and reliable ideal for home and small office use



## Features

- Uninterruptable power supply with pure sine wave output
- USB interface
- Automatic AC voltage regulation (AVR)
- Intelligent overload and short-circuit protection
- Audible and visual alarms
- LCD display and LED status indication
- Internal battery with overcharge and over-discharge protection

## Packaging

Q'ty in crtn, pcs	1
Crtn volume, CUM	0.042075
Crtn weight, kgs	19.73
Individual package size LxWxH:	492x316x236 mm
Carton size LxWxH:	510x330x250 mm
Country of origin	CN
Barcode	8716309124812
Customs code	8504408490

## Package contents

- UPS
- Power input cord

## Specifications

Type: line interactive with pure sine wave  
 Waveform: pure sine, 5% distortion at linear load, PF > 0.8

Input: AC 220V±25%, 50Hz/60Hz ±10%  
 Output: AC 220V±10%, 50Hz/60Hz ±1% (AC 220V±10% at inverter mode)  
 Switching time: up to 10 ms typically  
 Backup time: 10...30 mins (depends on the load)  
 Battery: 151 x 65 x 94 mm, sealed lead-acid 12V/9Ah, F2 terminals x 3 pcs  
 Charge time: up to 90% after 6-8 hours  
 Sockets: C14 input, outputs: 3x IEC C13, 2x Schuko

## System requirements

In order to work correctly, the connected load should be at least 5% of the maximum capacity of the UPS. For example, a 700 W UPS needs at least a connected load of 35 W to work.

## Certificates

