

# HP Thunderbolt G4 Dock



1. Backward compatible with USB-C® Alt mode, ports will work at USB-C® Alt mode speeds which are dependent on host specifications.
2. For USB-C® Alt mode, host PC must support Thunderbolt™ 3 or Thunderbolt™ 4 running a DP 1.4 DSC host.
3. Based on HP's internal analysis of docking stations that are Thunderbolt™ 4, have auto validating & self healing firmware, Meet NIST 800-173 requirements, have Port control, the ability to disable the RJ-45 and a BIOS MAPT authorized list.
4. HP Sure Start on HP Thunderbolt G4 dock supports firmware integrity verification and recovery it does not include real-time and runtime protections or Microsoft SCCM integration typically found on HP Sure Start in HP notebooks.
5. For USB-C® alt mode functionality, host PC must support the DisplayPort™ Alt mode protocol through its USB-C® port. Charging and port replication is supported on notebooks that have implemented USB-C® Alt Mode industry specifications. Power button to turn on or wake the system, Wake-on LAN from warm and cold dock, Wake-on LAN from S4/S5, and MAC Address Pass-Through S0, S3, S4, S5 warm and cold dock features only function on HP or HP supported notebooks. HP does not provide ethernet and audio drivers on Mac PCs
6. Requires infrastructure to support 2.5Gb ethernet speeds.
7. Windows Management Instrumentation installation required. Requires Windows 10 or higher.

## The Dock That Does It All

Boost your security, productivity, and connectivity with this Thunderbolt™ 4 dock. It protects your network and devices from the moment you log in, supports multi-OS compatibility<sup>1</sup>, and can support up to four 4K displays<sup>2</sup>. Ideal for ITDMs and hybrid workers, this dock also makes home or office device management easy.

### The World's Most Secure Dock<sup>3</sup>

Feel safe and secure from the moment you log in. The HP Thunderbolt G4 Dock with HP Sure Start<sup>4</sup> prevents hackers from using the dock to attack the network and the attached notebook. Everything connected to this dock is protected and meets full NIST 800-193 requirements.

### Expanded Compatibility. Easy Connectivity

Focus on your work and not your compatibility<sup>1</sup> with a dock that works seamlessly with most notebooks and operating systems. Whether you use Windows, Mac, or Chrome OS—rigorous testing and certifications ensure that one USB-C® cable<sup>5</sup> connects your device and peripherals without issue.

### The Power To Be Productive

Multitask, create, and collaborate faster with a dock that supports up to four 4K displays through superfast Thunderbolt™ 4 technology<sup>2</sup> and has double the ethernet speed for faster downloads<sup>6</sup>. This dock also delivers up to 100W/230W of power—enough to charge most notebooks.

### Device Management Made Easy

Manage your mixed fleet more efficiently with wired Intel® vPro® support that allows authorized administrators to remotely access and manage vPro® enabled notebooks using wired connections to make updates. IT Managers can also plan dock firmware updates anytime, even after the user disconnects through HP's One Click Installer<sup>7</sup>.

## Features

### Modern Device Manageability

With Intel® vPro® Active Management Technology, authorized administrators can remotely access notebooks using wired connections, even if turned off, to make updates.

### Electronic Asset Management for Your Docks

Empower your IT to manage and track your docks by product name, serial number, and MAC Address from anywhere with the time-saving, easy-to-use Electronic Tag (eTag) asset management tool.<sup>1</sup>

### Thoughtful Product Packaging

HP is committed to reducing plastic in landfills by using recyclable, fiber-based, and sustainably sourced packaging<sup>2</sup> that meets recycling requirements, so it can stay out of the landfill<sup>3</sup> when customers are finished with it.

### One Cable. Two Power Options

With two power options (120W/280W) from one cable, you can power mainstream and high performance PCs alike with just one cable/dock.

### We Test So You Can Rest

Rigorous testing<sup>4</sup> helps assure dock compatibility across select HP notebooks and select Apple®, Dell, and Lenovo notebooks with USB-C® power ports.

### More Ports. More Flexibility

More ports means more capabilities. With a TB4™, HDMI, two USB-C®, two DisplayPorts™, four USB-A 3.2 ports and an RJ45 port, you can connect multiple devices like a keyboard and mouse<sup>5</sup>.

### 1-year Limited Warranty

Get added peace of mind with a 1-year limited warranty that includes technical support, diagnostic services, and hardware replacement.



1. Windows Management Instrumentation installation required. Requires Windows 10 or higher.

2. 100% outer box/corrugate cushion packaging made from sustainably sourced certified and recycled fibers. Fiber cushions made from 100% recycled wood fiber and organic material. Any plastic cushions are made from >90% recycled plastic. Excludes plastic bags and plastic foam sheeting.

3. Recycling facilities not available in all locations.

4. Based on HP internal testing on select non-HP notebook models compatible with USB-C® industry standards. For HP notebook compatibility please visit - <https://pcb.inc.hp.com/webapp/#!/us-en> and search by notebook.

Certain Alt mode features are not supported, such as power button, MAC Address Pass-Through,

Wake-on LAN, and OOB Wake on LAN. Visit the HP Support page to determine your HP notebook's wattage and port specifications. Visit the support page of your non-HP notebook to determine its wattage and port specifications..

5. Comes with Power Cord.



## Specifications



### HP Thunderbolt G4 Dock

|  |   |
|--|---|
| <b>Part number</b>                                 | HP Thunderbolt 120W G4 Dock - 4J0A2AA<br>HP Thunderbolt 280W G4 Dock w/Combo Cable - 4J0G4AA  |
| <b>Dimensions (H x W x D)</b>                      | 3.9 x 3.9 x 2.7 in (98 x 98 x 68 mm)  |
| <b>Weight</b>                                      | 120W: 1.68 lbs (762 g)<br>280W: 1.76 lbs (798.3 g)  |
| <b>Security</b>                                    | HP Sure Start <sup>1</sup>  |
| <b>Operating systems<sup>2</sup></b>               | Windows 10, Windows 11; MacOS: Chrome   |
| <b>Systems management</b>                          | Wired vPRO Management   |
| <b>Top components</b>                              | LED and power button to power or wake host system <sup>3</sup>  |
| <b>Front components</b>                            | (1) USB Type-C <sup>®</sup> 3.2 Gen 2 (10 Gbps) port with data and power out (15W)  |
| <b>Side components</b>                             | Right side: (1) Kensington Standard Lock Slot<br>(2) USB 3.2 Gen 1 ports - 1 on each side (5 Gbps each)   |
| <b>Back components</b>                             | (2) USB 3.2 Gen 1 (5 Gbps each) Charging ports, power output: 7.5W<br>(1) HDMI 2.0 port<br>(2) DisplayPort 1.4 ports<br>(1) Power barrel port (120W or 280W)<br>(1) Ethernet port: 2 internal NIC cards to support 1 Gb and 2.5 Gb Ethernet <sup>4</sup><br>(1) USB-C <sup>®</sup> 3.2 Gen 1 DisplayPort<br>(1) Thunderbolt™ 4 port |
| <b>Network manageability features</b>              | vPRO (wired or wireless) <sup>4</sup><br>eTag<br>Disconnected Firmware updates<br>PXE Boot<br>Wake on LAN (from the Off, Sleep or Hibernation States <sup>5</sup> )<br>MAC address pass-through (from the On, Off, Sleep or Hibernation States <sup>6</sup> )<br>WLAN-LAN Switching   |
| <b>Networking</b>                                  | Supports 1 Gb and 2.5G Ethernet   |
| <b>Power to host (USB-C PD)</b>                    | Up to 100W via USB-C / 230W to host using 280W power supply via combo cable   |
| <b>External monitor support</b>                    | Up to 4   |
| <b>Power delivery (PD) profiles</b>                | PD 3.0: 5V/5A, 9V/5A, 12V/5A, 15V/5A, 20V/5A  |
| <b>Power to system</b>                             | Up to 100W/230W via USB-C   |
| <b>Operating voltage and current</b>               | 120W: Input 100 to 240V 1.7A 50 to 60Hz. Output is 19.5V at 6.15A<br>280W: Input 100 to 240V 1.7A 50 to 60Hz. Output is 19.5V at 14.35A   |
| <b>Temperature (operating)</b>                     | 0° C to 35° C (32° F to 95° F)  |
| <b>Relative humidity noncondensing (operating)</b> | 10 % to 90 %  |
| <b>Maximum altitude unpressurized (operating)</b>  | 15 m to 3,048 m (- 50 ft to 10,000 ft)  |
| <b>Cable length</b>                                | 0.8 M   |
| <b>Security slot type</b>                          | Standard Kensington lock slot   |
| <b>Warranty</b>                                    | 1-0-0   |
| <b>What's in the box</b>                           | Dock, power supply, power cord, warranty  |

1. HP Sure Start on HP Thunderbolt G4 dock supports firmware integrity verification and recovery it does not include real-time and runtime protections or Microsoft SCCM integration typically found on HP Sure Start in HP notebooks.

2. Operating systems supported: Windows 10 19H1 and up, Win 10 IoT Enterprise LTSC 2021, Windows 11 21H2 and up, ChromeOS M101 and up, Ubuntu Linux 20.04 LTS with 5.14 kernel, ThinPro OS 8.0 and MacOS Big Sur 12.1. Not all features work with all operating systems, ask your sales representative about compatibility with your PC. Linux testing currently underway and expected to be completed after launch.

3. The dock power button is not functional when connected to non-supported HP notebooks or non-HP notebooks.

4. Requires infrastructure that supports 2.5 GB Ethernet speeds.

5. Your computer might support Wake on LAN from the Off, Sleep or Hibernate States, or only when the computer is On or in Sleep.

6. Your computer might support MAC address pass-through the On, Off, Sleep or Hibernate States, or only when the computer is On or in Sleep.

Thunderbolt™ host systems require Thunderbolt™ software (minimum SW17.x).

Ethernet drivers need to be installed separately on non-HP Windows systems for headset auto switching functionality. Drivers available on HP website.

For MAC PCs, HP does not provide ethernet and audio drivers.

Firmware updates on Window-based host systems only.

Certain features are not functional on non-HP supported nor non-HP notebooks:

- Power button to turn on or wake the system.
- Wake on LAN from warm and cold dock.
- Wake on LAN from S4/S5.
- MAC Address pass-through S0, S3, S4, S5 warm and cold dock.



## Specifications

### HP Thunderbolt G4 Dock video resolution specifications

Video resolution and support is dependent on the maximum capability of the notebook.  
(All Thunderbolt resolutions assume at least dual DP streams. All high resolution mode resolutions assume 4 DP streams)

#### Host specification

|  |                             |   |
|--|-----------------------------|---|
| <b>DP 1.2 Thunderbolt™ host:</b>         |                             | Dual 4K @30Hz or dual 4K UHD @ 60Hz or (1) 6k TBT running multiple tiles<br>Triple displays: (3) 2.5k @30Hz<br>Quad displays: (3) 2.5k @30Hz + (1) FHD @ 30Hz   |
| <b>DP 1.2 USB-C host:</b>                | <b>Multi-function mode</b>  | Single display: (1) 4K DCI @ 30Hz<br>Dual display: (1) 4K DCI @ 30Hz + (1) FHD @ 30Hz<br>Triple displays: (3) FHD @30Hz   |
|  | <b>High resolution mode</b> | Single display: (1) 4K DCI @60Hz<br>Dual displays: (2) 4K DCI @ 30Hz<br>Triple displays: (3) 2.5k @30   |
| <b>DP 1.3/1.4 Thunderbolt host</b>       |                             | Single display: (1) 4K DCI @60Hz<br>Dual displays: (2) 4K UHD @60Hz<br>Triple displays: (2) 5K single cable@30Hz + (1) 2.5K@30Hz or (3) 4K DCI @ 30Hz   |
| <b>DP 1.3/1.4 USB-C host:</b>            | <b>Multi-function mode</b>  | Single display: (1) 5k Ultra Wide @60Hz or (1) 4K DCI @ 60Hz<br>Dual displays: (2) 4K UHD @60Hz<br>Triple displays: (3) 2.5K@ 30Hz  |
|  | <b>High resolution mode</b> | Single display: (1) 5k Ultra Wide (5120X1440) @ 60Hz or (1) 8k single cable @ 30Hz<br>Dual displays: (2) 4K UHD @60Hz or (2) 4K DCI @ 30Hz<br>Triple displays: (3) 4K DCI @ 30Hz  |
| <b>DP 1.4 with DSC Thunderbolt host:</b> |                             | Single display: up to (1) 8K Thunderbolt with multiple tiles @ 60Hz<br>Dual displays: (2)4K DCI @ 60Hz or<br>Triple displays: (3) 4K@ 60Hz up to (2) 5K single cable @30Hz + (1) 4K UHD @30Hz<br>Quad displays: (4) 4K DCI @ 60Hz                     |
| <b>DP 1.4 with DSC USB-C host:</b>       | <b>Multi-function mode</b>  | Single display: (1) 4K DCI @ 60Hz up to (1) 8K single cable @ 30Hz<br>Dual displays: (2) 4K DCI @ 60 Hz up to (1) 5K dual cable + (1) 4K<br>Triple displays: (3) 4K DCI @ 30Hz or (3) 4K UHZ @ 60Hz up to (2) 5K single cable@30Hz + (1) 4K UHD @30Hz |
|  | <b>High resolution mode</b> | Single display: upto (1) 8K dual @ 60Hz<br>Dual displays: (2) 4K DCI @ 60Hz or up to (2) 5K single cable + (1) 4K UHD@ 60 Hz<br>Triple displays: (3) 4K DCI @ 60Hz up to (2) 5K single cable + (1) 4K UHD   |

Sign up for updates  
[hp.com/go/getupdated](https://hp.com/go/getupdated)



Share with colleagues



Rate this document

Copyright © 2022 HP Development Company, L.P. The only warranties for HP products are set forth in the express limited warranty statements accompanying such products. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

DisplayPort™ is a trademark owned by the Video Electronics Standards Association (VESA®) in the United States and other countries.

USB Type-C® and USB-C® are registered trademarks of USB Implementers Forum.

Microsoft, Encarta, MSN, and Windows are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries.

4AA8-1295ENW, May 2022

