

- 80PLUS® Gold certified efficiency
- Fully modular cable management
- High power density design for compact size
- LLC half-bridge converter with DC-to-DC technology

The Polaris Series brings CHIEFTEC's trusted and proven experience with high quality, 80PLUS® Gold certified, fully modular power supplies back to the forefront of modern technology. Polaris Series PSU's feature state-of-the-art technical design including LLC half-bridge converter with DC-to-DC technology, as well as high power-density to allow higher efficiency and power output with a more compact size.

With the size of only 140mm in length and fully modular cable management, the Polaris Series is easy to install in any system for standard ATX PSU. Cable lengths of 650mm ensure that these power-supplies can be used even in large builds. Whether a small PSU housing for compact system is needed or longer cables for large systems, the Polaris Series can be trusted to do the job with top performance and efficiency.






Technical data	
Model	Polaris 550W
Artikel no.	PPS-550FC
EAN code	0753263076427
Weight (Net/Gross)	2.025 kg / 2.330 kg
Specification	ATX 12V 2.4
Form factor	PS II
Efficiency	80 PLUS® Gold
PFC	Active PFC
Fan	120mm silent fan
Dimension (DxWxH)	140mm x 150mm x 87mm
Security	AFC (Automatic Fanspeed Control) OCP (Overcurrent protection) OPP (Overload protection) OTP (Over-temperature protection) OVP (Overvoltage protection) SCP (Short-circuit protection) SIP (Surge & Inrush Protection) UVP (Undervoltage protection)
Warranty	24 Months

Output data						
Polaris Series 550W	AC Input	100-240V 50-60Hz 8.0A				
	DC Output	+3.3V	+5V	+12V	-12V	+5VSB
	Max. Current	20A	20A	45.8A	0.3A	3.0A
	Max. Combined Power	105W		550W	3.6W	15W
			550W			

* The listed specifications may be altered at any point in time without any pre-notice.

** Chieftec® is a registered trademark. All other brands and/or logos are property of the respective owners.

	Cable	Connectors	Length (mm)
	24 PIN (20+4)	1	650
	8 PIN PCI-E (6+2)	2	500/150
	8 PIN EPS (4+4)	2	650/150
	SATA	6	2x 450/150/150
	MOLEX	3	450/150/150/150
	FLOPPY	1	

Certification



* The listed specifications may be altered at any point in time without any pre-notice.

** Chieftec® is a registered trademark. All other brands and/or logos are property of the respective owners.