

USB-C Dual Monitor Multiport Adapter up to 4K 60Hz USB-C DP Alt Mode Video Output & HDMI 2.0, or 1080p VGA, 100W PD Pass-Through, USB Type C Mini Dock, USB-C Docking Station, MST Hub - TAA

Product ID: DKM31C3HVCPD



This USB-C Multiport Adapter/Docking Station with DisplayPort 1.4 (Alt Mode) and Multi-Stream Transport (MST), features three video output options (HDMI, VGA and USB-C video) to support a single or multi-monitor workstation. The USB-C video port supports USB 3.2 Gen 2 (10Gbps) with 10W of power, to connect a USB-C monitor or a USB-C peripheral. In addition, the Docking Station also features a 2-Port USB-A 3.2 Gen 2 (10 Gbps) Hub, a Gigabit Ethernet port, and providing advanced charging through a USB Power Delivery (PD) 3.0 pass-through port. The Multiport Adapter connects to a laptop's USB-C or Thunderbolt 3/4 port, using the integrated 10-inch (25cm) USB-C cable.

The compact USB Type-C Docking Station features three video output options to turn your laptop into a single or multi-monitor workstation.

HDMI Port

Provides HDR video with resolutions up to 4K 60Hz.

VGA Port

Provides analog video with resolutions up to 1080p 60Hz.

USB-C Port

Provides the industry's first downstream full featured video or data (10Gbps) USB-C port that supports DP Alt Mode video or peripheral connection, on a non-Thunderbolt adapter.

The advanced video versatility of this Multiport Adapter, makes it suitable for a wide variety of applications:

- Connect a portable USB-C monitor as an extended display, to obtain a high resolution external monitor during on-the-go travel between an office desk, home office, hot desk, or the boardroom.

- Connect a USB-C peripheral to the downstream 10Gbps USB-C port, while using the HDMI and/or VGA ports to connect external monitor(s) as extended display(s).
- Connect multiple external monitors as extended displays, using any combination of the two video ports, to create a high-productivity workstation. USB-C video adapters (sold separately) can be used to connect HDMI, DVI, VGA, or DisplayPort monitors to the USB-C video port.

This Docking Station utilizes MST to obtain video versatility. Video performance is based upon the number of attached monitors and the host computer's video controller. Consult the manufacturer of the host computer to determine MST video performance. StarTech.com performs rigorous performance benchmarks with all major host computer video controllers. The video performance results of our testing are listed below:

Notes:

- This chart displays maximum performance capabilities with Intel Integrated Graphics (performance may vary depending on system configuration)

The USB 3.2 Gen 2 (10Gbps) hub features two USB-A ports and one USB-C port, for connecting your USB devices. The downstream USB-C port can be used to connect a monitor, or USB-C peripheral with up to 10W (5V/2A) of power, to power or charge your peripherals.

A versatile docking solution for use at an office desk, home office, hot desk, or in the boardroom. It's portable enough to be carried in a bag / backpack for mobile use. The USB-C dock can operate with bus-power alone, or with a USB-C power adapter connected to the USB Power Delivery pass-through port - for full laptop and USB-C peripheral charging. The lightweight docking station features a built-in 10 in (25 cm) USB-C host cable for added setup flexibility and to reduce port strain with laptop connection elevated off desktop surface.

With support for USB PD 3.0 (100W - 80W charging, 20W reserved for multiport adapter), the Multiport Adapter enables charging of the host computer and peripherals connected to the USB-C port. USB PD is only available when a USB-C power adapter is connected to the PD pass-through port. PD 3.0 features Fast Role Swap (FRS) which prevents USB data disruption when switching power sources (e.g., USB-C power adapter to bus power).

The Gigabit Ethernet port ensures reliable wired network access. Support for Wake-on-LAN (WoL) enables remote booting of the host computer.

Developed to improve performance and security, StarTech.com Connectivity Tools is the only software suite on the market that works with a wide range of IT connectivity accessories. The software suite includes:

Advanced Windows Layout Utility: Setup and save custom windows layouts.

MAC Address Pass-Through Utility: Improve network security.

USB Event Monitoring Utility: Track and log connected USB devices.

Wi-Fi Auto Switch Utility: Enable users to quickly access faster network speeds via wired LAN.

For more information and to download the StarTech.com Connectivity Tools application, please visit:
www.startech.com/connectivity-tools

This product is backed for 3-years by StarTech.com, including free lifetime 24/5 multi-lingual technical assistance.

Certifications, Reports and Compatibility



Applications

- Home office IT deployment, ideal for traveling between the home and office
- Connect a portable USB-C monitor as an extended display during on-the-go travel between your office desk, home office, hotel desk, or the boardroom
- Connect a USB-C peripheral to the downstream 10Gbps USB-C port, while using the HDMI and/or VGA port(s) to connect external monitor(s)
- Charge your tablets and smartphones from the 10W USB-C port

Features

- **DUAL MONITOR MULTIPOINT ADAPTER:** Multi monitor 4K UHD mini dock with USB-C DP Alt mode video output, HDMI 2.0b, or VGA, 2 x USB-A hub, 100W USB-C PD Pass-Through (80W laptop charging), Gigabit Ethernet; USB-C video port also supports USB 10Gbps data
- **USB-C VIDEO OUTPUT:** USB-C hub with downstream USB-C port (video + 10Gbps data) supports USB-C or desktop monitors; NOTE: Host system must support USB-C Power Delivery and DP alt mode. For a multi-monitor configuration, the computer must support MST
- **VIDEO PERFORMANCE:** Dual Monitor support up to 1 x 4K 30Hz & 1 x 1440p 60Hz through USB-C & HDMI with Intel 11th Gen DP 1.4 Alt Mode or higher Processors & Discreet GPU, Works w/DP 1.2 laptops supporting 2x 1080p; Single display on Apple M1/M2/M3 Pro/Max
- **RELIABLE PERFORMANCE:** Adapter is designed to bus power the portable USB-C monitor upto 12W; 100W USB-C PD Pass-Through w/20W reserved for adapter to avoid video flickering, device dropouts or overdrawing power common in other hubs
- **OUR ADVANTAGE:** Includes IT Pro Connectivity Tools to improve network performance and security - featuring MAC Address passthrough, USB Event Monitoring, Windows Layout, and Wi-Fi Auto Switch; Works w/ USB-C, Thunderbolt 3/4, Windows, Linux, ChromeOS

Hardware

Warranty	3 Years
4K Support	Yes

Fast-Charge Port(s)	Yes
Displays Supported	2
Interface	USB 3.2 Gen 2 (10 Gbps)
Bus Type	USB-C
Industry Standards	HDMI 2.0b HDR10 DisplayPort 1.4 USB 3.2 Gen 2 (10Gbps) USB Power Delivery Specification Rev. 3.0
Chipset ID	Genesys Logic - GL3590 Genesys Logic - GL9510-UFP Genesys Logic - GL9510-DFP Realtek - RTD2142 Realtek - RTL8153

Performance

Wake On Lan	Yes
Maximum Data Transfer Rate	10Gbps
Maximum Digital Resolutions	HDMI: Up to 4K (3840 x 2160p) 60Hz USB-C (DP Alt Mode): Up to Up to 4K (3840 x 2160p) 60Hz VGA: Up to 1080p (1920x1200p/1920x1080p)
Type and Rate	USB 3.2 Gen 2 - 10 Gbit/s
UASP Support	Yes
Compatible Networks	10/100/1000 Mbps
Full Duplex Support	Yes

General Specifications Maximum Laptop Charging: 80W

MTBF 40,030 Hours

Connector(s)

External Ports	<p>1 - HDMI (19 pin)</p> <p>1 - VGA (15 pin, High Density D-Sub)</p> <p>1 - USB 3.2 Type-C (24 pin, Gen 2, 10Gbps, 10W Power, DP Alt-Mode Video)</p> <p>2 - USB 3.2 Type-A (9 pin, Gen 2, 10Gbps)</p> <p>1 - USB Type-C (24 pin) USB Power Delivery Only</p> <p>1 - RJ-45</p>
Host Connectors	<p>1 - USB 3.2 Type-C (24 pin, Gen 2, 10Gbps)</p>

Software

OS Compatibility	Windows 7, 8, 8.1, 10, 11, 11 ARM<br / >Chrome OS
------------------	---

Special Notes / Requirements

System and Cable Requirements	<p>A host laptop with an available USB-C port (to ensure full adapter functionality, the host USB-C port must support USB Power Delivery 2.0 and DP alt mode).</p>
-------------------------------	--

For a multi-monitor configuration, the computer must support MST

Optional: USB-C power adapter (e.g., your laptop's USB-C based power adapter).

Note	<p>Not all USB-C ports support the full functionality of the USB Type-C standard. Ensure that your host USB-C port supports USB Power Delivery and DP alt mode.</p>
------	---

The adapter can connect to USB-C ports that don't support USB PD. PD will not occur without a connection to a PD capable USB-C port. However, in this configuration if a power adapter is connected to the multifunction adapter, it will not pass power through to your host laptop.

A 4K-capable display is required to achieve 3840 x 2160p resolution (4K is also known as 4K x 2K).

A 4K-capable computer is required to achieve 3840 x 2160p resolution (4K is also known as 4K x 2K).

USB 3.2 Gen 2 (10Gbps) is also known as USB 3.1 Gen 2

(10Gbps).

Your laptop might have specific charging requirements. For example, if your laptop requires exactly 60W of power and an adapter consumes some of the 60W, your laptop might not recognize that it is getting enough power. For more information about Power Delivery, refer to the manufacturer of your hardware.

Indicators

LED Indicators	1 - Network Link LED
	1 - Network Activity LED (Amber)

Power

Power Source	Bus Powered and Host USB-C Power Adapter
Output Voltage	5 DC
Power Consumption (In Watts)	20W

Environmental

Operating Temperature	0C to 60C (32F to 140F)
Storage Temperature	-20C to 60C (-4F to 140F)
Humidity	<90% RH

Physical Characteristics

Color	Space Gray
Material	Plastic
Cable Length	9.8 in [25 cm]
Product Length	5.7 in [14.4 cm]
Product Width	3.3 in [8.3 cm]
Product Height	1.1 in [2.8 cm]
Weight of Product	5.9 oz [168.0 g]

Packaging Information

Package Length	8.3 in [21.0 cm]
----------------	------------------

Package Width	5.7 in [14.5 cm]
Package Height	1.6 in [4.0 cm]
Shipping (Package) Weight	9.2 oz [262.0 g]

What's in the Box

Included in Package	1 - Docking Station
	1 - Quick-Start Guide

Warranty Information

Warranty	3 Years
----------	---------

****Product appearance and specifications are subject to change without notice.***