

OVERVIEW



| | |
|----------------------------------|--|
| 1. Smart card reader * | 5. 2x Thunderbolt 4 |
| 2. USB-A (USB 5Gbps) | 6. HDMI |
| 3. USB-A (USB 5Gbps), Always On | 7. Headphone / microphone combo jack (3.5mm) |
| 4. Kensington Nano Security Slot | 8. Nano-SIM card slot * |

Notes:

- Items with * are only available on selected models

PERFORMANCE

Processor

Processor Family

- Intel® U Series Core Ultra 5 / 7 or Intel® H Series Core Ultra 7 Processor (Series 2) - Arrow Lake (ARL)
- Intel® V Series Core Ultra 5 / 7 Processor (Series 2) - Lunar Lake (LNL)

Processor**

| Processor Name | Cores | Threads | Base Frequency | Max Frequency | Cache | Processor Graphics | NPU | Overall TOPS |
|-------------------------|--|---------|--|--|-------------------------|--|--------------------------------|----------------|
| Core Ultra 5 225U (ARL) | 12 (2 P-core + 8 E-core + 2 LP E-core) | 14 | P-core 1.5GHz / E-core 1.3GHz / LP E-core 700MHz | P-core 4.8GHz / E-core 3.8GHz / LP E-core 2.4GHz | 12MB Intel® Smart Cache | Intel® Graphics, up to 8 TOPS | Intel® AI Boost, up to 12 TOPS | Up to 24 TOPS |
| Core Ultra 5 226V (LNL) | 8 (4 P-core + 4 LP E-core) | 8 | P-core 2.1GHz / LP E-core 2.1GHz | P-core 4.5GHz / LP E-core 3.5GHz | 8MB Intel® Smart Cache | Intel® Arc™ Graphics 130V, up to 53 TOPS | Intel® AI Boost, up to 40 TOPS | Up to 97 TOPS |
| Core Ultra 5 228V (LNL) | 8 (4 P-core + 4 LP E-core) | 8 | P-core 2.1GHz / LP E-core 2.1GHz | P-core 4.5GHz / LP E-core 3.5GHz | 8MB Intel® Smart Cache | Intel® Arc™ Graphics 130V, up to 53 TOPS | Intel® AI Boost, up to 40 TOPS | Up to 97 TOPS |
| Core Ultra 5 235U (ARL) | 12 (2 P-core + 8 E-core + 2 LP E-core) | 14 | P-core 2.0GHz / E-core 1.6GHz / LP E-core 700MHz | P-core 4.9GHz / E-core 4.1GHz / LP E-core 2.4GHz | 12MB Intel® Smart Cache | Intel® Graphics, up to 8 TOPS | Intel® AI Boost, up to 12 TOPS | Up to 24 TOPS |
| Core Ultra 5 236V (LNL) | 8 (4 P-core + 4 LP E-core) | 8 | P-core 2.1GHz / LP E-core 2.1GHz | P-core 4.7GHz / LP E-core 3.5GHz | 8MB Intel® Smart Cache | Intel® Arc™ Graphics 130V, up to 53 TOPS | Intel® AI Boost, up to 40 TOPS | Up to 97 TOPS |
| Core Ultra 5 238V (LNL) | 8 (4 P-core + 4 LP E-core) | 8 | P-core 2.1GHz / LP E-core 2.1GHz | P-core 4.7GHz / LP E-core 3.5GHz | 8MB Intel® Smart Cache | Intel® Arc™ Graphics 130V, up to 53 TOPS | Intel® AI Boost, up to 40 TOPS | Up to 97 TOPS |
| Core Ultra 7 255H (ARL) | 16 (6 P-core + 8 E-core + 2 LP E-core) | 16 | P-core 2.0GHz / E-core 1.5GHz / LP E-core 700MHz | P-core 5.1GHz / E-core 4.4GHz / LP E-core 2.5GHz | 24MB Intel® Smart Cache | Intel® Arc™ 140T GPU, up to 74 TOPS | Intel® AI Boost, up to 13 TOPS | Up to 96 TOPS |
| Core Ultra 7 255U (ARL) | 12 (2 P-core + 8 E-core + 2 LP E-core) | 14 | P-core 2.0GHz / E-core 1.7GHz / LP E-core 700MHz | P-core 5.2GHz / E-core 4.2GHz / LP E-core 2.4GHz | 12MB Intel® Smart Cache | Intel® Graphics, up to 8 TOPS | Intel® AI Boost, up to 12 TOPS | Up to 24 TOPS |
| Core Ultra 7 258V (LNL) | 8 (4 P-core + 4 LP E-core) | 8 | P-core 2.2GHz / LP E-core 2.2GHz | P-core 4.8GHz / LP E-core 3.7GHz | 12MB Intel® Smart Cache | Intel® Arc™ Graphics 140V, up to 64 TOPS | Intel® AI Boost, up to 47 TOPS | Up to 115 TOPS |
| Core Ultra 7 265H (ARL) | 16 (6 P-core + 8 E-core + 2 LP E-core) | 16 | P-core 2.2GHz / E-core 1.7GHz / LP E-core 700MHz | P-core 5.3GHz / E-core 4.5GHz / LP E-core 2.5GHz | 24MB Intel® Smart Cache | Intel® Arc™ 140T GPU, up to 75 TOPS | Intel® AI Boost, up to 13 TOPS | Up to 97 TOPS |
| Core Ultra 7 265U (ARL) | 12 (2 P-core + 8 E-core + 2 LP E-core) | 14 | P-core 2.1GHz / E-core 1.7GHz / LP E-core 700MHz | P-core 5.3GHz / E-core 4.2GHz / LP E-core 2.4GHz | 12MB Intel® Smart Cache | Intel® Graphics, up to 8 TOPS | Intel® AI Boost, up to 12 TOPS | Up to 24 TOPS |
| Core Ultra 7 268V (LNL) | 8 (4 P-core + 4 LP E-core) | 8 | P-core 2.2GHz / LP E-core 2.2GHz | P-core 5.0GHz / LP E-core 3.7GHz | 12MB Intel® Smart Cache | Intel® Arc™ Graphics 140V, up to 66 TOPS | Intel® AI Boost, up to 48 TOPS | Up to 118 TOPS |

AI (Artificial Intelligence)

AI PC Category**

- Copilot+ PC (Lunar Lake)^[1]
- AI PC (Arrow Lake)^[2]

NPU

Integrated Intel® AI Boost, up to 48 TOPS

Notes:

[1] Copilot+ PCs have at least 16GB RAM, 256GB storage, and a NPU that runs 40+ TOPs to run the latest AI tools build-in latest Windows® 11 to accelerate productivity and creativity.

[2] AI PCs have a NPU capable of 10+ TOPs to run the Copilot assistant by pressing the optional Microsoft® Copilot key or using Win + C.

Operating System

Operating System**

- Windows® 11 Pro
- Windows® 11 Home
- Windows® 11 Home Single Language
- Ubuntu Linux^[1]
- Linux^[2]
- No preload operating system

Notes:

[1], [2] Some features may not be supported on the system with Linux preload, including but not limited to Intel® RST RAID, MIPI computer vision camera, WWAN, Human Presence Detection, etc.

Graphics

Graphics**

| Graphics | Type | Memory | Key Features |
|---------------------------|------------|--------|---------------|
| Intel® Graphics | Integrated | Shared | DirectX® 12.2 |
| Intel® Arc™ 140T GPU | Integrated | Shared | DirectX® 12.2 |
| Intel® Arc™ Graphics 130V | Integrated | Shared | DirectX® 12.2 |
| Intel® Arc™ Graphics 140V | Integrated | Shared | DirectX® 12.2 |

Monitor Support

Monitor Support^[1]

Arrow Lake: supports up to 4 independent displays (native display and 3 external monitors via HDMI® and Thunderbolt™)

Lunar Lake: supports up to 3 independent displays (native display and 2 external monitors via HDMI® and Thunderbolt™)

- HDMI® supports up to 4K@60Hz
- Thunderbolt™ supports up to 8K@60Hz^[2]

Notes:

[1] Refresh rates >60hz also supported, however max resolution will be limited.

[2] 8K resolution support needs 2 display pipes. That is, simultaneous display number will "-1" when 8K resolution displayed.

Chipset

Chipset

Intel® SoC (System on Chip) platform

Memory

Max Memory

- 16GB soldered memory, not upgradable
- 32GB soldered memory, not upgradable
- 64GB soldered memory, not upgradable

Memory Slots

Memory soldered to systemboard, no slots, dual-channel

Memory Type**

- Lunar Lake: LPDDR5X-8533, MoP (Memory on Package) memory
- Arrow Lake: LPDDR5X-7467^[1]

Notes:

[1] Installed memory is actually LPDDR5X-8533 but runs as LPDDR5X-7467 due to platform limitation.

Storage**Max Storage Support^[1]**

One drive, up to 1TB M.2 2280 SSD

Storage Slot^[2]

- Models with U series processor: one M.2 2280 PCIe® 4.0 x4 slot
- Models with V or H series processor: one M.2 2280 PCIe® 5.0 x4 slot

Storage Type**

| Disk Type | Interface | Offering | Security |
|--------------|--|---------------------|----------|
| M.2 2280 SSD | PCIe® NVMe®, PCIe® 4.0 x4 | 256GB / 512GB / 1TB | Opal 2.0 |
| M.2 2280 SSD | PCIe® NVMe®, PCIe® 4.0 x4 Performance | 512GB | Opal 2.0 |
| M.2 2280 SSD | PCIe® NVMe®, PCIe® 5.0 x4 Performance ^[3] | 512GB / 1TB | Opal 2.0 |

Notes:

[1] The storage capacity supported is based on the test results with current Lenovo® storage offerings.

[2] The actual data transfer rate of the following PCIe® interface also depends on the capabilities of the connected PCIe® device. The listed values represent theoretical maximums.

PCIe® 3.0 (x2 / x4): 2 GB/s (16 Gbps) / 4 GB/s (32 Gbps);

PCIe® 4.0 (x2 / x4): 4 GB/s (32 Gbps) / 8 GB/s (64 Gbps);

PCIe® 5.0 (x2 / x4): 8 GB/s (64 Gbps) / 16 GB/s (128 Gbps).

[3] PCIe® 5.0 x4 SSD is downgraded to PCIe® 4.0 x4 performance on the models with U series processor.

Removable Storage**Card Reader**

No card reader

Multi-Media**Audio Chip**

High Definition (HD) Audio, Realtek® ALC3287 codec

Speakers

Stereo speakers, 2W x2, Dolby Atmos®

Microphone

- Dual-microphone array, 360° far-field, Dolby Voice®
- No microphone^[1]

Camera**

- 5.0MP + IR discrete, with privacy shutter, fixed focus, Computer Vision on Image Signal Processor (ISP), temporal noise reduction^[2]
- 5.0MP, with privacy shutter, fixed focus, temporal noise reduction^[3]
- No camera^[4]

Notes:

[1] No microphone is for special bid only.

[2] Computer Vision on ISP is only available on the models with preloaded OS.

[3] 5.0MP camera is only available for Arrow Lake.

[4] No camera is for special bid only.

Battery

Battery^[1]

58Wh Rechargeable Li-ion Battery, supports Rapid Charge (charge up to 80% in 1hr)

Battery Life^[2]

Configuration 1 (max battery life)

MobileMark® 25: up to 23.46 hr with 677 performance score @250nits

JEITA-BAT 3.0 (Video/Idle): up to 16.14 hr / 38.97 hr @200nits

Local video playback: up to 34.96 hr @150nits

Alternate configuration 2

MobileMark® 25: up to 18.58 hr with 646 performance score @250nits

JEITA-BAT 3.0 (Video/Idle): up to 15.81 hr / 27.39 hr @200nits

Local video playback: up to 28.27 hr @150nits

Alternate configuration 3

MobileMark® 25: up to 16.68 hr with 583 performance score @250nits

JEITA-BAT 3.0 (Video/Idle): up to 18.32 hr / 34.9 hr @200nits

Local video playback: up to 28.9 hr @150nits

Notes:

[1] Rapid charge is only guaranteed when the computer is turned off or in standby mode or in hibernation mode. When the computer is powered on, the Charge Time will vary depending on system power consumption and AC adapter power.

[2] Configuration 1 (max battery life): WUXGA (non-touch), Intel® Core™ Ultra 5 228V, 32GB LPDDR5X, Win 11, 58Wh battery, best power efficiency power mode

Alternate configuration 2: WUXGA (touch), Intel® Core™ Ultra 5 238V, 32GB LPDDR5X, Win 11, 58Wh battery, best power efficiency power mode

Alternate configuration 3: WUXGA low power (non-touch), Intel® Core™ Ultra 5 225U, 16GB LPDDR5X, Win 11, 58Wh battery, best power efficiency power mode

All battery life claims are approximate maximum and based on results using [MobileMark® 25](#), JEITA 3.0, continuous 1080p local video playback (using default Media Player in Fullscreen mode with 150nits brightness and default volume level), or Google Power Load Test (PLT) battery-life benchmark tests.

Actual battery life will vary depending on many factors such as product configuration, software, wireless functionality, power management settings, and screen brightness.

The maximum capacity of the battery will decrease with time, ambient temperature and use.

Refer to [Microsoft® link](#) for more information about the Windows® Performance power slider.

Power Adapter

Power Adapter**^[1]

- 65W USB-C® (2-pin) AC adapter, supports PD 3.0, 100-240V, 50-60Hz
- 65W USB-C® (3-pin) AC adapter, supports PD 3.0, 100-240V, 50-60Hz
- 65W USB-C® nano GaN (2-pin, wall-mount) AC adapter, supports PD 3.0, 100-240V, 50-60Hz
- 65W USB-C® nano GaN (3-pin, wall-mount) AC adapter, supports PD 3.0, 100-240V, 50-60Hz
- 65W USB-C® slim GaN (2-pin) AC adapter, supports PD 3.0, 100-240V, 50-60Hz
- 65W USB-C® slim GaN (3-pin) AC adapter, supports PD 3.0, 100-240V, 50-60Hz
- No power adapter

Notes:

[1] AC adapter offerings depend on the country.

DESIGN

Display

Display**^[1]

| Size | Resolution | Touch | Type | Brightness | Surface | Aspect Ratio | Contrast Ratio | Color Gamut | Refresh Rate | Viewing Angle (L/R/U/D) | Key Features |
|------|------------|-------|--------------------|------------|------------|--------------|----------------|-------------|--------------|-------------------------|--------------|
| 14" | WUXGA | Non- | IPS ^[2] | 400nits | Anti-glare | 16:10 | 800:1 | 45% | 60Hz | 89° / 89° / | 3M™ DBEF5 |

| | | | | | | | | | | | |
|-----------------------|-------------------|-------------------|--------------------|---------|--|-------|-----------|-------------|-----------|-----------------------|---|
| | (1920x1200) | touch | | | | | | NTSC | | 89° / 89° | |
| 14" | WUXGA (1920x1200) | On-cell touch | IPS ^[3] | 400nits | Anti-glare | 16:10 | 800:1 | 45% NTSC | 60Hz | 89° / 89° / 89° / 89° | Eyesafe [®] Certified 2.0, 3M [™] DBEF5 |
| 14" | WUXGA (1920x1200) | Non-touch | IPS ^[4] | 500nits | Anti-glare | 16:10 | 800:1 | 100% sRGB | 60Hz | 89° / 89° / 89° / 89° | Low power, Eyesafe [®] Certified 2.0 |
| 14" | WUXGA (1920x1200) | On-cell touch | IPS ^[5] | 500nits | Anti-glare | 16:10 | 1500:1 | 100% sRGB | 60Hz | 89° / 89° / 89° / 89° | ThinkPad [®] Privacy Guard, Eyesafe [®] Certified 2.0 |
| 14" ^[6] | 2.8K (2880x1800) | Add-on Film touch | OLED | 500nits | Anti-glare, anti-reflection, anti-smudge | 16:10 | 100,000:1 | 100% DCI-P3 | 120Hz VRR | 85° / 85° / 85° / 85° | Dolby Vision [®] , Eyesafe [®] Certified 2.0 |

Touchscreen**

- Add-on Film Touch, supports 10-point touch
- On-cell multi-touch, supports 10-point touch
- Non-touch

Screen-to-Body Ratio

88%

Notes:

- [1] 3M[™] DBEF5 (Dual Brightness Enhancement Film) improves the experience with higher brightness and lower energy.
- [2], [3], [4], [5] IPS (in-plane switching) technology may refer to IPS, PLS, ADS, AHVA, AAS.
- [6] 2.8K display is only available for Arrow Lake.

Input Device

Pen

No support

Keyboard

6-row, spill-resistant, multimedia Fn keys, key travel 1.5mm / 1.35mm (Fn row & G/H/B), Copilot key

Keyboard Backlight

LED backlight

UltraNav[™]

TrackPoint[®] pointing device, double-tap to open the TrackPoint[®] Quick Menu
Glass-like Mylar[®] surface multi-touch 3-button Trackpad, 61 x 115 mm (2.40 x 4.53 inches)

Mechanical

Dimensions (WxDxH)^[1]

| Models | Dimensions |
|-------------------------|---|
| Models with grey cover | 313.6 x 219.4 x 11.2/15.8 (front/rear), 19.75 (maximum) mm 12.35 x 8.64 x 0.44/0.62 (front/rear), 0.78 (maximum) inches |
| Models with black cover | 313.6 x 219.4 x 11.43/16.4 (front/rear), 19.75 (maximum) mm 12.35 x 8.64 x 0.45/0.65 (front/rear), 0.78 (maximum) inches |

Weight^[2]

| Models | Weight |
|------------|--------------------------------|
| Arrow Lake | Starting at 1.24 kg (2.72 lbs) |
| Lunar Lake | Starting at 1.28 kg (2.82 lbs) |

Case Color**

- Black
- Grey^[3]

Case Material

Carbon fiber hybrid or aluminium (top), aluminium (bottom)^[4]

Notes:

[1] The system dimensions may vary depending on configurations.

[2] The system weight is approximate and based on results in Lenovo® lab, which varies depending on the source of component, variance of the distribution of each component, and manufacturing process. It may not be the exact weight for each specific model.

[3] Grey case color is only available for Arrow Lake.

[4] Aluminium top cover is only available for Arrow Lake.

CONNECTIVITY

Network

WLAN + Bluetooth®^{[1][2]}**

- Intel® Wi-Fi® 6E AX211, 802.11ax 2x2 Wi-Fi® + Bluetooth® 5.3
- Intel® Wi-Fi® 6E AX211, 802.11ax 2x2 Wi-Fi® + Bluetooth® 5.3, Intel® vPro® technology support^[3]
- Intel® Wi-Fi® 7 BE201, 802.11be 2x2 Wi-Fi® + Bluetooth® 5.4
- Intel® Wi-Fi® 7 BE201, 802.11be 2x2 Wi-Fi® + Bluetooth® 5.4, Intel® vPro® technology support^[4]

WWAN**

- Wireless WAN upgradable to 4G (with antenna ready)
- Wireless WAN upgradable to 5G (with antenna ready)^[5]
- Quectel EM061K-GL, 4G LTE CAT6, M.2 card, with embedded eSIM functionality
- Quectel RM520N-GL, 5G Sub-6 GHz, M.2 card, with embedded eSIM functionality
- No support

SIM Card^[6]**

- KDDI eSIM Program (Japan)
- KDDI eSIM Program 3-year (Japan)
- KDDI eSIM Program 3-year with international roaming (Japan)
- KDDI eSIM Program 4-year (Japan)
- KDDI eSIM Program 4-year with international roaming (Japan)
- KDDI eSIM Program 5-year with international roaming (Japan)
- No physical SIM card inbox

Ethernet

No onboard Ethernet^[7]

NFC

No support

Notes:

[1] Wi-Fi® operation (including Wi-Fi® 6, Wi-Fi® 6E, Wi-Fi® 7, etc.) is subject to the regulatory requirements of each country. Bluetooth® may operate at a lower version than hardware design depending on the factors such as operating system, driver, etc.

[2] Wi-Fi® 6E is only available for Arrow Lake.

[3], [4] Intel® vPro® platform requires the hardware and software necessary to deliver the manageability use cases, security features, system performance, and stability that define the platform. For detailed vPro® support information, please refer to the System Management section.

[5] Wireless WAN upgradable to 5G is only available in EMEA.

[6] KDDI eSIM Program has no physical SIM card inbox and is for special bid only.

[7] Ethernet support via optional Lenovo® USB-C® to Ethernet Adapter.

Ports^[1]

Standard Ports

- 1x USB-A (USB 5Gbps / USB 3.2 Gen 1)
- 1x USB-A (USB 5Gbps / USB 3.2 Gen 1), Always On
- 2x USB-C® (Thunderbolt™ 4 / USB4® 40Gbps), with USB PD 3.1 and DisplayPort™ 2.1

- 1x HDMI® 2.1, up to 4K/60Hz
- 1x Headphone / microphone combo jack (3.5mm)

Optional Ports***

- 1x Nano-SIM card slot (WWAN support models)
- 1x Smart card reader

Notes:

[1] The transfer speed of the ports will vary and, depending on many factors, such as the processing speed of the host device, file attributes and other factors related to system configuration and your operating environment, will be slower than theoretical speed.

Docking

Docking

Various docking solutions supported via Thunderbolt™ / USB-C®.

For more compatible docking solutions, please visit [Docking for ThinkPad® T14s Gen 6 \(Intel®\)](#)

SECURITY & PRIVACY

Security

ThinkShield

ThinkShield is a comprehensive security solution that encompasses hardware, software, and supply chain components. For more details, visit [here](#)

Security Chip

Discrete TPM 2.0 (TCG certified, FIPS 140-3 certified) and Microsoft® Pluton TPM 2.0, one enabled at one time^[1]

Physical Locks

Kensington® Nano Security Slot™, 2.5 x 6 mm

Smart Card Reader

- Smart card reader, supports ISO 7816 and EMV
- No smart card reader

Fingerprint Reader

- Touch style fingerprint reader integrated in power button, match-on-chip
- No fingerprint reader

BIOS Security

- Certificate-based BIOS authentication
- FIDO (Fast Identity Online) authentication
- NVMe® password
- Power-on password
- Supervisor password
- System management password
- Self-healing BIOS
- More BIOS security features (Arrow Lake), please visit [BIOS Simulator](#)^[2]
- More BIOS security features (Lunar Lake), please visit [BIOS Simulator](#)^[3]

Other Security

- (Optional) Computer Vision-based Human Presence Detection on Image Signal Processor (ISP)
- (Optional) Camera privacy shutter
- (Optional) IR camera for Windows® Hello (facial recognition)

Notes:

[1] By default, discrete TPM 2.0 is enabled and Microsoft® Pluton TPM 2.0 is disabled. Microsoft® Pluton TPM 2.0 is only available for Lunar Lake.

[2], [3] The BIOS simulator is just for reference. Default settings and some options may vary depending on the hardware, operating system and BIOS version.

MANAGEABILITY

System Management

System Management^[1]

- Intel® vPro® Enterprise^[2]
- Non-vPro®

Notes:

[1] Intel® vPro® platform require an eligible Intel® processor, a supported operating system, Intel® LAN and/or WLAN silicon, firmware enhancements, and other hardware and software necessary to deliver the manageability use cases, security features, system performance, and stability that define the platform. See [Intel® vPro® Platform](#) for details.

[2] Intel® vPro® offers a superset of DASH's defined capabilities.

SERVICE

Warranty

Base Warranty**

- 1-year courier or carry-in service
- 1-year courier or carry-in with 2-year system board service (Korea only)
- 1-year limited onsite service
- 3-year (1-yr battery) courier or carry-in service
- 3-year (1-yr battery) limited onsite service
- No base warranty

ACCESSORIES

Bundled Accessories

Bundled Accessories***^[1]

- Lenovo® HDMI® to VGA Monitor Adapter
- Lenovo® USB-C® to DisplayPort™ Adapter
- Lenovo® USB-C® to Ethernet Adapter (1Gbps)
- Lenovo® USB-C® to VGA Adapter
- None

Notes:

[1] For more compatible accessory solutions, please visit [Accessories for ThinkPad® T14s Gen 6 \(Intel®\)](#).

OPERATING REQUIREMENTS

Operating Environment

Temperature^[1]

- Operating: 5°C (41°F) to 35°C (95°F)
- Storage and transportation in original shipping package: -20°C (-4°F) to 60°C (140°F)
- Storage without package: 5°C (41°F) to 43°C (109°F)

Relative Humidity

- Operating: 8% to 95% at wet-bulb temperature 23°C (73°F)
- Storage and transportation: 5% to 95% at wet-bulb temperature 27°C (81°F)

Altitude

Maximum altitude (without pressurization): 3048 m (10,000 ft)

Notes:

[1] When you charge the battery, its temperature must be no lower than 10°C (50°F).

ENVIRONMENTAL

Sustainability

Material^[1]

30% recycled Carbon fiber on top cover

90% recycled magnesium on keyboard frame
55% recycled aluminum on bottom cover
85% PCC recycled plastic used in backlit keycaps
90% PCC recycled plastic used in speaker enclosure
90% recycled plastic used in the 58Wh battery frame
90% PCC recycled plastic used in standard 65W slim adapter
95% PCC recycled plastic used in cable / antenna holders
100% plastic free packaging with FSC certified paper

Notes:

[1] PCC: Post Consumer Content, recycled materials from customers.

CERTIFICATIONS

Green Certifications^[1]

Green Certifications^[2]

- ENERGY STAR® 9.0
- EPEAT™ Gold Registered
- ErP Lot 6/26
- RoHS compliant
- TCO Certified, generation 10

Notes:

[1] The items listed under the "Green Certifications" section may not only refer to certification but also registration or self-declaration. For ESG & regulatory compliance documents, please visit <https://compliance.lenovo.com>.

[2] EPEAT™ registration and ENERGY STAR® certification are optional and only available on the models with preloaded OS. Please visit epeat.net and energystar.gov for more information.

Other Certifications

Mil-Spec Test

MIL-STD-810H military test passed

Other Certifications

- (Optional) EyeSafe® Certified 2.0
 - (Optional) Intel® Evo™ Platform
- Feature with ** means that only one option listed under the feature can be configured on selected models. Please refer to the model configuration for specific information.
- Feature with *** means that one or more options listed under the feature can be configured on selected models. Please refer to the model configuration for specific information.
- Lenovo reserves the right to change specifications or other product information without notice. Lenovo is not responsible for photographic or typographical errors. **LENOVO PROVIDES THIS PUBLICATION "AS IS", WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.** Some jurisdictions do not allow disclaimer of express or implied warranties in certain transactions, therefore this disclaimer may not apply to you.
- The specifications on this page may not be available in all regions, and may be changed or updated without notice.



intel




intel



intel



intel



intel



intel