

# Product data sheet

Specifications



## APC NetShelter SX Server Rack Gen 2, 42U, 1991H x 750W x 1200D mm, with Sides, Black [TAA]

AR3350B2

### Main

Product or Component Type	Rack enclosure
Number of rack unit	42U
Provided equipment	Baying hardware Key(s) Keyed-alike doors and side panels Leveling feet Mounting Hardware Pre-installed casters Side Panels

### Physical

Height	78.4 in (1991 mm)
Width	29.5 in (750 mm)
Depth	47.2 in (1200 mm)
Product Weight	347.29 lb(US) (157.53 kg)
Color	Black
Mounting preference	No preference
Mounting Mode	Not rack-mountable
Maximum Mounting Depth	41.3 in (1048 mm)
Minimum Mounting Depth	11.3 in (286 mm)
Rack Width	19"
Marking	14 gauge EIA mounting rail 16 gauge front door 16 gauge post 18 gauge rear door 18 gauge roof 18 gauge side panels
Permanent permissible load	2250 lb(US) (1020.6 kg) dynamic 4000 lb(US) (1814.4 kg) static

### Conformance

Standards	UL 2416 EIA-310E
-----------	---------------------

### Ordering and shipping details

GTIN	731304642213
Country of origin	CN

### Packing Units

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

---

<b>Unit Type of Package 1</b>	PCE
<b>Nbr. of units in pkg.</b>	1
<b>Package 1 Height</b>	83.8 in (212.8 cm)
<b>Package 1 Width</b>	33.6 in (85.3 cm)
<b>Package 1 Length</b>	52.09 in (132.3 cm)
<b>Package weight(Lbs)</b>	403.84 lb(US) (183.18 kg)

---

## Compliance

---

<b>Compliance</b>	TAA Compliant BAA Compliant via COTS
-------------------	---

## Contractual warranty

---

<b>Warranty (in months)</b>	60
-----------------------------	----



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Environmental footprint

Total lifecycle Carbon footprint	1 168 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	978 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	54 kg CO2 eq.
Carbon footprint of the installation phase [A5]	21 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	0 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	439 kg CO2 eq.
Environmental Disclosure	<a href="#">Product Environmental Profile</a>

### Use Better

#### Materials and Substances

Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	<a href="#">Compliant</a>
REACH Regulation	<a href="#">Free of Substances of Very High Concern above the threshold</a>

### Use Longer

#### Lifetime extension

Repair	No
--------	----

### Use Again

#### Repack and remanufacture

Recyclability potential, in %	97
Circularity Profile	No need of specific recycling operations
Take-back	No

Technical Illustration

Dimensions

---

